System Support Addendum

PRODUCT NAME: VAX 2780/3780 Protocol Emulator, Version 1.7 **SSA 25.07.14-A**

HARDWARE REQUIREMENTS

The following table shows the supported configurations of VAX system and synchronous communications interface(s) and the maximum number of these interfaces:

VAX System	Communications Interface	Maximum No. of Interfaces
MicroVAX I	DPV11	1
VAXstation II	DSV11	1 (2 lines)
MicroVAX II	DPV11 DSV11	2 2 (4 lines)
MicroVAX 3300 MicroVAX 3400	DSV11-S	2 (4 lines)
MicroVAX 3500 MicroVAX 3600		
DPV11-S DSV11	2 2 (4 lines)	
VAXstation 3200 VAXstation 3500	DSV11	1 (2 lines)
VAX-11/725 VAX-11/730	DMF32	1
VAX-11/750	DUP11 DMF32	2 2
VAX-11/780 VAX-11/785	DUP11 DMF32	2 2
VAX 6210 VAX 6220 VAX 6230 VAX 6240	DMB32	4
VAX 8200 VAX 8250		
DMB32 DMF32* DUP11*	2 2 1	
VAX 8300 VAX 8350		
DMB32 DMF32* DUP11*	2 2 1	
VAX 8500 VAX 8530 VAX 8550	DMB32	4
VAX 8600 VAX 8650	DUP11 DMF32	2 2
VAX 8700	DMB32	4
VAX 8800 VAX 8810 VAX 8820 VAX 8830 VAX 8840 VAX 8974 VAX 8978	DMB32	4

* Requires use of a DWBUA UNIBUS to BI Bus Adapter

Note that a DSV11 synchronous communications interface supports two separate communication lines.

Not supported: MicroVAX 2000, VAXstation I, VAXstation 2000, VAXstation 8000, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAX-11/782

digital software

January 1989

AE-MH87A-TE

Processor Restrictions

Where more than one type of interface is shown in the table above, only ONE type of interface should be selected. Mixed configurations are not supported.

MicroVAX I system supports a maximum line speed of 4800 baud. Maximum supported line speed for other configurations is 9600 baud.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation: 650 blocks (325K bytes)

Disk space required for use (permanent): 600 blocks (300K bytes)

These counts refer to the disk space required on the system disk. The sizes are approximations; actual sizes may vary depending on the user's system environment, configuration, and software options selected.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster configuration without restrictions. The HARDWARE REQUIREMENTS sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

Cluster licenses are available for this product.

SOFTWARE REQUIREMENTS

VMS Operating System V5.0

VAX WAN Device Drivers Kit V1.0

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Programming Support
- System Programming Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System (SPD 25.01.xx).

OPTIONAL SOFTWARE

EDE-W Document Exchange V1.2

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Disk: RX33 Floppy Diskette

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

ORDERING INFORMATION

Software Licenses: QL-111A*-**
Software Media: QA-111A*-**
Software Documentation: QA-111AA-GZ
Software Product Services: QT-111A*-**

* Denotes variant fields. For additional information on available licenses, services and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your local DIGITAL office for the most up-to-date information.