System Support Addendum

PRODUCT NAME: VAX COBOL, Version 4.4 **SSA 25.04.22-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310

VAX 4000 Model 200
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350,
VAX 8500, VAX 8530, VAX 8550, VAX 8600,
VAX 8650, VAX 8700, VAX 8800, VAX 8810,
VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000 Model 400 Series

VAX-11/730, VAX-11/750, VAX-11/780,
VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000,
MicroVAX 3100, MicroVAX 3300,
MicroVAX 3400, MicroVAX 3500,
MicroVAX 3600, MicroVAX 3800,
MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300,
VAXserver 3400, VAXserver 3500,
VAXserver 3600, VAXserver 3602,
VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200
VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-210,
VAXserver 6000-310, VAXserver 6000-320,
VAXserver 6000-410, VAXserver 6000-420,
VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

The VAX-11/780 must have the hardware engineering change order (ECO) status of system level 4 or higher.

The VAX-11/730 must have the writeable control store (WCS) status of system level 50 or higher.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required during installation:	7,000 blocks (3.6M bytes)
Disk space required for use (permanent):	4,000 blocks (2.1M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

Memory Requirements for DECwindows Support

The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 8MB.

digital™

February 1991
AE-LT29E-TE

OPTIONAL HARDWARE

A VT100 family, VT200 family, VT300 family, VT52 or Professional terminal emulating a VT100 is required for the screen handling extensions to the ACCEPT and DISPLAY statements.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.0 - V5.4

For Workstations Running VWS:

VMS Operating System V5.0 - V5.4
VMS Workstation Software V4.2 - V4.3

For Workstations Running DECwindows:

VMS Operating System V5.1 - V5.4 (and necessary components of VMS DECwindows)

VAX COBOL supports a DECwindows compiler interface for compile qualifier selection on workstations. This interface is accessible from FileView.

This product may run in either of the following ways:

- Stand-alone execution - running the X11 display server and the client application on the same machine.
- Remote execution - running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately on versions prior to V5.4. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

- VMS DECwindows Compute Server (base kit; provides runtime support)
- VMS DECwindows Programming Support
- VMS DECwindows Device Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server (runtime support)
- VMS DECwindows Programming Support
- VMS DECwindows Device Support

For remote execution, the following DECwindows components must be installed on the machine:

Server Machine

- VMS DECwindows Compute Server (runtime support)
- VMS DECwindows Device Support

Client Machine

- VMS DECwindows Compute Server (runtime support)
- VMS DECwindows Programming Support

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Programming Support

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

Certain versions of these products depend upon a specific version of the operating system. Please refer to the System Software Addendum of the product in question to determine which version is necessary.

In order to use the following, VAX Language-Sensitive Editor/Source Code Analyzer V3.1 is required:

- /DESIGN qualifier
- /ANALYSIS_DATA qualifier
- VAX Language-Sensitive Editor component

Note: VAX Language-Sensitive Editor/Source Code Analyzer V3.1 is available individually or in VAXset V10.0

VAX COBOL Data Manipulation Language features require:

For Systems Running VMS Operating System V5.0 - V5.1:

- VAX DBMS V4.0
- VAX CDD/Plus V4.0 - V4.2A

For Systems Running VMS Operating System V5.2 - V5.4:

- VAX DBMS V4.1 or
- VAX DBMS V4.2 (VMS V5.3 - V5.4 only)
- VAX CDD/Plus V4.2A

VAX COBOL COPY FROM DICTIONARY feature requires:

For Systems Running VMS Operating System V5.0 - V5.3:

- VAX CDD/Plus V4.1A

For Systems Running VMS Operating System V5.2 - V5.4:

- VAX CDD/Plus V4.2A

VAX COBOL Vertical Forms Printing features require:

- VMS Operating System V5.2 - V5.4

DECwindows Compile Interface requires:

- VMS Operating System V5.1 - V5.4

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-099A*-**
Software Media: QA-099A*-**
Software Documentation: QA-099AA-GZ
Software Product Services: QT-099A*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, VAX COBOL, CI, VAX, MicroVAX, VAXstation, VAXserver, VAXcluster, VMS, VAX CDD/Plus, RSX, DBMS, VMS, DECwindows, and VT are trademarks of Digital Equipment Corporation.