System Support Addendum

PRODUCT NAME: DECimage Character Recognition Services for VMS, Version 1.0 **SSA 34.24.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310

VAX 4000 Model 200,
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000 Model 400 Series

VAX–11/730, VAX–11/750, VAX–11/780, VAX–11/785

MicroVAX: MicroVAX II, MicroVAX 2000,
MicroVAX 3100, MicroVAX 3300,
MicroVAX 3400, MicroVAX 3500,
MicroVAX 3600, MicroVAX 3800,
MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200,
VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX–11/725, VAX–11/782, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX and VAXstation systems.

A recommended minimum configuration is based on the VAXstation and includes:

VAXstation 3100

- At least 24MB of memory required
- One VR150 or 262 (monochrome), or VR160 or 290 (color) monitor
- One RZ55 for mass storage
- One TZ50 cartridge tape drive (for software installation)
- One mouse, one keyboard

Any other hardware required for product use:

- MD300, MD410, or MD400 Scanner for scanning images
- Digital LAN Adapter for remote systems communication

digital™

May 1991
AE-PFL9A-TE

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	8,000 blocks (4.1 Mbytes)
Disk space required for use (permanent):	3,000 blocks (1.6 Mbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.4 (and necessary components of VMS DECwindows)

This product may run in either of the following ways:

- Stand-alone execution — running the X11 display server and the client application on the same machine.
- Remote execution — running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes IMG$SHRLIB.EXE for image runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support*

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server
- DECwindows Programming Support*

* Required for application development; not required to run application.

VMS Tailoring

For VMS V5.x systems, the following classes of VMS are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- System Programming Support
- Utilities
- Miscellaneous Files

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

DECimage Application Services for VMS, V2.0 (required for developing applications)

OPTIONAL SOFTWARE

DECimage Scan Software for VMS V2.1

DECwrite for VMS V1.1

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

TK50 Streaming Tape, 9-track 1600 BPI Magtape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-GJFA*-**

Software Media and Documentation: QA-GJFAA-H*

Software Documentation: QA-GJFAA-GZ

Software Product Services: QT-GJFA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for most up-to-date information.

® PostScript is a registered trademark of Adobe Systems, Incorporated.

™ The DIGITAL Logo, CI, DEC, DECimage, DECwindows, DECwrite, MicroVAX, TK, VAX, VAXcluster, VAXft, VAXserver, VAXstation, VMS, VR150, and VR160 are trademarks of Digital Equipment Corporation.