System Support Addendum

PRODUCT NAME: Digital Cartridge Server Component for VMS, Version 1.0 **SSA 33.59.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX:	VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series, VAX 6000 Model 500 Series
	VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840
	VAX 9000-210, VAX 9000 Model 400 Series
	VAX-11/750, VAX-11/780, VAX-11/785

Processors Not Supported

VAX:	VAXft 3000-310
	VAX 4000 Model 200, VAX 4000 Model 300
	VAX-11/725, VAX-11/730, VAX-11/782
MicroVAX:	MicroVAX family of processors
VAXstation:	VAXstation family of processors
VAXserver:	VAXserver family of processors

The VAX processor used must be sufficiently capable of handling both the installation and daily operations of the Digital Cartridge Server Component (DCSC) as well as any customized applications and the VMS/ULTRIX Connection software.

The VAX processor must be physically connected to either an HSC40 or HSC70 to provide a data path through the TC44-AA/BA controller boards for tape cartridge read and write functions.

Processor Restrictions:

A TK50 or 9-track 1600 BPI Magtape (PE) Tape Drive is required for DCSC installation.

A connection to a HSC40 or HSC70 is required for cartridge read/write operations.

An Ethernet connection is required for each processor that uses the DCSC. That processor must support the Ethernet boards supported by Version 1.3 of the VMS/ULTRIX Connection software.

Other Hardware Required:

TC44-AA/BA

Digital Equipment Corporation VT220, VT240, VT320, or VT340 terminal to use the DCSC utilities and user interface.

StorageTek® 4400 Automated Cartridge System and associated software.

Disk Space Requirements (Block Cluster Size = 1):

The following counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

Disk space required for installation:	9,000 blocks (4.61 Mbytes)
Disk space required for use (permanent):	8,000 blocks (4.10 Mbytes)

The minimum memory supported is 32 Mbytes. However, increasing the memory capability improves the performance of this software. The memory size suggested for most typical hardware configurations is at least 32 Mbytes.

digital™

February 1991
AE-PETZA-TE

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals:

VMS Operating System V5.4
VMS/ULTRIX Connection V1.3

For Workstations Running VWS:

VMS Operating System V5.4
VMS Workstation Software V4.3
VMS/ULTRIX Connection V1.3

For Workstations Running DECwindows:

VMS Operating System V5.4 (and necessary components of VMS DECwindows)
VMS/ULTRIX Connection V1.3

A DECwindows interface is not supported.

VMS Tailoring:

The following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-YWNA9-AA
Software Media: QA-YWNAA-H*
Software Documentation: QA-YWNAA-GZ
Software Product Services: QT-YWNA9-AA

* Denotes variant fields. For additional information on available licenses, services, and media, see the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® StorageTek is a registered trademark of Storage Technology Corporation.

™ The DIGITAL Logo, DEC, DECwindows, MicroVAX, ULTRIX, VAX, VAXcluster, VAXft, VAXserver, VAXstation, VMS, and VT320 are trademarks of Digital Equipment Corporation.