System Support Addendum

PRODUCT NAME: DECdx/VMS, Version 1.2 **SSA 26.36.05-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX:	VAX 6210, VAX 6220, VAX 6230, VAX 6240, VAX 6310, VAX 6312, VAX 6320, VAX 6330, VAX 6333, VAX 6340, VAX 6350, VAX 6360 VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978 VAX-11/725, VAX-11/730, VAX-11/750, VAX-11/780
MicroVAX:	MicroVAX II, MicroVAX 2000, MicroVAX 3300/3400, MicroVAX 3500, MicroVAX 3600
VAXstation:	VAXstation II, VAXstation 2000, VAXstation 3100, VAXstation 3200, VAXstation 3500, VAXstation 8000
VAXserver:	VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 6210/6220, VAXserver 6310/6320

Processors Not Supported

VAXstation I, VAX-11/782, MicroVAX I

VMS system must also have an available local or remote serial full duplex asynchronous terminal line supported by the operating system.

Any valid DECmate II, III, with WPS-8 communication option enabled. Each additional DECmate system simultaneously connected to the host requires its own line.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:
3,650 blocks
(1868.8K bytes)

Disk space required for use (permanent):
500 blocks
(256K bytes)

These counts refer to disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration and software options selected.

OPTIONAL HARDWARE

None

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The HARDWARE REQUIREMENTS sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V4.7 - V5.0

MicroVMS Operating System V4.7

DECmate II/III WPS, Version 2.0 at a minimum of V2.0 (with communications software activated)

VMS Tailoring

For VMS 5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Secure User's Environment
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

MicroVMS Tailoring

For MicroVMS 4.x systems, the following components of MicroVMS are required for full functionality of this layered product:

- Base System
- Secure User's Environment

May 1989
AE-MM39B-TE

OPTIONAL SOFTWARE

None

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from minimum requirements for the current version.

DISTRIBUTION MEDIA

Disk: RX01 Floppy Diskette

Tape: TK50 Streaming Tape, TU58 DECtape II Cartridge, 9-track 1600 BPI Magtape (PE)

ORDERING INFORMATION

Software License: QL-708A*-**
Software Media: QA-708A*-**
Software Documentation: QA-708AA-GZ
Software Product Services: QT-708A*-**

* Denotes variant fields. For additional information on available licenses, services and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your local DIGITAL office for the most up-to-date information.

May 1989
AE-MM39B-TE