System Support Addendum

PRODUCT NAME: DECintact, Version 2.0 **SSA 29.58.04-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 4000 Model 200,
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000 Model 210,
VAX 9000 Model 400 Series

VAXft 3000 Model 310

VAX–11/730, VAX–11/750, VAX–11/780, VAX–11/785

MicroVAX: MicroVAX II, MicroVAX 2000,
MicroVAX 3100, MicroVAX 3300,
MicroVAX 3400, MicroVAX 3500,
MicroVAX 3600, MicroVAX 3800,
MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200,
VAXserver 4000 Model 300

VAXserver 6000 Model 210,
VAXserver 6000 Model 220,
VAXserver 6000 Model 310,
VAXserver 6000 Model 320,
VAXserver 6000 Model 410,
VAXserver 6000 Model 420,
VAXserver 6000 Model 510,
VAXserver 6000 Model 520

Processors Not Supported

MicroVAX I, VAXstation I, VAX–11/725, VAX–11/782, VAXstation 8000

Processor Restrictions:

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	52,000 blocks (26,624 Kbytes)
Disk space required for use (permanent):	46,000 blocks (23,552 Kbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

- VT100, VT200, VT300, VT400 (in VT200 emulation mode) terminals.
- Any device supported by the prerequisite software.

digital™

July 1991
AE-LT11E-TE

- Any DECNET hardware as required by the distributed DECintact environment, including VAX front-end processors in conjunction with the DECintact product's operation in a host VAX orVAXcluster system.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (SPD 29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.4

For Workstations Running VWS:

VMS Operating System V5.4
VMS Workstation Software V4.3

In addition to these requirements, DECnet–VAX V5.4 is required for Remote-Access Option.

VMS Tailoring

For VMS V5.x the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- System Programming Support
- Secure User's Environment
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

- DECforms V1.3
- DECnet–VAX V5.4
- DEctrace for VMS V1.1
- VAX BASIC V3.4
- VAX C V3.2
- VAX COBOL V4.4
- VAX CDD/Plus V4.3
- VAX DBMS V4.2
- VAX DEC/MMS V2.3-V2.5
- VAX DEC/Test Manager V2.3-V3.0
- VAX FORTRAN V5.5
- VAX Language-Sensitive Editor V3.1
- VAX Pascal V4.1
- VAX PL/I V3.4
- VAX Rdb/VMS V4.0
- VMS Volume Shadowing V5.4

Certain versions of these products depend upon a specific version of the operating system. Please see the System Support Addendum of the product in question to determine which version is required.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

9 track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

The software documentation for this product is also available as part of the VMS Online Documentation Library on CDROM.

ORDERING INFORMATION

Development Option

Software Licenses: QL-VF1A*-**
Software Media: QA-VF1A*-**
Software Documentation: QA-VF1AA-GZ
Software Product Services: QT-VF1A*-**

Run-Time Option

Software Licenses: QL-VF2A*-**
Software Media: QA-VF2A*-**
Software Documentation: QA-VF2AA-GZ
Software Product Services: QT-VF2A*-**

Remote-Access Option

Software Licenses: QL-VF3A*-**
Software Media: QA-VF3A*-**
Software Documentation: QA-VF3AA-GZ
Software Product Services: QT-VF3A*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, CI, DEC, DECdtm, DECforms, DECtrace, DECnet, DECnet–VAX, DECintact, MicroVAX, VAX, VAX BASIC, VAX C, VAX CDD/Plus, VAX COBOL, VAX DBMS, VAX FORTRAN, VAX Pascal, VAX RMS, VAXcluster, VAXft, VAXserver, VAXstation, VMS, VT100, VT200, and VT300 are trademarks of Digital Equipment Corporation.