VMS

DECwindows V2.1 Language Variants Installation Guide

AA-PAJHB-TE

October 1990

This guide describes how to install VMS DECwindows V2.1 Language Variants on the VMS Operating System.

Revision Information:	This is a revised manual.
Operating System:	VMS V5.4
Software Version:	VMS DECwindows V2.1 Language Variants

digital equipment corporation
maynard, massachusetts

October 1990

The information in this document is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation. Digital Equipment Corporation assumes no responsibility for any errors that may appear in this document.

The software described in this document is furnished under a license and may be used or copied only in accordance with the terms of such license.

No responsibility is assumed for the use or reliability of software on equipment that is not supplied by Digital Equipment Corporation or its affiliated companies.

Restricted Rights: Use, duplication, or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013.

© Digital Equipment Corporation October 1990.

All Rights Reserved.
Printed in U.K.

The following are trademarks of Digital Equipment Corporation:

CDA	LiveLink	VAXcluster
DDIF	LN03	VAX RMS
DEC	MASSBUS	VAXserver
DECnet	MicroVAX	VAXstation
DECUS	PrintServer 40	VMS
DECwindows	Q-bus	VT
DECwrite	ReGIS	XUI
DEQNA	ULTRIX	
DIGITAL	UNIBUS	
GIGI	VAX	

The following is a third-party trademark:

PostScript is a registered trademark of Adobe Systems, Inc.

Contents

Preface v

1 Preparing to Install VMS DECwindows V2.1 Language Variants

1.1 Prerequisite Software 1–1
1.2 Installation Procedure Requirements 1–2
1.2.1 Time 1–2
1.2.2 Privileges 1–2
1.2.3 Disk Space 1–2
1.2.4 VMSINSTAL Requirements 1–3
1.2.5 Backing Up Your System Disk 1–4
1.2.6 VMS DECwindows V2.1 Language Variant Requirements 1–4

2 Installing VMS DECwindows V2.1 Language Variants

2.1 General Information 2–1
2.1.1 Accessing the Online Release Notes 2–1
2.1.2 Determining the Files Added to the System 2–2
2.1.3 Installation Verification Procedure (IVP) 2–2
2.1.4 Aborting the Installation 2–2
2.2 The Installation Procedure 2–2
2.2.1 Invoking VMSINSTAL 2–3
2.2.2 Installation Questions 2–4
2.2.3 Informational Messages 2–6
2.2.4 Completing the Installation Procedure 2–7
2.3 Error Recovery 2–7

3 After Installing VMS DECwindows V2.1 Language Variants

3.1 Editing the System Startup File 3–1
3.2 Amending the LIBRARY.DECW$BOOKSHELF file 3–2
3.3 Checking the Installation 3–3
3.4 Invoking and Running a Language Variant 3–3
3.5 Determining and Reporting Problems 3–4

A Sample Installation

B Files and Logical Names Installed on Your System

B.1 Directories B–1
B.2 Files B–2
B.3 Logical Names B–5

Index

Tables

1–1 Disk space requirements 1–2
2–1 Release Notes 2–2
2–2 Installation names 2–3
3–1 Parameter values 3–2
3–2 Language variant bookshelf files 3–3
B–1 Directory values B–2
B–2 New files installed B–3
B–3 Logical name values B–6

Preface

The VMS DECwindows V2.1 Language Variants are translated versions of the VMS DECwindows V2.1 user interface, online help and online documentation. The language variants are installed on top of the American English version of VMS DECwindows V2.1.

The following language variants are covered by this guide:

Dutch
French
French Canadian
German
Italian
Norwegian
Swedish
Swiss French
Swiss German
Swiss Italian

Purpose of This Guide

This guide describes how to install the VMS DECwindows V2.1 Language Variants on the VMS operating system. You must read the whole guide before you start to install the product.

Who Should Use This Guide

This guide is intended for VMS system managers or others who are responsible for installing system software. To install the VMS DECwindows V2.1 Language Variants, you must have access to a privileged account, such as the SYSTEM account. You must also be familiar with the VMS installation procedure, VMSINSTAL.

Keep this document with your distribution kit. You will need it if for any reason you have to reinstall any of the VMS DECwindows V2.1 Language Variants.

Structure of This Guide

This guide has three chapters and two appendices.

Chapter 1 describes the prerequisites and preparations for the installation.

Chapter 2 describes the installation procedure.

Chapter 3 describes what to do after the installation.

Appendix A lists a sample installation procedure.

Appendix B lists the files and logical names which are created on your system during the installation.

For More Information

For more information about installing products on VMS systems, refer to your processor-specific Installation/Operations guide.

For more information about VMSINSTAL, refer to the *VMS System Manager's Manual*.

For more information on DECwindows, refer to the following manuals:

- *VMS DECwindows User's Guide*
- *VMS DECwindows Desktop Applications Guide*

1

Preparing to Install VMS DECwindows V2.1 Language Variants

This chapter discusses the preparations and requirements for installing the VMS DECwindows V2.1 Language Variants.

Your bill of materials (BOM) and indented bills report (BIL) specify the number and contents of your media. Be sure to verify the contents of your kit using this information. If your kit is damaged, or if you find that parts of it are missing, contact your Digital representative.

The VMS DECwindows V2.1 Language Variants provide online Release Notes. Digital strongly recommends that you read the Release Notes before proceeding with the installation. For information on accessing the online Release Notes, refer to Section 2.1.1.

You can install VMS DECwindows V2.1 Language Variants on a standalone VAX and on a VAXcluster.

1.1 Prerequisite Software

This section discusses the software you must have installed on your system before you install any VMS DECwindows V2.1 Language Variants. The System Software Addendum (SSA) contains a complete list of prerequisite software and the required version numbers. The SSA is part of the Software Product Description (SPD).

You must have VMS V5.4 and the American English version of VMS DECwindows V2.1 installed and running on your system before you install the VMS DECwindows V2.1 Language Variants.

Note *All VMS DECwindows V2.1 Language Variants run on VMS V5.4 releases only.*

1.2 Installation Procedure Requirements

The following sections discuss various requirements for installing the VMS DECwindows V2.1 Language Variants.

1.2.1 Time

The installation takes approximately 10 minutes, depending on your type of media and your system configuration.

1.2.2 Privileges

To install the VMS DECwindows V2.1 Language Variants, you must be logged in to an account that has SETPRV or at least the following privileges:

- CMKRNL
- WORLD
- SYSPRV

Note that VMSINSTAL turns off BYPASS privilege at the start of the installation.

1.2.3 Disk Space

Installing one of the VMS DECwindows V2.1 Language Variants requires a certain amount of free disk storage space during and after the installation. Table 1–1 summarizes the storage requirements:

Table 1–1 Disk space requirements

Language Variant Kit	Blocks During Installation	Blocks After Installation
Dutch	7,000	7,000
French	7,000	7,000
French Canadian	7,000	7,000
German	7,000	7,000
Italian	7,000	7,000
Norwegian	7,000	7,000
Swedish	7,000	7,000
Swiss French	7,000	7,000
Swiss German	7,000	7,000
Swiss Italian	7,000	7,000

To determine the number of free disk blocks on the current system disk, enter the following command at the DCL prompt:

```
$  SHOW DEVICE SYS$SYSDEVICE
```

1.2.4 VMSINSTAL Requirements

When you invoke VMSINSTAL, it checks the following:

- Whether you have set your default device and directory to SYS$UPDATE
- Whether you are logged in to a privileged account
- Whether you have adequate quotas for installation
- Whether DECnet is running
- Whether any users are logged in to the system

Note that VMSINSTAL requires the installation account to have a minimum of the following quotas:

ASTLM = 24
BIOLM = 18
BYTLM = 18,000
DIOLM = 18
ENQLM = 30
FILLM = 20

Account quotas are stored in the file SYSUAF.DAT. Use the VMS Authorize Utility to verify and change account quotas. First set your directory to SYS$SYSTEM and then run AUTHORIZE:

```
$  SET DEFAULT SYS$SYSTEM
$  RUN AUTHORIZE
UAF>
```

At the UAF> prompt, use the SHOW command with an account name to check a particular account. For example:

```
UAF>  SHOW SYSTEM
```

To change a quota, use the MODIFY command. MODIFY has the following format:

MODIFY account-name /quota-name=NNN

The following example changes the FILLM quota for the SYSTEM account and then exits from the utility:

```
UAF>  MODIFY SYSTEM /FILLM=30
UAF>  EXIT
```

After you exit from the utility, the system displays messages indicating whether or not changes were made. Once the changes have been made, you must log out and log in again for the new quotas to take effect.

For more information on modifying account quotas, refer to the description of the Authorize Utility in the *VMS System Management Documentation Subkit*.

If VMSINSTAL detects any problems during the installation, it notifies you and asks if you want to continue the installation. In some instances, you can enter YES to continue. To stop the installation process and correct the situation, enter NO or press Return. Then correct the problem and restart the installation.

1.2.5 Backing Up Your System Disk

At the beginning of the installation, VMSINSTAL asks if you have backed up your system disk. Digital recommends that you do a system disk backup before installing any software.

Use the backup procedures that are established at your site. For details on performing a system disk backup, refer to the section on the Backup Utility in the *VMS System Management Documentation Subkit*.

1.2.6 VMS DECwindows V2.1 Language Variant Requirements

During the installation of VMS DECwindows V2.1 Language Variants, the product checks that you have VMS V5.4 and the American English version of VMS DECwindows V2.1 installed and running on your system. If you do not have VMS V5.4 and VMS DECwindows V2.1, an error message will be displayed and the installation procedure will abort.

The product also checks that you have sufficient disk space available for the installation. The disk space for each language variant is listed in Table 1–1. If you do not have enough disk space, an error message will be displayed and the installation procedure will abort.

2

Installing VMS DECwindows V2.1 Language Variants

This chapter describes how to install VMS DECwindows V2.1 Language Variants.

Section 2.2 contains a step-by-step description of the installation procedure.

2.1 General Information

This section includes information about the following topics:

- Accessing online Release Notes.
- Determining which files have been added to your system
- Aborting the installation.

2.1.1 Accessing the Online Release Notes

The VMS DECwindows V2.1 Language Variants provide online Release Notes. You must specify OPTIONS N when you invoke VMSINSTAL to see the question about online Release Notes. This question comes near the beginning of the installation. This is described in Section 2.2.1.

You must review the Release Notes in case they contain any information about last minute changes in the installation procedure. If you have already reviewed the Release Notes during a previous installation, you do not need to specify OPTIONS N.

Once the language variant has been installed, the Release Notes are located in the directory SYS$HELP: in one of the files listed in Table 2–1.

Table 2–1 Release Notes

Language variant	Release Notes file
Dutch	DECWNL_NL021.RELEASE_NOTES
French	DECWFR_FR021.RELEASE_NOTES
French Canadian	DECWFR_CA021.RELEASE_NOTES
German	DECWDE_DE021.RELEASE_NOTES
Italian	DECWIT_IT021.RELEASE_NOTES
Norwegian	DECWNO_NO021.RELEASE_NOTES
Swedish	DECWSV_SE021.RELEASE_NOTES
Swiss French	DECWFR_CH021.RELEASE_NOTES
Swiss German	DECWDE_CH021.RELEASE_NOTES
Swiss Italian	DECWIT_CH021.RELEASE_NOTES

2.1.2 Determining the Files Added to the System

During the installation, some directories and files are created on your system. These directories and files are listed in Appendix B.

2.1.3 Installation Verification Procedure (IVP)

The installation procedure for the VMS DECwindows V2.1 Language Variants does not include an Installation Verification Procedure (IVP).

This is because the VMS DECwindows V2.1 Language Variants consist only of the user interface and online help.

As there is no IVP, Digital recommends that you check after the installation that the files have been installed correctly and that the language variant runs correctly. Refer to Section 3.3 and Section 3.4 for more information.

2.1.4 Aborting the Installation

To abort the installation procedure at any time, press CTRL/Y. When you press CTRL/Y, the installation procedure deletes all files it has created up to that point and exits. You can then start the installation again.

2.2 The Installation Procedure

The installation procedure consists of a series of questions and informational messages.

2.2.1 Invoking VMSINSTAL

To start the installation, invoke the VMSINSTAL command procedure from a privileged account, such as the SYSTEM account. VMSINSTAL is in the SYS$UPDATE directory. You use the following syntax to invoke VMSINSTAL:

```
@SYS$UPDATE:VMSINSTAL saveset-name device-name OPTIONS N
```

saveset-name

The installation name for the component. For the VMS DECwindows V2.1 Language Variants, use the installation names shown in Table 2–2.

Table 2–2 Installation names

Language variant	Installation name
Dutch	DECWNL_NL021
French	DECWFR_FR021
French Canadian	DECWFR_CA021
German	DECWDE_DE021
Italian	DECWIT_IT021
Norwegian	DECWNO_NO021
Swedish	DECWSV_SE021
Swiss French	DECWFR_CH021
Swiss German	DECWDE_CH021
Swiss Italian	DECWIT_CH021

device-name

The name of the device on which you plan to mount the media. For example, MTA0: is a device name for a tape drive.

It is not necessary to use the console drive for this installation. However, if you do use the console drive, once the installation is complete, you should replace any media you removed.

OPTIONS N

An optional parameter that indicates you want to see the Release Notes question. If you do not include the OPTIONS N parameter, VMSINSTAL does not ask you about the Release Notes. You must review the Release Notes before proceeding with the installation in case they contain new information about the installation.

Note that there are several other options you can select when you invoke VMSINSTAL. Refer to the VMS documentation on software installation in the *VMS System Management Subkit* for information on these options. If you specify more than one option, separate the options with commas, for example, OPTIONS A,N.

The following example invokes VMSINSTAL to install the Dutch VMS DECwindows language variant from tape drive MTA0: and shows the system response.

```
$  @SYS$UPDATE:VMSINSTAL DECWNL_NL021 MTA0: OPTIONS N

       VAX/VMS Software Product Installation Procedure V5.4


It is 16-SEP-1991 at 11:44.

Enter a question mark (?) at any time for help.
```

If you do not supply either the product name or the device name, VMSINSTAL prompts you for this information later in the installation procedure. If you do not specify any installation options, VMSINSTAL also prompts you to enter options.

2.2.2 Installation Questions

This section discusses the questions that appear during the installation. Appendix A contains a sample installation procedure which shows how the questions can be answered.

Each question in the installation is marked with an asterisk (*) at the beginning of the line. Some questions show the default response in brackets, for example [YES] or [Y]. To use the default response, press Return.

1 System backup

VMSINSTAL asks if you are satisfied with your system backup. You should always back up your system disk before performing an installation. If you are satisfied with the backup of your system disk, press Return. Otherwise, enter NO to discontinue the installation. After you back up your system disk, you can restart the installation.

```
* Are you satisfied with the backup of your system disk [YES]?
```

2 Options

If you did not specify any options on the command line, VMSINSTAL asks you to enter the installation options you want to use. Press Return if you do not want any options.

```
* Enter installation options you wish to use (none):
```

3 Mounting the media

You must now mount the first distribution volume on the device you specified when you invoked VMSINSTAL. The device name appears in the line preceding the question. VMSINSTAL then asks you if you are ready to continue with the installation.

If you respond YES, to indicate that you are ready, VMSINSTAL displays a message that the media containing the language variant has been mounted on the specified device and that the installation has begun. For example:

```
Please mount the first volume of the set on MTA0:.
* Are you ready?  YES
%MOUNT-I-MOUNTED, DECWNL_NL021 MOUNTED ON _$$MTA0:
The following products will be processed:
  DECWNL_NL V2.1

    Beginning installation of DECWNL_NL V2.1 at 11:45

%VMSINSTAL-I-RESTORE, Restoring product saveset A...
```

If you entered the wrong device name when you invoked VMSINSTAL and need to restart the installation, enter NO in response to the ''Are you ready?'' question. To abort the installation for other reasons, press CTRL/Y.

4 Release Notes

If you specified OPTIONS N when you invoked VMSINSTAL or when VMSINSTAL prompted you to enter an option, you are now asked to choose one of the four options for reviewing the Release Notes.

```
Release notes included with this kit are always copied to SYS$HELP.

Additional Release Notes Options:

 1.  Display release notes
 2.  Print release notes
 3.  Both 1 and 2
 4.  None of the above

* Select option [2]:
```

If you select option 1, VMSINSTAL displays the Release Notes immediately on the console terminal. You can terminate the display at any time by pressing CTRL/C.

If you select option 2, VMSINSTAL prompts you for the name of the print queue that you want to use:

```
* Queue name [SYS$PRINT]:
```

You can press Return to send the file to the default output print device or you can enter another queue name.

If you select option 3, VMSINSTAL displays the Release Notes immediately on the console terminal and then prompts you for a queue name for the printed version.

Select option 4 if you have already reviewed the Release Notes and are restarting the installation.

5 Continuing the installation

The installation procedure now asks if you want to continue the installation. To continue, enter YES. Otherwise, press Return. In either case, the Release Notes are copied to a file in the SYS$HELP directory. For example:

```
* Do you want to continue the installation [NO]?:  YES
%VMSINSTAL-I-RELMOVED, The product's release notes have been
                              successfully moved to SYS$HELP.
%DECWNL_NL-I-INTRO, Installing VMS DECwindows Dutch language support.
```

The Release Notes for each language variant are located in one of the files listed in Table 2–1 in Section 2.1.1.

6 Choosing to purge files

You have the option to purge files from any previous versions of VMS DECwindows Language Variants that are superseded by this installation. Purging is recommended; however, if you need to keep files from the previous version, enter NO in response to the question.

```
* Do you want to purge files replaced by this installation [YES]?
```

2.2.3 Informational Messages

At this point, the installation procedure displays a number of informational messages that report on the progress of the installation. The installation procedure does not ask any further questions.

If the installation procedure has been successful up to this point, VMSINSTAL moves the new or modified files to their target directories, updates help files, and updates DCL tables, if necessary. If you chose to have files purged, that work is done now.

The following messages are displayed:

```
%DECWNL_NL-I-NOMORE, No more questions will be asked.
%DECWNL_NL-I-TIME, This installation will take approximately 10
                   minutes
%VMSINSTAL-I-RESTORE, Restoring product save set B ...
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[DECW$DEFAULTS.SYSTEM.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSHLP.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSHLP.EXAMPLES.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSLIB.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSMSG.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[VUE$LIBRARY.SYSTEM.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[DECW$DEFAULTS.USER.NL_NL]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[VUE$LIBRARY.USER.NL_NL]
%VMSINSTAL-I-MOVEFILES, files will now be moved to their
                        target directories...
```

2.2.4 Completing the Installation Procedure

The following messages indicate that the entire installation procedure is complete:

```
   Installation of DECWNL_NL V2.1 completed at 11:55

   VMSINSTAL procedure done at 11:55
```

You can now log out of the privileged account:

```
$  LOGOUT
SYSTEM     logged out at 16-SEP-1991 11:57:24.14
```

Note that VMSINSTAL deletes or changes entries in the process symbol tables during the installation. Therefore, if you are going to continue using the system manager's account and you want to restore these symbols, you must log out and log in again.

2.3 Error Recovery

If errors occur during the installation, VMSINSTAL displays failure messages. If the installation fails, you see the following message:

```
%VMSINSTAL-E-INSFAIL, The installation of DECWNL_NL V2.1 has failed.
```

Errors can occur during the installation if any of the following conditions exist:

- The operating system version is incorrect

- Disk space necessary for successful installation is insufficient
- Quotas necessary for successful installation are insufficient
- System parameter values for successful installation are insufficient
- The VMS help library is currently in use

For descriptions of the error messages generated by these conditions, refer to the VMS documentation on system messages, recovery procedures, and VMS software installation. If you are notified that any of these conditions exist, you should take the appropriate action as described in the message. (You might need to change a system parameter or increase an authorized quota value.) For information on installation requirements, refer to Chapter 1.

3

After Installing VMS DECwindows V2.1 Language Variants

After installing a language variant, you must perform the following tasks:

- Edit the system startup file
- Amend the LIBRARY.DECW$BOOKSHELF file
- Check the installation
- Run the language variant

3.1 Editing the System Startup File

You must edit the system startup file to provide for automatic startup of VMS DECwindows V2.1 Language Variants when your system is rebooted.

Add the command line that starts the language variant to the system startup file, SYS$MANAGER:SYSTARTUP_V5.COM.

The VMS DECwindows V2.1 Language Variants cannot start until after the network has started. You must put this new command line *after* the line that invokes the network startup command procedure.

The following example shows the startup command lines for the network followed by the VMS DECwindows V2.1 Language Variants startup command line:

```
$  @SYS$MANAGER:STARTNET.COM
      .
      .
$  @SYS$MANAGER:DECW$STARTI18N.COM parameter1 parameter2
```

parameter1
This is the list of all the language variants which are available on the system. If you specify more than one language variant, you must separate the variants with commas. Table 3–1 shows the possible values for this parameter.

Table 3–1 Parameter values

Language variant	Parameter values
Dutch	NL_NL
French	FR_FR
French Canadian	FR_CA
German	DE_DE
Italian	IT_IT
Norwegian	NO_NO
Swedish	SV_SE
Swiss French	FR_CH
Swiss German	DE_CH
Swiss Italian	IT_CH

It is not necessary to include English in the list of language variant parameters.

parameter2
This is an optional parameter which defines a system-wide default language variant for all users. You cannot specify more than one value for this parameter. Table 3–1 shows the possible values for this parameter.

3.2 Amending the LIBRARY.DECW$BOOKSHELF file

You must include a reference to the translated language version of the online book *Using the Bookreader* in the main library bookshelf file. The main library bookshelf file is called LIBRARY.DECW$BOOKSHELF and it is in the directory SYS$COMMON:[DECW$BOOK].

This does not apply to the Norwegian language variant, which has no translated online documentation.

To include the reference to *Using the Bookreader* in the file LIBRARY.DECW$BOOKSHELF, follow these instructions:

Use the DCL APPEND command to append the file which contains the reference to the appropriate language version of *Using the Bookreader* to the file LIBRARY.DECW$BOOKSHELF. For more information about the APPEND command, refer to the *VMS DCL Dictionary*.

Table 3–2 lists the file for each language variant which contains the reference to *Using the Bookreader*. This file is in the directory SYS$COMMON:[DECW$BOOK].

Table 3–2 Language variant bookshelf files

Language variant	File name
Dutch	DECWNL_NL021BOOKREADER.DECW$BOOKSHELF
French	DECWFR_FR021BOOKREADER.DECW$BOOKSHELF
French Canadian	DECWFR_CA021BOOKREADER.DECW$BOOKSHELF
German	DECWDE_DE021BOOKREADER.DECW$BOOKSHELF
Italian	DECWIT_IT021BOOKREADER.DECW$BOOKSHELF
Norwegian	No translated online documentation available
Swedish	DECWSV_SE021BOOKREADER.DECW$BOOKSHELF
Swiss French	DECWFR_CH021BOOKREADER.DECW$BOOKSHELF
Swiss German	DECWDE_CH021BOOKREADER.DECW$BOOKSHELF
Swiss Italian	DECWIT_CH021BOOKREADER.DECW$BOOKSHELF

3.3 Checking the Installation

To make sure that the language variant has installed successfully, check that all the necessary files are installed on your system in the correct directories. The files are listed in Section B.2.

If all the files are in the correct directories, invoke and run the language variant according to the instructions in Section 3.4.

If all the files listed in Section B.2 are not installed, or if your language variant does not run correctly, report this to Digital. Refer to Section 3.5 for more information.

3.4 Invoking and Running a Language Variant

If you did not specify a system-wide default language variant (parameter2) on the startup command line in the file SYS$MANAGER:SYSTARTUP_V5.COM, you must tell all users how to start up the language variant which you have installed. Refer to Section 3.1 for more information on the startup command line.

To start up the language variant, each user must do the following:

1 Choose Language . . . from the Session Manager's Customize menu.

The Session Manager displays the Customize Language dialog box.

2 Scroll through the list of languages and choose the language which corresponds to the language variant installed.

The next application which the user starts is displayed in the selected language. If the application is not available on your system in the selected language, it is displayed in American English.

3 Choose Save Current Settings from the Session Manager's Customize menu.

When the user starts a new DECwindows session, the DECwindows environment will appear in the selected language.

3.5 Determining and Reporting Problems

If you encounter a problem while using VMS DECwindows V2.1 Language Variants, report it to Digital. Depending on the nature of the problem and the type of support you have, you can take one of the following actions:

- Call Digital if your software contract or warranty agreement entitles you to telephone support.
- Submit a Software Performance Report (SPR).
- Fill out and submit a Reader's Comments form if the problem has to do with the VMS DECwindows V2.1 documentation. There are Reader's Comments forms at the back of each manual. Use the form from the manual in which you found the error. Include the section and page number.

Review the Software Product Description (SPD) and Warranty Addendum for an explanation of warranty. If you encounter a problem during the warranty period, report the problem as indicated above or follow alternate instructions provided by Digital for reporting SPD nonconformance problems.

A

Sample Installation

This appendix contains a sample installation of one language variant. This sample was run on a system that had no previous version of that language variant installed.

The sample installation assumes that no users are logged on to your system.

```
$ @SYS$UPDATE:VMSINSTAL DECWDE_DE021 MTA0: OPTIONS N

 VAX/VMS Software Product Installation Procedure V5.4

It is 20-SEP-1991 at 12:05

Enter a question mark (?) at any time for help.
* Are you satisfied with the backup of your system disk [YES]? YES

Please mount the first volume of the set on MTA0:.
* Are you ready? YES
%MOUNT-I-MOUNTED, DECWDE_DE mounted on _$$MTA0:

The following products will be processed:

  DECWDE_DE V2.1

 Beginning installation of DECWDE_DE V2.1 at 12:06

%VMSINSTAL-I-RESTORE, Restoring product saveset A ...

Release notes included with this kit are always copied to SYS$HELP.

Additional Release Notes Options:

 1.  Display release notes
 2.  Print release notes
 3.  Both 1 and 2
 4.  None of the above

* Select option [2]: 2
```

```
* Queue name [SYS$PRINT]: LASER
Job 810 (queue LASER, entry 1295) started on LASER
* Do you want to continue the installation [NO]?: YES
%VMSINSTAL-I-RELMOVED, The product's release notes have been
                                successfully moved to SYS$HELP.

%DECWDE_DE-I-INTRO, Installing VMS DECwindows German language support.
* Do you want to purge files replaced by this installation [YES]? YES
%DECWDE_DE-I-NOMORE, No more questions will be asked.
%DECWDE_DE-I-TIME, This installation will take approximately 10 minutes.
%MVSINSTAL-I-RESTORE, Restoring product save set B ...
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[DECW$DEFAULTS.SYSTEM.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSHLP.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSHLP.EXAMPLES.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSLIB.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[SYSMSG.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[VUE$LIBRARY.SYSTEM.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[DECW$DEFAULTS.USER.DE_DE]
%VMSINSTAL-I-SYSDIR, This product creates system disk directory
                     VMI$ROOT:[VUE$LIBRARY.USER.DE_DE]
%VMSINSTAL-I-MOVEFILES, Files will now be moved to their
                                          target directories...

        Installation of DECWDE_DE V2.1 completed at 12:14

        VMSINSTAL procedure done at 12:14
```

B

Files and Logical Names Installed on Your System

The installation procedure for the VMS DECwindows V2.1 Language Variants creates directories on your system, installs a number of files and defines some logical names. Section B.1 lists the directories. Section B.2 lists the files installed. Section B.3 lists the logical names that are added to the system logical name table.

B.1 Directories

The following directories are created on your system when a language variant is installed:

- SYS$SYSROOT:[DECW$DEFAULTS.USER.x]
- SYS$SYSROOT:[DECW$DEFAULTS.SYSTEM.x]
- SYS$SYSROOT:[SYSHLP.x]
- SYS$SYSROOT:[SYSHLP.EXAMPLES.X]
- SYS$SYSROOT:[SYSLIB.x]
- SYS$SYSROOT:[SYSMSG.x]
- SYS$SYSROOT:[VUE$LIBRARY.USER.x]
- SYS$SYSROOT:[VUE$LIBRARY.SYSTEM.x]

x represents one of the names in Table B–1.

Table B–1 Directory values

Language variant	Directory name
Dutch	NL_NL
French	FR_FR
French Canadian	FR_CA
German	DE_DE
Italian	IT_IT
Norwegian	NO_NO
Swedish	SV_SE
Swiss French	FR_CH
Swiss German	DE_CH
Swiss Italian	IT_CH

For example, the directories created when the Swedish language variant is installed are:

- SYS$SYSROOT:[DECW$DEFAULTS.USER.SV_SE]
- SYS$SYSROOT:[DECW$DEFAULTS.SYSTEM.SV_SE]
- SYS$SYSROOT:[SYSHLP.SV_SE]
- SYS$SYSROOT:[SYSHLP.EXAMPLES.SV_SE]
- SYS$SYSROOT:[SYSLIB.SV_SE]
- SYS$SYSROOT:[SYSMSG.SV_SE]
- SYS$SYSROOT:[VUE$LIBRARY.USER.SV_SE]
- SYS$SYSROOT:[VUE$LIBRARY.SYSTEM.SV_SE]

B.2 Files

Table B–2 contains the names of all files installed on your system when a language variant is installed.

Table B–2 New files installed

Directory	Filename
SYS$SYSROOT:[DECW$DEFAULTS.SYSTEM.x]	DDIF$VIEW.UID
	DDIF$VIEWWGT.UID
	DECW$BOOKREADER.DAT
	DECW$BOOKREADER.UID
	DECW$CALC.DAT
	DECW$CALC.UID
	DECW$CALENDAR.DAT
	DECW$CALENDAR.UID
	DECW$CARDFILER.DAT
	DECW$CARDFILER.UID
	DECW$CLOCK.DAT
	DECW$CLOCK.UID
	DECW$LOGIN.DAT
	DECW$LOGIN.UID
	DECW$MAIL.DAT
	DECW$MAIL_MAIN.UID
	DECW$MAIL_MISC.UID
	DECW$MAIL_READ.UID
	DECW$MAIL_SEND.UID
	DECW$NOTEPAD.DAT
	DECW$NOTEPAD.UID
	DECW$PAINT.DAT
	DECW$PAINT.UID
	DECW$PRINTWGT_UI.UID
	DECW$PUZZLE.UID
	DECW$PUZZLE.DAT
	DECW$SESSION.DAT
	DECW$SESSION.UID
	DECW$SM_BW.DAT
	DECW$SM_COLOR.DAT

(continued on next page)

Table B–2 (Cont.) New files installed

Directory	Filename
	DECW$SM_GENERAL.DAT
	DECW$SM_GRAY.DAT
	DECW$TERMINAL.DAT
	DECW$TERMINAL.UID
	DECW$WINMGR.DAT
	DECW$WINMGR.UID
	VUE$MASTER.UID
SYS$SYSROOT:[SYSHLP]	DECWx021.RELEASE_NOTES. See Table 2–1.
SYS$SYSROOT:[SYSHLP.x]	DDIF$VIEW.HLB
	DECW$BOOKREADER.HLB
	DECW$CALC.HLB
	DECW$CALENDAR.HLB
	DECW$CARDFILER.HLB
	DECW$CLOCK.HLB
	DECW$HELPHELP.HLB
	DECW$MAIL.HLB
	DECW$NOTEPAD.HLB
	DECW$PAINT.HLB
	DECW$PRINTWGT.HLB
	DECW$PUZZLE.HLB
	DECW$SESSION.HLB
	DECW$TERMINAL.HLB
	DECW$VUE.HLB
SYS$SYSROOT:[SYSMGR]	DECW$STARTI18N.COM
SYS$SYSROOT:[SYSMSG.x]	DDIF$VIEWMSG.EXE
	DECW$DWTERRDB.DAT
	DECW$TERMINALMSG.EXE
	DECW$XLIBERRDB.DAT
SYS$SYSROOT:[VUE$LIBRARY.SYSTEM.x]	VUE$COMPARE.COM
	VUE$COMPILE.COM

(continued on next page)

Table B–2 (Cont.) New files installed

Directory	Filename
	VUE$COPY.COM
	VUE$CREATE_DIRECTORY.COM
	VUE$CREATE_PUBLIC_PROFILE.COM
	VUE$DELETE.COM
	VUE$EDIT.COM
	VUE$LINK.COM
	VUE$PURGE.COM
	VUE$RENAME.COM
	VUE$RUN.COM
	VUE$SEARCH.COM
	VUE$SET_PROTECTION.COM
	VUE$SHOW.COM
	VUE$SYSTEM_PROFILE.VUE$DAT
	VUE$TYPE.COM
SYS$COMMON:[DECW$BOOK]	DECWx021BOOKREADER.DECW$BOOKSHELF. See Table 3–2.[1]
	DECWx021BOOKREADER.DECW$BOOK. The language version of *Using the Bookreader*.[1]

[1]These files are not installed with the Norwegian language variant, which has no Norwegian online documentation.

B.3 Logical Names

The following logical names are entered into the system logical name table when you invoke a language variant. These names are stored in the product's startup file. They are automatically entered into the system logical name table whenever the system reboots or whenever the software is invoked.

The logical name XNL$LANG is only created when you specify a value for both parameter1 and parameter2 in the system startup file. Refer to Section 3.1 for more information about these parameters.

- DECW$SYSTEM_DEFAULTS_x
- SYS$EXAMPLES_x
- SYS$HELP_x

- SYS$LIBRARY_x
- SYS$MESSAGE_x
- VUE$LIBRARY_x
- XNL$LANG

x represents one of the values in Table B–3.

Table B–3 Logical name values

Language variant	Values
Dutch	NL_NL
French	FR_FR
French Canadian	FR_CA
German	DE_DE
Italian	IT_IT
Norwegian	NO_NO
Swedish	SV_SE
Swiss French	FR_CH
Swiss German	DE_CH
Swiss Italian	IT_CH

For example, the logical names for the Italian language variant are:

- DECW$SYSTEM_DEFAULTS_IT_IT
- SYS$EXAMPLES_IT_IT
- SYS$HELP_IT_IT
- SYS$LIBRARY_IT_IT
- SYS$MESSAGE_IT_IT
- VUE$LIBRARY_IT_IT
- XNL$LANG

Index

A

Aborting the installation, 2–2
Account quotas, 1–3
Amending the bookshelf file, 3–2
APPEND command, 3–2
Authorize utility, 1–3

B

Backing up the system disk, 1–4
Bill of materials, 1–1
Bookshelf file, 3–2

C

Checking the installation, 3–3
Completing the installation, 2–7
Contents of media kit, 1–1
CTRL/Y, 2–2

D

Device name, 2–3
Disk space, 1–2

E

Editing the system startup file, 3–1
Error messages, 2–8
Error recovery, 2–7

F

Files created on the system, 2–2, B–1
Free disk blocks, 1–2

I

Informational messages, 2–6
Installation
  aborting, 2–2
  checking, 3–3
  procedure, 2–1, 2–2
  questions, 2–4
  requirements, 1–2, 1–4
  starting, 2–3
Installation names, 2–3
Installation verification procedure, 2–2
Invoking language variants, 3–3
IVP, 2–2

L

Library bookshelf file, 3–2
Logical names, B–5

M

Media kit, 1–1
Messages
  error, 2–8
  informational, 2–6

Mounting the media, 2–5

O

Online documentation, 3–2
Online release notes, 1–1
  accessing, 2–1
  reading, 2–5
OPTIONS, 2–1, 2–3

P

Preparing for the installation, 1–1
Prerequisite software, 1–1
Privileges, 1–2
Problems, 3–4

Q

Quotas
  setting, 1–3

R

Release notes, 1–1
  accessing, 2–1
  reading, 2–5
Reporting problems, 3–4
Running language variants, 3–3

S

Sample installation, A–1
Saveset names, 2–3
SETPRV, 1–2
SHOW DEVICE command, 1–3
Software product description (SPD), 1–1
Starting the installation, 2–3
Startup file, 3–1
System disk, 1–4
System software addendum (SSA), 1–1

V

VMS DECwindows V2.1, 1–1
VMSINSTAL
VMSINSTAL (Cont.)
  command line, 2–3
  invoking, 2–3
  OPTIONS, 2–1, 2–3
  requirements, 1–3
VMS V5.4, 1–1