System Support Addendum

PRODUCT NAME: VAX DIBOL, Version 4.1 **SSA 25.49.14-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series
VAX 6000 Model 300 Series
VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserer 3800, VAXserver 3900, VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

- Minimum of 1 megabyte of memory
- RD52 or larger system disk
- VAXcluster environment

Processor Restriction

A TK50 Tape Drive is required for MicroVAX 2000 and VAXstation 2000 systems.

Block Space Requirements: (Block Cluster Size = 1):

Disk space required for installation:	7500 blocks (3.8M byte)
Disk space required for use (permanent):	6500 blocks (3.5M byte)

These block counts refer to the disk space required on the system disk. The sizes are approximations; actual sizes may vary depending on the user's system environment, configuration and software options selected.

During the installation of this product, as described in the VAX DIBOL Installation Notes, the installer is queried to determine which components of VAX DIBOL are required, and only the required components will be installed. For more detailed information, please consult the VAX DIBOL Installation Notes.

OPTIONAL HARDWARE

Floating point intensive applications should be run on configurations with the appropriate hardware support for the floating point data types being used. Consult the base operating system Software Product Description for the Floating Point Accelerator or other floating point hardware appropriate for your configuration.

VAXCLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration, with the following exception: The DIBOL SEND and RECV statements allow the transmission of data between separate processes running on the same node of a cluster. However, these statements do not support the transmission of data between processes running on separate cluster nodes.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.0 - V5.3

VMS Workstation Software V4.2

digital™

March 1990
AE-LT26D-TE

OPTIONAL SOFTWARE

VAX CDD/Plus V4.1 *

VAX Language-Sensitive Editor V3.0

VAX Performance and Coverage Analyzer V2.2

* VAX DIBOL currently does not fully support all features of VAX CDD/Plus.

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Programming Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-018A*-**
Software Media: QA-018A*-**
Software Documentation: QA-018AA-GZ
Software Product Services: QT-018A*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.

™ VAX, VMS, MicroVAX, VAXstation, VAXserver and Ethernet are trademarks of Digital Equipment Corporation.