System Support Addendum

PRODUCT NAME: DECmessageQ for VMS, Version 1.0 **SSA 34.07.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX:	VAXft 3000-310
	VAX 4000 Model 200, VAX 4000 Model 300
	VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series, VAX 6000 Model 500 Series
	VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840
	VAX 9000-210, VAX 9000 Model 400 Series
	VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785
MicroVAX:	MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900
VAXstation:	VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540
VAXserver:	VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900
	VAXserver 4000 Model 300
	VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX-11/725, VAX-11/782, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	30,000 blocks (15.4 Mbytes)
Additional space for LU6.2 Services:	5,000 blocks (2.6 Mbytes)
Disk space required for use (permanent):	
Permanent disk space for Development Only:	23,000 blocks (11.7 Mbytes)
Permanent disk space for Run-Time Only:	10,000 blocks (5.1 Mbytes)
Additional space for LU6.2 Services:	5,000 blocks (2.6 Mbytes)

These counts refer to the disk space required on the system disk, or the installation target disk if other than the system disk, for the permanent storage requirement. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

Any communication device capable of supporting DECnet-VAX. Any Ethernet controller supported by VMS Operating System.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

digital™

March 1991
AE-PF5GA-TE

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.3 - V5.4
DECnet/SNA APPC LU6.2 Programming Interface V2.2 at a minimum (for LU6.2 Services option only)

VMS Tailoring

The following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- System Programming Support
- Secure User's Environment

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DECnet/VAX V5.4
VAX Distributed Name Service V1.1
DECmessageQ for ULTRIX V1.0
DECmessageQ for MS-DOS V1.0
DECmessageQ for OS/2 V1.0

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape : 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

The software documentation for this product is also available as part of the VMS Online Documentation Library on CDROM.

ORDERING INFORMATION

Software Licenses:

DECmessageQ for VMS/Development: QL-GKPA9-J*
DECmessageQ for VMS/Run-Time Only: QL-GHVA9-J*
DECmessageQ for VMS/LU6.2 Services:
QL-GKQA9-J*

Software Media:

DECmessageQ for VMS/Development: QA-GKPAA-H*
DECmessageQ for VMS/Run-Time Only:
QA-GKPAA-H*
DECmessageQ for VMS/LU6.2 Services:
QA-GKPAA-H*

Software Documentation:

DECmessageQ for VMS/Development: QA-GKPAA-GZ
DECmessageQ for VMS/Run-Time Only:
QA-GKPAA-GZ
DECmessageQ for VMS/LU6.2 Services:
QA-GKPAA-GZ

Software Product Services:

DECmessageQ for VMS/Development: QT-GKPA*-**
DECmessageQ for VMS/Run-Time Only: QT-GHVA*-**
DECmessageQ for VMS/LU6.2 Services: QT-GKQA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® IBM and OS/2 are registered trademarks of International Business Machines Corporation.

® MS-DOS is a registered trademark of Microsoft Corporation.

™ The DIGITAL Logo, CI, DECwindows, DECnet, DECnet-VAX, MicroVAX, ULTRIX, VAX, VAXcluster, VAXft, VAXserver, VAXstation, and VMS are trademarks of Digital Equipment Corporation.