System Support Addendum

PRODUCT NAME: VAX DOCUMENT, Version 2.0 **SSA 27.55.05-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX:	VAXft 3000-310
	VAX 4000 Model 300
	VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series, VAX 6000 Model 500 Series
	VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840
	VAX 9000-210, VAX 9000 Model 400 Series
	VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785
MicroVAX:	MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900
VAXstation:	VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540
VAXserver:	VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900
	VAXserver 4000 Model 300
	VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX-11/725, VAX-11/782, VAXstation 8000

Processor Restriction

A TK50 tape drive is required for MicroVAX 2000 and VAXstation 2000 systems.

Disk Space Requirements (Block Cluster Size = 1):

The total number of blocks required during installation of the V2.0 kit: Minimum = 35,700 blocks, Maximum = 40,000 blocks.

The total number of blocks checked for on the target disk: 26,600 blocks.

Since the VAX DOCUMENT files can be installed on a non-system disk (that is, the target disk), the space available on the target disk is checked during the installation procedure. The target space required is 26,600 blocks.

The peak block usage when using VAX DOCUMENT: Minimum = 26,600 blocks, Maximum = 30,000 blocks.

These counts refer to the maximum disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options. The VAX DOCUMENT software need not be installed on the system disk.

OPTIONAL HARDWARE

Appropriately formatted VAX DOCUMENT files can be printed using any Digital line printer, matrix printer, LN03, LN03 PLUS, LN03R, LPS40, or LPS20 laser printer, and PostScript® graphic files for the LPS40, LPS20, or LN03R printers.

The LN03 and LN03 PLUS laser printers require 2 RAM cartridges.

digital™

February 1991
AE-LT68E-TE

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.3–5.4
VMS DECwindows
(VMS DECwindows must be installed to use the VAX Document Graphics Editor and associated graphics components as well as to build online books with VAX DOCUMENT using the ONLINE doctype option.)

OPTIONAL SOFTWARE

VAX Language-Sensitive Editor (VAX LSE/SCA) V3.1

VAX DEC/CMS V3.0–V3.4

VAX DOCUMENT/LN03 Font Package V1.1. This package is required in order to print files on the LN03 and LN03 PLUS laser printers.

Certain versions of these products depend upon a specific version of the Operating System. Please see the System Support Addendum of the product in question to determine which version of the Operating System is required.

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

ORDERING INFORMATION

Software Licenses: QL-VEEA*-**
Software Media: QA-VEEA*-**
Software Documentation: QA-VEEAA-GZ
Software Product Services: QT-VEEA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® PostScript is a registered trademark of Adobe Systems Incorporated.

™ The DIGITAL Logo, CDA, DEC, DECwindows, LN03, LN03 PLUS, MicroVAX, VAX, VAXcluster, VAXft, VAXserver, VAXstation, and VMS are trademarks of Digital Equipment Corporation.