System Support Addendum

PRODUCT NAME: DRB32 VMS DRIVERS, Version 3.0 **SSA 27.69.02-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350,
VAX 8500, VAX 8530, VAX 8550, VAX 8700
VAX 8800, VAX 8810, VAX 8820, VAX 8830,
VAX 8840, VAX 8842, VAX 8974, VAX 8878

VAX 9000 Model 200 Series

Processors Not Supported

VAX-11/725, VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/782, VAX-11/785, VAX 8600, VAX 8650, MicroVAX systems, VAXserver systems and VAXstation systems.

A minimum system configuration includes:

- One VAXBI based VAX host system
- One DRB32-M (minimum requirement for UQDRIVER) or
- One DRB32-M and one DRB32-W (minimum requirement for UQWDRIVER) or
- One DRB32-M and one DRB32-E (minimum requirement for UQDRIVER with long length cables)

Block Space Requirements (Block Cluster Sizes = 1):

The installation procedure allows the user to install the drivers on a system, or to simply copy the sources off the kit, or both. The disk space requirements depend on the option the user selects:

	DRB32-M/-E	
	Peak	Final
Install and copy sources:	5600	2800
Copy sources only:	2500	2000
Install only:	5600	1200

	DRB32-W	
	Peak	Final
Install and copy sources:	5600	2000
Copy sources only:	1600	1300
Install only:	5600	1100

These block counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, software options selected, and any modifications by the user.

OPTIONAL HARDWARE

The number of additional DRB32s will depend on system configuration and user's application. DRB32s can be configured on multiple VAXBIs. Refer to the VAX Systems and Options Guide for specifics.

digital™

September 1990
AE-LX37B-TE

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.0 or greater

VMS Operating System V5.0 supports DRB32 VMS DRIVER V3.0. This can include, but is not limited to V5.0, V5.1, V5.2, V5.3 and V5.4.

VMS Tailoring

The following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Programming Support
- System Programming Support
- Utilities
- Miscellaneous Files

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

In order to modify the test programs provided with the DRB32 VMS DRIVERS layered product, VAX FORTRAN at a minimum of V4.4 and VAX C at a minimum of V3.0.

No optional software is necessary to modifiy the device drivers of the kit.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

ORDERING INFORMATION

Software Licenses: QL-VF5A*-**
Software Media: QA-VF5A*-**
Software Documentation: QA-VF5AA-GZ
Software Product Services: QT-VF5A*-**

* Denotes variant fields. For additional information on available licenses, services and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, VAX, MicroVAX, VAXstation, VAXserver and VMS are trademarks of Digital Equipment Corporation.