System Support Addendum

PRODUCT NAME: VAX DATATRIEVE, Version 5.1 **SSA 25.44.22-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000 Model 310
VAX 4000 Model 300
VAX 9000 Model 210, 410

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Other Hardware Required:

Mass storage with a minimum of 12,000 disk blocks for VAX DATATRIEVE system software.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	17,000 blocks (8.70M bytes)
Disk space required for use (permanent):	12,000 blocks (6.14M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

Memory Requirements for DECwindows Support

The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 8M bytes.

The performance and memory usage of DECwindows applications are particularly sensitive to system configuration. Less memory may be required on the client system (the system where the software is installed and executed) if the server (the component that displays the application) resides on another system. More memory may be required on a system with several applications running or where it may be desirable to improve the performance of an application.

OPTIONAL HARDWARE

Any device supported by the prerequisite software.

digital™

November 1990
AE-LT62E-TE

Graphics can be displayed on VT125, VT240, VT241, VT330, and VT340 terminals only. For users with DECwindows, graphics can be displayed in DECterm windows.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.2 - V5.4
VAX CDD/Plus V4.1 - V4.2A

For Workstations Running VWS:

VMS Operating System V5.2 - V5.4
VMS Workstation Software V4.1 - V4.2
VAX CDD/Plus V4.1 - V4.2A

For Workstations Running DECwindows:

VMS Operating System V5.2 - V5.4 (and necessary components of VMS DECwindows)
VAX CDD/Plus V4.1 - V4.2A

Note: For systems using VMS V5.4, VAX CDD/Plus at least at V4.2A is required

This product may run in either of the following ways:

- Stand-alone execution - running the X11 display server and the client application on the same machine.
- Remote execution - running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server (Base kit; includes run-time support)

For remote execution, the following DECwindows components must be installed on the machine:

Server Machine

- VMS DECwindows Compute Server (Base kit; includes run-time support)

Client Machine

- VMS DECwindows Compute Server (Base kit; includes run-time support)

VMS Tailoring

For VMS V5.x, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- System Programming Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

VAX DBMS V4.2
VAX FMS V1.8 - V1.9
VAX Language-Sensitive Editor V2.3 - V3.0 or
VAX Language-Sensitive Editor/Source Code Analyzer V3.1
VAX Rdb/VMS V3.1B
VAX TDMS V1.8 - V1.9
VIDA for DB2 V1.0

Certain versions of these products depend upon a specific version of the operating system. Please see the System Software Addendum of the product in question to determine which version you need.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

CPU Capacity

Software Licenses: QL-898A*-**
Software Media: QA-898A*-**
Software Documentation: QA-898AA-GZ
DATATRIEVE Handbook: QA-896AA-GZ
Software Product Services: QT-898A*-**

4-User

Software License: QL-898A9-PD

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® IBM is a registered trademark of International Business Machines Corporation.

™ DB2 is a trademark of International Business Machines Corporation.

™ The DIGITAL Logo, VAX, MicroVAX, VAXstation, VAXserver, VMS, DECnet, DECwindows, DECterm, PDP-11, VAX CDD/Plus, VAX DATATRIEVE, VAX FMS, VAX Rdb/VMS and VIDA are trademarks of Digital Equipment Corporation.