System Support Addendum

Product Name: DECforms, Version 1.3 **SSA 29.90.03-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310
VAX 4000 Model 300,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000 Model 400 Series

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 300, VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX-11/725, VAX-11/782, VAXstation 8000

Processor Restriction

A TK50 Tape Drive is required for MicroVAX 2000 and VAXstation 2000 systems.

Terminals [1]

VT100	VT100 with AVO
VT101	VT102
VT103	VT125
VT131 [2]	VT220
VT240	VT241
VT320 [3]	VT330 [3]
VT340 [3]	VT420 [4]
IBM ® 3270 compatible [5]	

1. DECforms also supports the Hebrew versions of the VT100, VT200, and VT300 series terminals.
2. The VT131 is supported in VT102 mode only.
3. DECforms does not support the use of the 25th status line nor the use of the locator device on VT300-series terminals.
4. DECforms panels of up to 72 lines may be defined for VT420 terminals. The VT420 can display 24, 36, or 48 lines on a single screen. Panels consisting of a number of lines greater than the screen size can be panned under local hardware control by the VT420 terminal. DECforms does not support access to the F1-F5 function keys or to the ALTERNATE key. The COMPOSE key is supported when configured for LOCAL COMPOSE.
5. DECforms supports display of forms on IBM 3270-class terminals only when those terminals are connected to the CXM04 3270 Terminal Option Card of a DECserver 550. This option card makes the IBM 3270-compatible device appear as a VT220 to the application.

Terminal Emulators

Terminal emulators on VAXstations and personal computers are supported only to the extent that the emulator conforms to the VT100, VT220, or VT320 environment it is emulating.

digital™

April 1991
AE-ME12D-TE

Printers

DECforms panels and forms can be printed on any Digital printer. Video attributes are not printed and lines are drawn using the characters "-", "+", " " rather than the line-drawing character set.

Disk Space Requirements (Block Cluster Size = 1):

Full Development System:

Disk space required for installation:	17,000 blocks (9 Mbytes)
Disk space required for use (permanent):	
With samples and demos	16,000 blocks (8 Mbytes)
Without samples and demos	7,500 blocks (4 Mbytes)

Run-time System:

Disk space required for installation:	1,500 blocks (.8 Mbytes)
Disk space required for use (permanent):	400 blocks (.2 Mbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the users' system environment, configuration and software options selected.

OPTIONAL HARDWARE

Any device supported by the prerequisite/optional software.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

- VMS Operating System V5.0 - V5.4

VMS Tailoring

The following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Programming Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

- VAX CDD/Plus V4.1 - V4.3
- VAX Language-Sensitive Editor/Source Code Analyzer V2.3 - V3.1 (requires VMS V5.1 - V5.3)

Any VMS programming language that adheres to the VAX Procedure Calling and Condition Handling Standard.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Full Development System

Software Licenses: QL-VCHA*-**
Software Media: QA-VCHAA-**
Software Documentation: QA-VCHAA-GZ
Software Product Services: QT-VCHA*-**

Run-time System

Software Licenses: QL-VNSA*-**
Software Media: QA-VNSAA-**
Software Product Services: QT-VNSA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® IBM is a registered trademark of International Business Machines Corporation.

™ The DIGITAL Logo, VAX, VMS, MicroVAX, VAXstation, VAXserver, VAXcluster, DECforms, DECintact, VT, VAX FMS, VAX TDMS, VAX ACMS, VAXTPU and VAX CDD/Plus are trademarks of Digital Equipment Corporation.