System Support Addendum

PRODUCT NAME: VAX DECgraph, Version 1.6 **SSA 26.07.11-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series,
VAX 9000 Model 210

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900,

VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

Other Hardware Required

- VT125 (at a minimum of Rev. 102), VT240, VT241, or VT300 series terminal,
- DECmate II or III (DECmate/WPS, at a minimum of Version 2.1)/DECmate III PLUS (DECmate/WPS, at a minimum of Version 2.2) with appropriate Graphics Option module; Graphics Terminal Emulator required if WPS not installed.
- Rainbow 100 computer with a terminal emulator and the ReGIS application diskette, or DECterm V2.0 terminal emulator or
- VAXmate with VT240 terminal emulator. If DMF32 is used, it must be at a minimum of Rev. F.

Note: GIGI terminals and the Professional 350 terminal emulator are not supported.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	3,500 blocks (1.80M bytes)
Disk space required for use (permanent):	1,600 blocks (0.82M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

- LCG01 color inkjet printer (formerly LCP01)
- VR241 RGB color monitor
- LN03 (at a minimum of Rev. 3.8), LN03 PLUS, and LPS40 laser printers. Complex graphics on the LN03 may require an additional RAM cartridge
- LA12, LA50, or LA75 printers (for black and white single size)
- LA100, LA210, or LA34-VA printers (for black and white single or double size)

digital™

September 1990
AE-LT66D-TE

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.4

VMS Tailoring

The following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Programming Support

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

VMS Workstation Software V4.2
VAX DATATRIEVE V4.2
VAX DECalc V3.1

VAX DECgraph can be used with VAX DECalc as described in SPD 25.79.xx provided VAX DECgraph is installed on the system before the installation of VAX DECalc.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-360A*-**
Software Media: QA-360A*-**
Software Documentation: QA-360AA-GZ
Software Product Services: QT-360A*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, DECgraph, VAX, MicroVAX, VAXstation, VAXserver and VMS are trademarks of Digital Equipment Corporation.