System Support Addendum

PRODUCT NAME: DECimage Scan Software for VMS, Version 2.1 **SSA 25.D4.02-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310

VAX 4000 Model 200,
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000 Model 400 Series

VAX–11/730, VAX–11/750, VAX–11/780, VAX–11/785

MicroVAX: MicroVAX II, MicroVAX 2000,
MicroVAX 3100, MicroVAX 3300,
MicroVAX 3400, MicroVAX 3500,
MicroVAX 3600, MicroVAX 3800,
MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200,
VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX–11/725, VAX–11/782, VAXstation 8000

Recommended Configuration

VAXstation 3100

At least 16MB of memory required
One VR150 or 262 (monochrome), or VR160 or 290 (color) monitor
One RZ55 for mass storage
One TZ50 cartridge tape drive (for software installation)
Graphics upgrade (for 8-plane grayscale or color)
One mouse, one keyboard

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Other Hardware Required

- MD300 Scanner and LNV21 Q–bus Controller for scanning bitonal images.
- MD400 or MD410 Scanner (VAXstation 3100 SCSI-2 connection) for scanning bitonal, and grayscale images.
- Digital LAN Adapter for remote systems communication.

digital™

May 1991
AE-MH11D-TE

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	3,000 blocks (1.54 Mbytes)
Disk space required for use (permanent):	400 blocks (0.21 Mbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

Memory Requirements for DECwindows Support

The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 16MB.

The performance and memory usage of DECwindows applications are particularly sensitive to system configuration. Less memory may be required on the client system (the system where the software is installed and executed) if the server (the component that displays the application) resides on another system. More memory may be required on a system with several applications running, or where it may be desirable to improve the performance of an application.

The minimum memory supported is 16MB. However, the use of this software in conjunction with increased memory capability improves performance. The memory size suggested for most typical hardware configurations is at least 16MB.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

- V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.4 (and necessary components of VMS DECwindows)
DECnet/VAX V5.4 (Phase IV endnode) (required for remote scanning and mail.)

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives the user the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes IMG$SHRLIB.EXE for image runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support*

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server
- VMS DECwindows Programming Support*

VMS Tailoring

For VMS V5.x systems, the following classes of VMS are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DECimage Application Services for VMS V2.0
DECwrite for VMS V1.1
DECpresent for VMS V1.0

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

TK50 Streaming Tape, 9-track 1600 BPI Magtape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-VPFA*-**
Software Media and Documentation: QA-VPFAA-H*
Software Documentation: QA-VPFAA-GZ
Software Product Services: QT-VPFA*-**

* Required for application development; not required to run application.

- Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for most up-to-date information.

™ The DIGITAL Logo, CI, DEC, DECimage, DECnet, DECpresent, DECwindows, DECwrite, MicroVAX, Q–bus, TK, ULTRIX, VAX, VAXcluster, VAXft, VAXserver, VAXstation, and VMS are trademarks of Digital Equipment Corporation.