System Support Addendum

PRODUCT NAME: VAX ISDN, Version 1.1 **SSA 31.23.01-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 4000 Model 300

MicroVAX: MicroVAX II, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 300

Processors Not Supported

VAX: VAXft 3000-310

VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series, VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000-410

VAX-11/725, VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/782, VAX-11/785

MicroVAX: MicroVAX I, MicroVAX 2000, MicroVAX 3100

VAXstation: VAXstation I, VAXstation 2000, VAXstation 3100 Series, VAXstation 8000

VAXserver: VAXserver 3100

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Other Hardware Required

Communication Interface: DEC ISDNcontroller 100 (DIV32).

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	2,200 blocks (1.1 Mbytes)
Disk space required for use (permanent):	1,750 blocks (.9 Mbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

For optional software (DECnet-VAX), the system must, in addition, meet the corresponding requirements. Consult the DECnet-VAX Software Product Description (SPD 25.03.xx) for a complete description.

Physical memory: at least 1.5 Mbytes.

Non-paged dynamic pool: at least 50 Kbytes.

digital™

December 1990
AE-NS26B-TE

OPTIONAL HARDWARE

Additional DIV32 communication devices.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product. The product should be installed once on each VAX system from which usage is planned in order to uniquely configure the product. The same version of VAX ISDN must be used on all systems in VAXcluster configurations accessing a common disk.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.2-1–V5.4

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- Utilities
- BLISS Require Files

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

For DECnet Operation:

DECnet-VAX (either end-node or full-functional) V5.4

For Ethernet Connected Nodes (which need to control the VAX ISDN software remotely):

VAX ISDN Access V1.1 (SPD 31.24.xx) and DECnet-VAX.

For VAX P.S.I. Operation:

VAX P.S.I. V4.3

Certain versions of these products depend on a specific version of the operating system. Please see the System Support Addendum of the product in question to determine which version is required.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-VZ9A*-**
Software Media: QA-VZ9A*-**
Software Documentation: QA-VZ9AA-GZ
Software Product Services: QT-VZ9A*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® AT&T is a registered trademark of American Telephone & Telegraph Company.

™ The DIGITAL Logo, CI, DEC, DECnet, DECnet-VAX, DECstation, DECsystem, ISDN, MicroVAX, VAX, VAXcluster, VAXft, VAXserver, VAXstation, and VMS are trademarks of Digital Equipment Corporation.