System Support Addendum

PRODUCT NAME: DECimage Storage Manager for VMS, Version 1.0 SSA 31.22.00-A

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series, VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not supported

11/725, 11/730, 11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Block Space Requirements (Block Cluster Size = 1)

Disk space required for installation	4,000 blocks (2.0 Mbytes)
Disk space required for use (permanent)	3,000 blocks (1.5 Mbytes)

These counts refer to the disk space required on the system disk.

CLUSTER ENVIRONMENT

For the server

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration. It must be installed once on each VAX, MicroVAX or VAXstation processor from which usage is planned. In order to configure some product specific attributes that must remain unique to each system, certain components of the product are stored in the system specific environment, SYS__$SPECIFIC:[SYSxxx]. of the VAX, MicroVAX or VAXstation processor on which the installation is performed. The remaining components of the product, including some or all of the executable images will be installed common to all accessing systems. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

For the client

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, NI, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

Operating System

VMS Operating System, Version 5.3

digital software

November 1989
AE-PAAAA-TE

Layered Products

DECnet/VAX V5.3 (Phase IV endnode) required for distributed client access to server.

VAX Rdb/VMS, Version 3.0 (Runtime Option)

VMS Tailoring

For VMS V5.0 or later systems, the following classes of VMS are required for full functionality of this layered product:

VMS Required Saveset
Network Support
Programming Support
System Programming Support
Utilities
Miscellaneous Files

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DECimage Application Services for VMS, Version 2.0
DECimage Scan Software for VMS, Version 2.0
VAX Rdb/VMS, Version 3.0
DECwrite for VMS, Version 1.0

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different than the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape9-Track 1600 BPI Magtape, TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software License (Server) - QL-893A*-**
Software License (Client) - QL-YGDA*-**
Software Media and Documentation - QA-893AA-H*
Software Product Services (Server) - QT-893A*-**
Software Product Services (Client) - QTYGDA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.

™ DECimage, DECwrite, VMS, MicroVAX, VAX, VAXstation and VAXserver are trademarks of Digital Equipment Corporation.