System Support Addendum

PRODUCT NAME: LAN Traffic Monitor for VMS Version 1.2 **SSA 27.80.02-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540, VAXstation 8000

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX: VAX-11/725, VAX-11/730, VAX-11/782

MicroVAX: MicroVAX I

VAXstation: VAXstation I, VAXstation 8000

Other Hardware Requirements

- A VT24x, VT330, or VT340 Terminal is required to display color graphics for systems with no DECwindows interface.
- To run the Listener, one of the following is required:

  A LAN Bridge 100 with ROM ECO Revision E or later

  A LAN Bridge 150

  A Chipcom™ Ethermodem™ III Bridge [Part Numbers 8318BS (18Mhz) or 8312BS (12 Mhz)

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:

1,100 blocks
(0.55M bytes)

Disk space required for use (permanent):

600 blocks
(0.3M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

- VMS Operating System V5.2 - V5.3
- DECnet-VAX V5.2 - V5.3

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- Secure User's Environment
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (25.01.xx).

™ Chipcom and Ethermodem are trademarks of Chipcom Corporation.

digital software

February 1990
AE-MJ49B-TE

OPTIONAL SOFTWARE

- Remote Bridge Management Software (RBMS) V2.0
- NMCC/VAX ETHERnim V2.2

For more information refer to the RBMS Software Product Description (SPD 27.12.xx) and NMCC/VAX ETHERnim Software Product Description (SPD 26.96.xx).

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

Additional LAN Bridge units can be purchased and configured with LTM Listener software after LAN Traffic Monitor VMS has been installed. By creating a separate VMS process (or subprocess), a single user account on the VAX host may simultaneously be collecting data from multiple LTM Listener units. The LTM Listener can be started in either private mode (sending to a single destination Ethernet address) or shared mode (multicasting its traffic reports).

Also, while multiple hosts may simultaneously view a single LTM Listener unit (thereby requiring additional licenses of the software be purchased for each additional processor), multiple accounts on a single host may NOT simultaneously view a single LTM Listener unit.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape, TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-VEHA*-**
Software Media: QA-VEHA*-**
Software Documentation: QA-VEHAA-GZ
Software Product Services: QT-VEHA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at the time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.
™ DECnet, DECwindows, LAN Traffic Monitor, LAN Bridge, MicroVAX, VAX, VAXstation, VAXserver, and VT are trademarks of Digital Equipment Corporation.