System Support Addendum

PRODUCT NAME: DECmcc Extended LAN Manager AM, Version 1.0 **SSA 31.33.01-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 4000 Model 200,
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000 Model 210,
VAX 9000 Model 400 Series

VAXft 3000 Model 310

VAX–11/750, VAX–11/780, VAX–11/785

MicroVAX: MicroVAX II, MicroVAX 2000,
MicroVAX 3100, MicroVAX 3300,
MicroVAX 3400, MicroVAX 3500,
MicroVAX 3600, MicroVAX 3800,
MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 6000 Model 210,
VAXserver 6000 Model 220,
VAXserver 6000 Model 310,
VAXserver 6000 Model 320,
VAXserver 6000 Model 410,
VAXserver 6000 Model 420,
VAXserver 6000 Model 510,
VAXserver 6000 Model 520

Processors Not Supported

MicroVAX I, VAXstation I, VAXstatiion II, VAxstation 2000, VAX–11/725, VAX–11/730, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Other Hardware Required

RA60 system disk is required at a minimum.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	5,700 blocks (2.9M bytes)
Disk space required for use (permanent):	5,700 blocks (2.9M Kbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

digital™

June 1991
AE-PH33B-TE

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.3 - V5.4

DECmcc (Plus one of the following required):

DECmcc Director for VMS V1.1
DECmcc Basic Management System for VMS V1.1
DECmcc Site Management Station for VMS V2.1
DECmcc Enterprise Management Station for VMS V2.1

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

When running DECmcc Extended LAN Manager AM V1.0 on the DECmcc Directory, the DECmcc Extended LAN Manager FM license is re- quired (QL-GX9A*-**).

This license is not required when running DECmcc Extended LAN Manager AM on DEcmcc Basic Management System V1.1, DECmcc Site Management Station V2.1, or DECmcc Enterprise Management Station V2.1.

Refer to the following DECmcc, for specific DECmcc information.

DECmcc Director for VMS V1.1 (SPD 32.46.xx)
DECmcc Basic Management System for VMS V1.1 (SPD 32.48.xx)
DECmcc Site Management Station for VMS V2.1 (SPD 31.87.xx)
DECmcc Enterprise Management Station for VMS V2.1 (SPD 31.88.xx)

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

The software documentation for this product is also available as part of the VMS Online Documentation Library on CDROM.

ORDERING INFORMATION

Software Licenses: QL-GX8A*-**
Software Media and Documentation: QA-GX8AA-**
Software Documentation: QA-GX8AA-GZ
Software Product Services: QT-GX8A*-**

(License Required with DECmcc Director 1.1)

Software License: QL-GX9A*-**

Software Product Services: QT-GX9A*-**

* Denotes variant fields. For additional information on available licenses, services, and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® Chipcom is a registered trademark of Chipcom Corporation.

™ Ethermodem is a trademark of Chipcom Corporation.

™ The Digital Logo, CI, DECmcc, DECbridge, DECconcentrator,DECelms, METROWAVE, VAXcluster, VAXft, VAX, VMS, MicroVAX, VAXstation and VAXserver are trademarks of Digital Equipment Corporation.