System Support Addendum

PRODUCT NAME: DECmcc TCP/IP SNMP Access Module for VMS, SSA 32.50.00-A

HARDWARE REQUIREMENTS

Processor Support

VAX: VAX 9000 Model 410,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978, VAX 9000

VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100, VAXstation 3150, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320

Processors not Supported

MicroVAX I, VAXstation I, VAX-11/725, VAX-11730, VAX-11/782, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstations 2000 systems.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	3,000 blocks (1536K bytes)
Disk space required for use (permanent):	3,000 blocks (1536K bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

None

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

Operating System

VMS Operating System V5.3 - V5.4

Layered Products

DECmcc Base Management System V1.0 and prerequisites or

DECmcc Director V1.0 and prerequisites

VMS/ULTRIX Connection V1.2 - V1.3

digital™

October 1990
AE-PE3WA-TE

DECmcc TCP/IP SNMP Access Module for VMS, SSA 32.50.00-A

VMS Tailoring

For VMS systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DECmcc Site Management Station V2.0
DECmcc Enterprise Management Station V2.0

GROWTH CONSIDERATIONS

The minimum hardware requirements for any future version of this product may be different from the minimum hardware requirements for the current version.

DISTRIBUTION MEDIA

TK50 Streaming Tape

ORDERING INFORMATION

Software License: QL-YSVA*-**
Software Media: QA-YSVA*-**
Software Documentation: QA-YSVAA-GZ
Software Product Services: QT-YSVA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, VAX, VMS, ULTRIX, MicroVAX, VAXstation and VAXserver are trademarks of Digital Equipment Corporation.