System Support Addendum

PRODUCT NAME: VAX Notes, Version 2.0 **SSA 27.06.04-A**

HARDWARE REQUIREMENTS

Processor Support

VAX: VAX 6210, VAX 6220, VAX 6230, VAX 6240, VAX 6310, VAX 6312, VAX 6320, VAX 6330, VAX 6333, VAX 6340, VAX 6350, VAX 6360, VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3300/3400, MicroVAX 3500/3600

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100, VAXstation 3200, VAXstation 3500, VAXstation 8000

VAXserver: VAXserver 3300/3400, VAXserver 3500/3600, VAXserver 3602, VAXserver 6210/6220, VAXserver 6310/6320

Processors Not Supported: MicroVAX I, VAXstation I, VAX-11/725, VAX -11/782

Processor Restrictions

A TK50 tape drive is required for MicroVAX 2000 and VAXstation 2000 systems.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation: 4,700 blocks (2406.4K bytes)

Disk space required for use (permanent): 3800 blocks (1945.6K bytes)

These block counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options selected. The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 6mb. The minimum supported memory is the minimum that will allow the product to run adequately. For optimal performance of the product, the recommended memory is 8mb.

OPTIONAL HARDWARE

VAX Notes supports screen-oriented editing only on terminals that respond to ANSI control functions and that operate in ANSI mode. VAX Notes screen-oriented editing is designed to optimize the features of the DIGITAL VT200 and VT100 families of terminals.

Line mode editing is provided for non-ANSI terminals supported by the VMS Operating System.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The HARDWARE REQUIREMENTS sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For systems using terminals: (No DECwindows interface)

VMS Operating System V5.1

For workstations running VMS Workstation Software:

VMS Operating System V5.1
VMS Workstation Software V4.0

For workstations running DECwindows:

VMS Operating System V5.1 (and necessary components of VMS DECwindows)

This product may run in either of the following ways:

- Stand-alone execution - Running the X11 display server and the client application on the same machine.
- Remote execution - Running the X11 display server and the client application on different machines.

digital software

April 1989
AE-LT35B-TE

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; provides runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server (Base kit; provides runtime support)
- VMS DECwindows Device support

For remote execution, the following DECwindows components must be installed on the machines:

Server Machine	Client Machine
VMS DECwindows Compute Server (Base kit; provides runtime support) VMS DECwindows Device support	VMS DECwindows Compute Server Base kit (Base kit; provides runtime support)

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Secure User's Environment
- Utilities

OPTIONAL SOFTWARE

DECnet-VAX V5.1 (Required for Client license)
ALL-IN-1 V2.3
VAX DECspell V1.1
VAX Distributed Name Service V1.1

GROWTH CONSIDERATIONS

Notefiles grow as more topics and replies are added to the conference; sufficient disk space must be allocated to allow these files to grow as needed.

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements of the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

ORDERING INFORMATION

Server Software:

Software Licenses: QL-960A*-**
Software Media: QA-960A*-**
Software Documentation: QA-960AA-GZ
Software Product Services: QT-960A*-**

Client Software:

Software Licenses: QL-VESA*-**
Software Media: QA-VESA*-**
Software Documentation: QA-VESAA-GZ
Software Product Services: QT-VESA*-**

User-Based Option:

Software Licenses: QL-960A9-P*
Software Media: QA-960A*-**
Software Documentation: QA-960AA-GZ
Software Product Services: QT-960A*-**

* Denotes variant fields. For additional information on available licenses, services and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your Local DIGITAL office for the most up-to-date information.