System Support Addendum

PRODUCT NAME: VAX Notes, Version 2.1 **SSA 27.06.05-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	4,800 blocks (2.5M bytes)
Disk space required for use (permanent):	3,800 blocks (1.9M bytes)

These block counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration and software options.

Memory Requirements for DECwindows Support

The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 8MB.

OPTIONAL HARDWARE

VAX Notes supports screen-oriented editing only on terminals that respond to ANSI control functions and that operate in ANSI mode. VAX Notes screen-oriented editing is designed to optimize the features of the Digital VT200 and VT100 families of terminals.

Line mode editing is provided for non-ANSI terminals supported by the VMS Operating System.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For systems using terminals (No DECwindows interface):

VMS Operating System V5.3

For workstations running VWS:

VMS Operating System V5.3
VMS Workstation Software V4.2

For workstations running DECwindows:

VMS Operating System V5.3 (and necessary components of VMS DECwindows)

This product may run in either of the following ways:

Stand-alone execution - running the X11 display server and client application on the same machine.

Remote execution - running the X11 display server and the client application on different machines.

February 1990
AE-LT35C-TE

digital™

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

VMS DECwindows Compute Server (Base kit; includes runtime support)

VMS DECwindows Device Support

VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

VMS DECwindows Compute Server (Base kit; includes runtime support)

VMS DECwindows Device Support

For remote execution, the following DECwindows components must be installed on the machines:

Server Machine

VMS DECwindows Compute Server
(Base kit; includes runtime support)

VMS DECwindows Device support

Client Machine

VMS DECwindows Compute Server
(Base kit; includes runtime support)

VMS Tailoring

The following VMS classes are required for full functionality of this layered product:

VMS Required Saveset
Network Support
Secure User's Environment
Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DECnet-VAX, V5.3 (Required for Client license)

ALL-IN-1, V2.3

VAX DECspell Verifier/Corrector, V1.1

GROWTH CONSIDERATIONS

Notefiles grow as more topics and replies are added to the conference; sufficient disk space must be allocated to allow these files to grow as needed.

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements of the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

The software documentation for this product is also available as part of the VMS Online Documentation Library on CDROM.

ORDERING INFORMATION

Server Software

Software Licenses: QL-960A*-**
Software Media: QA-960A*-**
Software Documentation: QA-960AA-GZ
Software Product Services: QT-960A*-**

Client Software

Software Licenses: QL-VESA*-**
Software Media: QA-960A*-**
Software Documentation: QA-960AA-GZ
Software Product Services: QT-VESA*-**

User-Based Option

Software Licenses: QL-960A9-P*
Software Media: QA-960A*-**
Software Documentation: QA-960AA-GZ
Software Product Services: QT-960A*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.

™ VAX, VMS, MicroVAX, VAXstation, VAXserver, VAXcluster, DECnet, DECnet-VAX, Ethernet, EDT, WPS, VMSmail, DECspell, GOLD KEY and ALL-IN-1 are trademarks of Digital Equipment Corporation.