System Support Addendum

PRODUCT NAME: DEC ODA Compound Document Architecture (CDA) Gateway for VMS, Version 1.0 **SSA 32.10.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310

VAX 4000 Model 200,
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000 Model 400 Series

VAX-11/780, VAX-11/785

MicroVAX: MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

VAX: VAX-11/725, VAX-11/730, VAX-11/750, VAX-11/782

MicroVAX: MicroVAX I, MicroVAX II

VAXstation: VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVax 2000 and VAXstation 2000 systems.

Suggested Configurations

- VAX 11/785 with a minimum of 12MB main memory
- VAXstation 2000 running DECwindows with a minimum of 12MB main memory installed on a VAXcluster
- VAXstation 3500 running DECwindows with a minimum of 32MB of main memory

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	1,600 blocks (819.2 Kbytes)
Disk space required for use (permanent):	1,500 blocks (768.0 Kbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

Memory requirements for DECwindows Support

Minimum supported memory for this application running in a standalone DECwindows environment with DECwrite is 12 MB of main memory.

digital™

March 1991
AE-PB6RA-TE

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.4 (and necessary components of VMS DECwindows)

For Workstations Running VWS:

VMS Operating System V5.4 (and necessary components of VMS DECwindows)
VMS Workstation Software V4.3

For Workstations Running DECwindows:

VMS Operating System V5.4 (and necessary components of VMS DECwindows)

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives users the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server (Base kit; includes runtime support)

For X.400 transmission, the Message Transport System used must be encoded to support ODA Body parts over a CCITT X.400-1984 service.

VMS Tailoring

The following VMS class is required for full functionality of this layered product:

- VMS Required Save Set

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DECwrite for VMS V1.1
A Message Transport System that supports ODA Body parts over CCITT X.400-1984

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-YHNAA*-**
Software Media: QA-YHN**-**
Software Documentation: QA-YHNAA-GZ
Software Product Services: QT-YHNA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, CDA, DEC, DECwindows, DECwrite, LiveLink, MicroVAX, VAX, VAXcluster, VAXft, VAXserver, VAXstation, and VMS are trademarks of Digital Equipment Corporation.