System Support Addendum

PRODUCT NAME: DECpage, Version 3.1 **SSA 26.29.09-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series
VAX 6000 Model 300 Series
VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540, VAXstation 8000

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX: VAX-11/725

MicroVAX: MicroVAX I

VAXstation: VAXstation I

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

At least one of the following printers is required:

- PrintServer 20 (LPS20)
- PrintServer 40 (LPS40)
- PrintServer 40 Plus (LPS40 PLUS)
- ScriptPrinter (LN03R)
- LN03 (rev level 4.4) with 2 RAM (LN03X-CR) cartridges
- LN03 PLUS with 2 RAM (LN03X-CR) cartridges

The following table shows printers and formats supported by DECpage, V3.1.

Printer	DECpage Supported Format
PrintServer 20	PostScript® text & graphics; ReGIS, Sixel, and GKS graphics by means of translation software
PrintServer 40	PostScript text & graphics; ReGIS, Sixel, and GKS graphics by means of translation software
PrintServer 40 Plus	PostScript text & graphics; ReGIS, Sixel, AND GKS graphics by means of translation software
ScriptPrinter	PostScript text & graphics; ReGIS, Sixel, and GKS graphics by means of translation software
LN03	ANSI Text & Sixel Graphics (for simple business graphics)
LN03 PLUS	ANSI Text & Sixel Graphics (for full page bit mapped graphics)

® PostScript is a registered trademark of Adobe Systems Inc.

digital software

December 1989
AE-MF59D-TE

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:
40,000 blocks
(20,480K bytes)

Disk space required for use (permanent):
35,000 blocks
(17,920K bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

VT125, VT240/241 or VT330/340 series video terminal to display ReGIS or Sixel graphics

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The HARDWARE REQUIREMENTS sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

Operating System

VMS Operating System V5.1 - V5.3

Layered Products

WPS-PLUS/VMS V3.0 or V3.1
Any other Language Variant of V3.0 or V3.1

or

ALL-IN-1 V2.3 - V2.4
Any other Language Variant of V2.3 or V2.4

VAX ScriptPrinter Software V2.1 is required to print PostScript and non-PostScript files to a ScriptPrinter.

VAX PrintServer Supporting Host Software V3.1 and VAX PrintServer Client Software V3.0 are required to print PostScript and non-PostScript files to PrintServers.

Fonts

DECpage LN03 Basic Office Font Package V1.3 if outputting to an LN03 or LN03 PLUS.

No font package is required when printing to a ScriptPrinter, PrintServer 20, PrintServer 40, or PrintServer 40 Plus in native mode.

For the prerequisite software, refer to the Software Product Description and System Support Addendum for WPS-PLUS/VMS (SPD/SSA 26.27.xx-x) or ALL-IN-1 (SPD/SSA 27.30.xx-x).

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- Secure User's Environment
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DEC GKS for VMS V4.0 - Required for GKS to PostScript output to either ScriptPrinter, PrintServer 20, PrintServer 40, or PrintServer 40 Plus

VAX DECslide V1.3, VAX DECgraph V1.5 or a base ReGIS software package

Adobe Illustrator V1.1 for PostScript graphics

DECpage LN03 Upgrade and Complete Office Font Packages V1.3 if outputting to an LN03 or LN03 PLUS

VAX ReGIS to Sixels Converter (RETOS) V1.0 - ReGIS to Sixel graphics converter

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-AANA*-**
Software Media: QA-AANA*-**
Software Documentation: QA-AANAA-GZ
Software Product Services: QT-AANA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.
™ ALL-IN-1, DEC, Ethernet, GKS, ReGIS, WPS-PLUS/VMS, LN03, LN03 PLUS, LN03R, PrintServer, PrintServer 40, PrintServer 40 PLUS, VAX, MicroVAX, VAXserver, VAXstation, and VT are trademarks of Digital Equipment Corporation.