System Support Addendum

PRODUCT NAME: PDP-11 C for VMS, Version 1.1 **SSA 31.54.01-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 4000 Model 300,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

VAX 9000-210, VAX 9000-410

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320 VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A device capable of reading a TK50 is required to install this product on MicroVAX 2000 and VAXstation 2000 systems.

Other Hardware Required

This product requires EIS or FPU support on the target PDP-11 system.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	8,500 blocks (4.25M bytes)
Disk space required for use (permanent):	3,500 blocks (1.75M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

The minimum memory supported is 4MB. However, the use of this software in conjunction with increased memory capability improves performance. The memory size suggested for most typical hardware configurations is at least 6MB.

OPTIONAL HARDWARE

None

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

digital™

January 1991
AE-NY62B-TE

SOFTWARE REQUIREMENTS

For Systems Using Terminals:

VMS Operating System V5.3 - V5.4

For Workstations Running VWS:

VMS Operating System V5.3 - V5.4
VMS Workstation Software V4.2

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

VAX-11 RSX V2.5

VAX CoProcessor RSX V1.1

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-YEJA*-**
Software Media: QA-YEJA*-**
Software Documentation: QA-YEJAA-GZ
Software Product Services: QT-YEJA*-**

* Denotes variant fields. For additional information on available licenses, services and media refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, VAX, VMS, MicroVAX, VAXstation, VAXserver, PDP-11, RSX, RSX-11M, RSX-11M-PLUS, Micro/RSX, RSTS/E and RT-11 are trademarks of Digital Equipment Corporation.