System Support Addendum

PRODUCT NAME: VAX DECalc-PLUS, Version 3.1 **SSA 27.37.03-A**

HARDWARE REQUIREMENTS

Processors Supported:

VAX: VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported:

MicroVAX I, VAX-11/725, VAX-11/782, VAXstation I, VAXstation 8000

Processor Restrictions:

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	6,000 blocks (3.07M bytes)
Disk space required for use (permanent):	6,000 blocks (3.07M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.0 - V5.3

VMS Workstation Software V4.0 - V4.2

VMS Tailoring

For VMS V5.x, the following VMS classes are required for full functionality of this layered product:

- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

digital™

June 1990
AE-LU02C-TE

OPTIONAL SOFTWARE

Certain versions of these products depend upon a specific version of the operating system. Please see the System Support Addendum of the products in question to determine which version is required.

VAX DECgraph V1.5
VAX DATATRIEVE V3.0 - V5.0
VAX Xway V1.1A

Any Language which runs under VMS and supports the VAX Procedure Calling Standard.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape : 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses:

DECalc-PLUS: QL-A98A*-**
VAX DECalc-PLUS Migration License: QL-VDFA*-**

Software Media: QA-A98A*-**
Software Documentation: QA-A98AA-GZ
Software Product Services: QT-A98A*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.

™ VMS, VAX, MicroVAX, VAXstation, VAXserver, DECalc PLUS, VAX DATATRIEVE, VT, DCL, TK50, DECgraph and VAX Xway are trademarks of Digital Equipment Corporation.