System Support Addendum

PRODUCT NAME: DECpresent for VMS, Version 1.0 **SSA 32.07.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310,
VAX 4000 Model 300,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series,

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840,

VAX 9000 Model-210, VAX 9000 Model-410

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	35,000 blocks (17,920K bytes)
Disk space required for use (permanent):	34,500 blocks (17,664K bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

Memory Requirements for DECwindows Support:

A minimum of 8MB of memory is required on a workstation to operate DECpresent and VMS whether DECpresent is running on the workstation or on another processor.

OPTIONAL HARDWARE

DECpresent files can be printed using any Digital PostScript® printer, ScriptPrinter (LN03R), PrintServer 20, PrintServer 40, PrintServer 40 Plus laser printer, and for color PostScript, the Colormate PS.

DECchart produces both monochrome and color PostScript. Monochrome PostScript can be printed using any Digital PostScript printers listed above. If the DEC GKS product, or runtime system is installed, and the CDA Converter Library is installed, the DDIF Graphics Hardcopy converter can be used to generate the color and monochrome sixel formats (printed on the Digital LJ250 Companion Color Printer) and the HPGL™ format (printed on the Digital LVP16). If the DECprint Utility for PostScript to Sixel Printing for VMS is installed, DECchart PostScript output (either color or monochrome) can be printed on the Digital LJ250 Companion Color Printer.

digital™

December 1990
AE-PE5EA-TE

DECpresent will accept images scanned with the MD-300 Scanner.

Optional Third Party Hardware

For 35mm film recording, Digital refers the customer to the AGFA ChromaScript and AGFA film recorder or the Management Graphics Inc. Solitaire file recorder system. Digital does not offer a warranty or directly support these third party devices.

Digital does not offer a warranty or directly support these third party devices.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

- VMS Operating System V5.3 - V5.4 (and necessary components of VMS DECwindows

This product may run in either of the following ways:

- Stand-alone execution - running the X11 display server and the client application on the same machine.
- Remote execution - running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives users the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server
- VMS DECwindows Device Support

For remote execution, the following DECwindows components must be installed on the machine:

Server Machine

- VMS DECwindows Compute Server
- VMS DECwindows Device Support

Client Machine

- VMS DECwindows Compute Server
- VMS DECwindows Device Support

VMS Tailoring:

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- VMS Workstation Support
- Programming Support

Optional:

- Network Support - Provides support for cluster and client/server systems.
- Utilities - Mail provides support for sending files created with DECpresent.

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

PC DECwindows Display Facility

The PC DECwindows Display Facility is an MS-DOS® application that implements an X server that uses the industry-standard X Window System, Version 11 (X11) protocol. DECpresent executing on a remote VMS system with DECnet may be displayed on and receive input from the personal computer. The PC DECwindows Display Facility is supported only on Intel 80286 and 80386 machines. Refer to the DECnet PCSA Client for DOS, Version 3.0 Software Product Description and System Support Addendum (SPD 55.07.08 and SSA 55.07.08-x) for full hardware/software requirements.

OPTIONAL SOFTWARE

- DECprint Printing Services for VMS V4.0
- DECwrite for VMS V1.1
- DECdecision for VMS V1.1
- DECimage Scan Software for VMS V2.0
- DECnet PCSA Client for DOS, V3.0

- International Lexicons for VMS, V1.0

  International Lexicon/Français for VMS V1.0
  International Lexicon/Deutsch for VMS V1.0
  International Lexicon/British for VMS V1.0
  International Lexicon/Español for VMS V1.0
  International Lexicon/Nederlands for VMS V1.0
  International Lexicon/Svenska for VMS V1.0
  International Lexicon/American English for VMS V1.0
  (included with the U.S. version)
  International Lexicon/American Business for VMS V1.0
  International Lexicon/American Medical for VMS V1.0

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-YHEA9-PB
Software Media: QA-YHEAA-H*
Software Documentation: QA-YHEAA-GZ
Software Product Services: QT-YHEA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

International Hyphenators, and International CorrectSpell licensed from Houghton Mifflin Company. Copyright (c) 1985, 1987, 1988 by Houghton Mifflin. German (c) 1985, 1987 by Langenscheidt K.G. French in cooperation with Libraire Larousse. Italian (c) 1988 by Nicola Zanichelli. All rights reserved. U.S. Pat. Nos. 4,580,241, 4,724,523 and 4,771,401. Canadian. Pat. No. 1,203,916. Thesaurus U.S. Pat. No. 4,724,523. English based upon *The AMERICAN HERITAGE DICTIONARY*. Reproduction or disassembly of embodied computer programs or algorithms prohibited.

Arts and Letters® clipart licensed to Digital Equipment Corporation, Maynard, Massachusetts. Copyright (c) Computer Support Corporation 1985-1990. All rights reserved.

® Arts and Letters is a registered trademark of Computer Support Corporation.

® Lotus 1-2-3 is a registered trademark of Lotus Development Corporation.

® MS-DOS is a registered trademark of Microsoft Corporation.

® PostScript is a registered trademark of Adobe Systems, Inc.

™ HPGL is a trademark of Hewlett-Packard Corporation.

™ The DIGITAL Logo, CDA, GOLD KEY, DECpresent, DECwrite, DECdecision, DECalc, DECalc-PLUS, DECgraph, DECwindows, LiveLink, LN03, LVP16, PrintServer, VAX, MicroVAX, VAXstation, VAXserver and VMS are trademarks of Digital Equipment Corporation.