System Support Addendum

PRODUCT NAME: VAX RALLY, Version 2.3 **SSA 27.03.06-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310

VAX 4000 Model 200
VAX 4000 Model 300

VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350,
VAX 8500, VAX 8530, VAX 8550, VAX 8600,
VAX 8650, VAX 8700, VAX 8800, VAX 8810,
VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000 Model 400 Series

VAX–11/730, VAX–11/750, VAX–11/780,
VAX–11/785

MicroVAX: MicroVAX II, MicroVAX 2000,
MicroVAX 3100, MicroVAX 3300,
MicroVAX 3400, MicroVAX 3500,
MicroVAX 3600, MicroVAX 3800,
MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000,
VAXstation 3100 Series, VAXstation 3200,
VAXstation 3500, VAXstation 3520,
VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300,
VAXserver 3400, VAXserver 3500,
VAXserver 3600, VAXserver 3602,
VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 200,
VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-220,
VAXserver 6000-310, VAXserver 6000-320,
VAXserver 6000-410, VAXserver 6000-420,
VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

VAX–11/725, VAX–11/782, MicroVAX I, VAXstation I, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

A minimum of 4 MB of memory is required, although typical configurations will require more than 4 MB of memory. There is a recommendation of 0.75 MB per concurrent user.

Other Hardware Required

Terminals

VAX RALLY Development Option and VAX RALLY Run-Time Option can be run on any VT100 (with AVO), VT100 compatible terminal emulators on VAXstations, VT102, VT125 (with AVO), VT220, VT240/241, VT320, VT330, VT340, or VT420 terminal.

Disk Space Requirements (Block Cluster Size =1):

Disk space required for installation:

digital™

May 1991
AE-LX94G-TE

VAX RALLY Development Option:

With Examples:	26,000 blocks (13.3 Mbytes)
Without Examples:	18,000 blocks (9.2 Mbytes)

VAX RALLY Run-Time Option:

With Examples:	10,000 blocks (5.1 Mbytes)
Without Examples:	7,000 blocks (3.6 Mbytes)

Disk space required for use (permanent):

VAX RALLY Development Option:

With Examples:	20,000 blocks (10.2 Mbytes)
Without Examples:	15,000 blocks (7.7 Mbytes)

VAX RALLY Run-Time Option:

With Examples:	8,000 blocks (4.1 Mbytes)
Without Examples:	2,000 blocks (1.0 Mbytes)

In addition, VAX RALLY Development Option includes a text-based instruction course (TBI) entitled *Getting Started with VAX RALLY*. If this course is installed, it requires:

Disk space required for installation:	6,000 blocks (3.1 Mbytes)
Disk space required for use (permanent):	3,000 blocks (1.5 Mbytes)

Note: These amounts are in addition to the amounts listed previously.

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the users' system environment, configuration, and software options.

OPTIONAL HARDWARE

Any device supported by the prerequisite/optional software.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.2–V5.4

For Workstations Running VWS:

VMS Operating System V5.2–V5.4
VMS Workstation Software V4.2–V4.3

For Workstations Running DECwindows:

VMS Operating System V5.2–V5.4 (and necessary components of VMS DECwindows)

This product may run under DECterm in either of the following ways:

- Stand-alone execution—running the X11 display server and the client application on the same machine.
- Remote execution—running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately on versions prior to V5.4. Installation of VMS DECwindows gives users the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes Run-Time support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For remote execution, the following DECwindows components must be installed on the machine:

Server Machine

- VMS DECwindows Compute Server
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

Client Machine

- VMS DECwindows Compute Server
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

Layered Products

VAX Rdb/VMS (Interactive or Development System) V3.1B–V4.0 is required for the VAX RALLY Development Option.

VAX Rdb/VMS V4.0 is required for the Two-Phase Commit Option.

VAX Rdb/VMS (Run-Time, Interactive, or Development) is required for the VAX RALLY Run-Time Option if the application uses VAX Rdb/VMS. If using the VAX RALLY Run-Time Option with RMS files only, VAX Rdb/VMS is NOT required.

VAX CDD/Plus V4.0–V4.2A is required for the VAX RALLY Development Option, but not required for the VAX RALLY Run-Time Option.

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Secure User's Environment
- Programming Support (Not required for VAX RALLY Run-Time Option)

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

ALL–IN–1 V2.3
VAX TEAMDATA V1.4
VAX DATATRIEVE V5.1
VAX DBMS V4.2
VAX Language-Sensitive Editor/
Source Code Analyzer V3.1

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

VAX RALLY Development Option (includes VAX RALLY Run-Time Option):

Software Licenses: QL-A86A*-**
Software Media: QA-A86A*-**
Software Documentation: QA-A86AA-GZ
Software Product Services: QT-A86A*-**

VAX RALLY Run-Time Option:

Software Licenses: QL-VF4A*-**
Software Media: QA-VF4A*-**
Software Documentation: QA-VF4AA-GZ
Software Product Services: QT-VF4A*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, ALL–IN–1, CI, DATATRIEVE, DBMS, DECterm, DECwindows, Micro/VAX, RALLY, Rdb/VMS, TEAMDATA, TK50, VAX, VAX ACMS, VAX CDD/Plus, VAX DOCUMENT, VMS, VAXstation, VAXserver, VAXcluster, VT, and WPS–PLUS are trademarks of Digital Equipment Corporation.