System Support Addendum

PRODUCT NAME: DEC Remote Operation Service for VMS, Version 1.0 **SSA 32.89.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX:	VAXft 3000-310
	VAX 4000 Model 300
	VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series, VAX 6000 Model 500 Series
	VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840
	VAX 9000-210, VAX 9000 Model 400 Series
	VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785
MicroVAX:	MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900
VAXstation:	VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540
VAXserver:	VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900
	VAXserver 4000 Model 300
	VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX-11/725, VAX-11/782, VAXstation 8000

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	3,000 blocks (1.5 Mbytes)
Disk space required for use (permanent):	3,000 blocks (1.5 Mbytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet, and Mixed Interconnect configurations.

digital™

February 1991
AE-PG5AA-TE

SOFTWARE REQUIREMENTS

VMS Operating System V5.3–V5.4

VAX OSI Applications Kernel V1.1 (SPD 27.47.01)

VMS Tailoring

The VMS Required Saveset is required for full functionality of this layered product.

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

DEC Remote Operation Service Development Kit for VMS, V4.0 (SPD 32.90.xx)

The DEC Remote Operation Service Development Kit includes an ASN.1 Cross-Compiler to facilitate the development of ASN.1 compatible data structures, and to ensure efficient data encoding/decoding to and from the Basic Encoding Rule (BER) Transfer Syntax.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9 Track 1600 BPI Magtape, TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-YU2A*-**
Software Media: QA-YU2A*-**
Software Documentation: QA-YU2AA-GZ
Software Product Services: QT-YU2A*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, CI, DEC, MicroVAX, TK, VAX, VAXcluster, VAXft, VAXserver, VAXstation, and VMS are trademarks of Digital Equipment Corporation.