System Support Addendum

PRODUCT NAME: DEC SoftPC for VMS, Version 2.2 **SSA 32.18.00-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310,
VAX 4000 Model 300,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 4000 Model 300
VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420,

Processors Not Supported

VAX-11/725, VAX-11/782, VAX 6000 Model 500 Series, VAX 9000-210, VAX 9000-410, MicroVAX I, VAXstation I, VAXstation 3520/3540, VAXstation 8000, VAXserver 6000-510, VAXserver 6000-520

Memory Requirements

The SoftPC application requires a minimum working set of 2 MB. The minimum supported system memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 6 MB. However, the use of this software in conjunction with increased memory capability improves performance.

Disk Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	7,500 blocks (3,750K bytes)
Disk space required for minimum single use:	6,378 blocks (3,265K bytes)
Disk space required for typical use:	28,818 blocks (14,754K bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

OPTIONAL HARDWARE

The software can use a local floppy disk drive with the following restrictions:

- RX33 - Read/write high density only. **Note:** RX33 is not supported on machines with RQDX3 controllers.
- RX23 - Read/write high density. Read only low density.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

digital™

February 1991
AE-PC3BA-TE

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For Systems Using Terminals (No DECwindows Interface):

VMS Operating System V5.3 - V5.4

For Workstations Running DECwindows:

VMS Operating System V5.3 - V5.4 (and the necessary components of VMS DECwindows)

This product may run in either of the following ways:

- Stand-alone execution - running the X11 display server and the client application on the same machine.
- Remote execution - running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server
- VMS DECwindows Device Support

For remote execution, the following DECwindows components must be installed on the machine:

Server Machine

- VMS DECwindows Compute Server
- VMS DECwindows Device Support

Client Machine

- VMS DECwindows Compute Server
- VMS DECwindows Device Support

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

ORDERING INFORMATION

Software Licenses: QL-YNWA9-P*
Upgrade License: QL-YWBA9-P*
Software Media: QA-YNWAA-H*
Software Documentation: QA-YNWAA-GZ
Software Product Services: QT-YNWA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® IBM is a registered trademark of International Business Machines Corporation.

™ The DIGITAL Logo, VAX, MicroVAX, VAXstation, VAXserver and VMS are trademarks of Digital Equipment Corporation.