System Support Addendum

PRODUCT NAME: VAX Software Performance Monitor, Version 3.4 **SSA 27.56.09-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series, VAX 6000 Model 300 Series, VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAXstation I, VAXstation 8000, MicroVAX I, VAX 11/725, VAX 11/782

Processor Restrictions

MicroVAX 2000 and VAXstation 2000 systems require a TK50 drive for software distribution and updates.

Other Hardware Requirements

A minimum system configuration includes:

- 2MB of physical memory for a single node and 4MB of physical memory for a VAXcluster
- Console terminal
- 10,000 pages of page file quota
- 250 pages of working set quota (1,000 pages for cluster reporting)

Block Space Requirements (Block Cluster Size = 1):

Full VAX SPM Facility including the Collector:

Disk space required for installation:

18,000 blocks (9.2M bytes)

Disk space required for use (permanent):

11,000 blocks (7.0M bytes)

For VAX SPM Collector:

Disk space required for installation:

5,000 blocks (2.6M bytes)

Disk space required for use (permanent):

2,000 blocks (1.0M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration and software options.

OPTIONAL HARDWARE

Some of the advanced video displays require a VT125, VT240, VT241, VT340, VT341 or PRO 350 terminal. The PRO 350 terminal must be equipped with a VC241-A extended bit map graphic option and the PRO/Communications Software Package.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

digital™

March 1990
AE-LT42D-TE

SOFTWARE REQUIREMENTS

VMS Operating System Version 5.0 - 5.3

Prerequisite for Collector Licensing

At least one Full Function VAX SPM License is required in a multi-CPU or VAXcluster environment

VMS Tailoring

For VMS V5.x, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- System Programming Support
- Secure User's Environment
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

None

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape, TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Full VAX SPM Facility

Software Licenses: QL-850A*-**
Software Media: QA-850A*-**
Software Documentation: QA-850AA-GZ
Software Product Services: QT-850A*-**

VAX SPM Collector Facility

Software Licenses: QL-VUPA*-**
Software Media: QA-VUPA*-**
Software Documentation: QA-VUPAA-GZ
Software Product Services: QT-VUPA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.
™ MicroVAX, PRO, VAX, VAX SPM, VAXstation, VAXserver, VMS, and VT are trademarks of Digital Equipment Corporation.