System Support Addendum

PRODUCT NAME: VAX TEAMDATA, Version 1.4 **SSA 27.02.04-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900,

VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

MicroVAX I, VAXstation I, VAXstation 8000, VAX-11/725, VAX-11/782

Processor Restrictions

A TK50 Tape Drive is required for standalone MicroVAX 2000 and VAXstation 2000 systems.

A minimum of four megabytes of memory. Typical configurations will require more than four megabytes of memory

Mass storage with a minimum of 12,300 disk blocks for VAX TEAMDATA system software and sufficient space for database storage areas

Terminals

VAX TEAMDATA may be run on any VT100 (with AVO), VT102, VT125 (with AVO), VT220, VT240/241, or VT320/330/340 terminal.

Graphics can be displayed on VT125, VT240/241, or VT330/340 terminals.

Printers

VAX TEAMDATA reports can be printed on any Digital text printer.

Graphics can be printed on Digital devices which support either the Sixel (e.g, LJ250, LN03, LA75) or ReGIS (e.g., LCP01) protocols.

Block Space Requirements (Block Cluster Size =1):

Disk space required for installation:	13,700 blocks 7.0M bytes)
Disk space required for use (permanent):	12,900 blocks 6.6M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximations; actual sizes may vary depending on the users' system environment, configuration and software options selected.

OPTIONAL HARDWARE

Any device supported by the prerequisite or optional software.

LK201-BA or LK201-PA Keyboards (WPS-PLUS key engravings - recommended).

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

VMS Operating System V5.3

™ IDMS/R is a trademark of Cullinet Software, Inc.
® IBM is a registered trademark of IBM Coroporation.

digital™

May 1990
AE-LS63B-TE

VMS Workstation Software V4.2

VAX Rdb/VMS V3.1A (Run-Time, Development or Interactive Option)

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Save Set
- Network Support
- Secure User's Environment
- Programming Support

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

Certain versions of these products depend upon a specific version of the operating system. Please see the System Software Addendum of the product in question to determine which version you require.

ALL-IN-1 V2.3
VAX RALLY V2.1A
VAX DATATRIEVE V5.0
VAX CDD/Plus V4.1
VAX DBMS V4.1
VAX Xway V1.1
VIDA with IDMS/R™ V2.2
VIDA for DB2 V1.0

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-741A*-**
Software Media: QA-741A*-**
Software Documentation: QA-741AA-GZ
Software Product Services: QT-741A*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® The DIGITAL Logo is a registered trademark of Digital Equipment Corporation.

™ VAX, VMS, MicroVAX, VAXstation, VAXserver and ALL-IN-1 are trademarks of Digital Equipment Corporation.