# System Support Addendum

**PRODUCT NAME: VAX DEC/Test Manager, Version 3.2** **SSA 26.68.09-A**

## HARDWARE REQUIREMENTS

*Processors Supported:*

VAX: VAX 4000 Model 300,
VAXft 3000 Model 310,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX 9000-210, VAX 9000-410

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900,

VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

*Processors Not Supported:*

VAX-11/725, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000

*Other Hardware Required:*

A device capable of reading a TK50 is required to install this product on MicroVAX 2000 and VAXstation 2000 systems.

*Block Space Requirements (Block Cluster Size = 1):*

| | |
|---|---|
| Disk space required for installation: | 8,500 blocks (4.4M bytes) |
| Disk space required for use (permanent): | 6,000 blocks (3.1M bytes) |

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options.

*Memory Requirements for DECwindows Support:*

The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 8 MB.

The performance and memory usage of DECwindows applications are particularly sensitive to system configuration. Less memory may be required on the client system (the system where the software is installed and executed) if the server (the component that displays the application) resides on another system. More memory may be required on a system with several applications running or where it may be desirable to improve the performance of an application.

## OPTIONAL HARDWARE

None

## CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

digital™

**September 1990**
**AE-LT65D-TE**

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

**SOFTWARE REQUIREMENTS**

*For Systems Using Terminals: (No DECwindows Interface):*

- VMS Operating System V5.3 - V5.4

*For Workstations Running VWS:*

- VMS Operating System V5.3 - V5.4
- VMS Workstation Software V4.2

*For Workstations Running DECwindows:*

- VMS Operating System V5.3 - V5.4 (and necessary components of VMS DECwindows)

This product may run in either of the following ways:

- Stand-alone execution - Running the X11 display server and the client application on the same machine.
- Remote execution - Running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives the user the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; includes runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server (runtime support)

For remote execution, the following DECwindows components must be installed on the machine:

**Server Machine**

- VMS DECwindows Compute Server (runtime support)

**Client Machine**

- VMS DECwindows Compute Server (runtime support)

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- System Programming
- Utilities

**Note:** The Network Support VMS Tailoring Class is required only if VAX DEC/Test Manager users wish to record and playback DECwindows tests remotely on a workstation other than the workstation running VAX DEC/Test Manager.

**OPTIONAL SOFTWARE**

VAX Performance and Coverage Analyzer V3.0

VAX DEC/CMS V3.4

**GROWTH CONSIDERATIONS**

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

**DISTRIBUTION MEDIA**

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

**ORDERING INFORMATION**

Software Licenses: QL-927A*-**
Software Media: QA-927A*-**
Software Documentation: QA-927AA-GZ
Software Product Services: QT-927*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, DECwindows, VAX, VAXstation, VAXserver, VAXset and VMS are trademarks of Digital Equipment Corporation.