System Support Addendum

PRODUCT NAME: VAXset Package, Release 10 **SSA 27.07.09-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAX 4000 Model 300,
VAXft 3000 Model 310,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840, VAX 8842, VAX 8974, VAX 8978

VAX 9000-210, VAX 9000-410

VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900

VAXserver 6000-210, VAXserver 6000-310, VAXserver 6000-410, VAXserver 6000-420

Processors Not Supported

VAX-11/725, VAX-11/730, VAX-11/782, MicroVAX I, VAXstation I, VAXstation 8000.

Processor Restrictions

- A TK50 tape drive is required for MicroVAX 2000 and VAXstation 2000 systems.
- VAXset requires sufficient on-line mass storage to accommodate the components of this package and the libraries created by VAX DEC/CMS and VAX Language-Sensitive Editor/Source Code Analyzer.
- VAXset requires a valid VAX, MicroVAX or VAXstation configuration. For more information on valid system configuration, please refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

Terminals

Some components of VAXset require the following terminals for Character Cell Interface:

- A VT1xx, VT2xx, VT3xx, or ANSI CRT

Some components of VAXset require the following configuration for DECwindows Interface:

- A valid DECwindows workstation configuration. Please refer to the individual component's Software Product Description for valid configuration.

Block Space Requirements (Block Cluster Size = 1):

Disk space required for installation:	33,700 blocks (17.5M bytes)
Disk space required for permanent use:	28,200 blocks (14.5M bytes)

Note: Approximately 275 blocks should be added for each language you choose to have supported by the Editor component of the VAX Language-Sensitive Editor/Source Code Analyzer.

digital™

September 1990
AE-LT84F-TE

For installation of the Language-Sensitive Editor component of the VAX Language-Sensitive Editor/Source Code Analyzer with support for all the languages:

Disk space required for installation:	36,725 blocks (18.9M bytes)
Disk space required for permanent use:	31,225 blocks (16.0M bytes)

These counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration, and software options selected.

Memory Requirements for DECwindows Support

The minimum supported memory for this application running in a standalone DECwindows environment with both the client and server executing on that same system is 8 MB.

The performance and memory usage of DECwindows applications are particularly sensitive to system configuration. Less memory may be required on the client system (the system where the software is installed and executed) if the server (the component that displays the application) resides on another system. More memory may be required on a system with several applications running or may be desirable to improve the performance of an application.

OPTIONAL HARDWARE

None

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

* V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (28.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.

SOFTWARE REQUIREMENTS

For systems using terminals: (No DECwindows interface)

- VMS Operating System V5.3 - V5.4

Note: VMS DECwindows Compute Server Component must be installed to use VAX Performance and Coverage Analyzer.

For workstations running VWS:

- VMS Operating System V5.3 - V5.4
- VMS Workstation Software V4.2

For workstations running DECwindows:

- VMS Operating System (and necessary components of VMS DECwindows) V5.3 - V5.4

VAXset may run in either of the following ways:

- Stand-alone execution - Running the X11 display server and the client application on the same machine.
- Remote execution - Running the X11 display server and the client application on different machines.

VMS DECwindows is part of the VMS Operating System but must be installed separately. Installation of VMS DECwindows gives you the option to install any or all of the following three components:

- VMS DECwindows Compute Server (Base kit; provides runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For stand-alone execution, the following DECwindows components must be installed on the machine:

- VMS DECwindows Compute Server (Base Kit; provides runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

For remote execution, the following DECwindows components must be installed on the machines:

Server Machine

- VMS DECwindows Compute Server (Base Kit; provides runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

Client Machine

- VMS DECwindows Compute Server (Base Kit; provides runtime support)
- VMS DECwindows Device Support
- VMS DECwindows Programming Support

VMS Tailoring

For VMS V5.x, the following classes of VMS are required for full functionality of this layered product.

- VMS Required Saveset
- Programming Support
- Utilities
- Secure User's Environment

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

VAX Ada V2.1
VAX BASIC V3.4
VAX BLISS-32 Implementation Language V4.6
VAX C V3.1
VAX COBOL V4.3
VAX CDD/Plus V4.2
VAX DIBOL V4.1
VAX FORTRAN V5.4 - V5.5
VAX FORTRAN High-Performance Option V1.0
VAX FMS V2.4
VAX PASCAL V4.0 - V4.1
VAX PL/I V3.3 - V3.4
VAX RPG II V2.1
VAX SCAN V1.2

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this package may be different from the minimum requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of the VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software License: QL-965A*-**
Software Media: QA-965A*-**
Software Documentation: QA-965AA-GZ
Software Product Services: QT-965A*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

™ The DIGITAL Logo, VMS, DECwindows, VAX, MicroVAX, VAXstation, VAXserver and VAXset are trademarks of Digital Equipment Corporation.