System Support Addendum

PRODUCT NAME: WPS-PLUS for VMS, Version 4.0 **SSA 26.27.10-A**

HARDWARE REQUIREMENTS

Processors Supported

VAX: VAXft 3000-310,
VAX 4000 Model 300,
VAX 6000 Model 200 Series,
VAX 6000 Model 300 Series,
VAX 6000 Model 400 Series,
VAX 6000 Model 500 Series

VAX 8200, VAX 8250, VAX 8300, VAX 8350, VAX 8500, VAX 8530, VAX 8550, VAX 8600, VAX 8650, VAX 8700, VAX 8800, VAX 8810, VAX 8820, VAX 8830, VAX 8840

VAX 9000-210, VAX 9000-410

VAX-11/730, VAX-11/750, VAX-11/780, VAX-11/785

MicroVAX: MicroVAX II, MicroVAX 2000, MicroVAX 3100, MicroVAX 3300, MicroVAX 3400, MicroVAX 3500, MicroVAX 3600, MicroVAX 3800, MicroVAX 3900

VAXstation: VAXstation II, VAXstation 2000, VAXstation 3100 Series, VAXstation 3200, VAXstation 3500, VAXstation 3520, VAXstation 3540

VAXserver: VAXserver 3100, VAXserver 3300, VAXserver 3400, VAXserver 3500, VAXserver 3600, VAXserver 3602, VAXserver 3800, VAXserver 3900, VAXserver 4000 Model 300

VAXserver 6000-210, VAXserver 6000-220, VAXserver 6000-310, VAXserver 6000-320, VAXserver 6000-410, VAXserver 6000-420, VAXserver 6000-510, VAXserver 6000-520

Processors Not Supported

MicroVAX I, VAXstation I, VAX-11/725, VAX-11/782, VAXstation 8000

Processor Restrictions

MicroVAX II and VAXstation II support requires either an RD53 or RD52 with at least one other hard disk configuration.

Memory Requirements

WPS-PLUS for VMS	6 Mbytes
First 2 users	1 Mbyte
Minimum Configuration Total	7 Mbytes
Each additional user requires	.5 Mbytes

A device capable of reading a TK50 is required to install this product on MicroVAX 2000 and VAXstation 2000 systems.

Terminals supported include (text only):

- A VT100W series video terminal with the Advanced Video Option (AVO)*
- VT100 (AVO)*
- VT200, VT300, VT400, VT1000 series
- VAXstation series

* WPS-PLUS supports only those terminals which have Advanced Video Option (AVO). It does not support the VT100 without AVO, VT131, DECmate I, or WS78.

Disk Space Requirements (Block Cluster Size = 1:)

Users can install WPS-PLUS for VMS software on the system disk or on an alternate disk. WPS-PLUS installation requires the following amounts of disk space before and after installation:

- WPS-PLUS for VMS software on the system disk:

  BEFORE installation: 27,000 free blocks must be available on the system disk.

  AFTER installation: WPS-PLUS for VMS software will use 22,000 blocks on the system disk.

digital™

January 1991
AE-LT75E-TE

- WPS-PLUS for VMS software on an alternate disk:

  BEFORE installation: 27,000 free blocks must be available on the system disk and 17,500 free blocks on the alternate disk.

  AFTER installation: WPS-PLUS for VMS software will use 4,500 blocks on the system disk and 17,500 blocks on the alternate disk.

- If installed, the Encapsulated PostScript® graphics files require an additional 3,000 blocks on the disk on which WPS-PLUS for VMS software is installed.
- The linguistic components packaged with the WPS-PLUS software require an additional 1,500 blocks on the disk on which it is to be installed.

Note:

The sizes are approximations; actual sizes may vary depending on the user's system environment, configuration, and software options selected.

OPTIONAL HARDWARE

- LQP02 with optional Sheet Feeder
- LQP03 with optional Sheet Feeder
- LQP45 with optional Sheet Feeder
- LA50
- LA75
- LA100
- LA210
- LA324 with optional Sheet Feeder
- LN03
- LN03R
- DEClaser Series
- PrintServer40 (LPS40)
- PrintServer20 (LPS20)
- LP11
- LJ250
- LJ252
- QUME [1]
- HP LaserJet Series II Printer
- HP LaserJet Series III Printer

Note:

[1] The QUME Sprint 11/40-130 WT PLUS Wide Track Letter Quality Printer is available only from QUME, and supports a 256 column width.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed VAXcluster* configuration without restrictions. The *HARDWARE REQUIREMENTS* sections of this product's Software Product Description and System Support Addendum detail any special hardware required by this product.

V5.x VAXcluster configurations are fully described in the VAXcluster Software Product Description (SPD 29.78.xx) and include CI, Ethernet and Mixed Interconnect configurations.)

SOFTWARE REQUIREMENTS

- VMS Operating System V5.2 - V5.4
- VAX FMS (Runtime Only System) V2.4

Note:

VAX FMS Runtime Only System is a prerequisite to run WPS-PLUS for VMS. Customers who have not purchased the complete FMS product kit, must purchase the FMS Runtime Only System software license as well as the FMS Runtime Only Media Kit.

VMS Tailoring

For VMS V5.x systems, the following VMS classes are required for full functionality of this layered product:

- VMS Required Saveset
- Network Support
- Programming Support
- Secure User's Environment
- Utilities

For more information on VMS classes and tailoring, refer to the VMS Operating System Software Product Description (SPD 25.01.xx).

OPTIONAL SOFTWARE

- DECpage, V3.0 - V3.1
- VAX Grammar Checker V1.0
- DECprint Utility for PostScript to Sixel Printing for VMS V1.0

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

DISTRIBUTION MEDIA

Tape: 9-track 1600 BPI Magtape (PE), TK50 Streaming Tape

This product is also available as part of VMS Consolidated Software Distribution on CDROM.

ORDERING INFORMATION

Software Licenses: QL-AAMA*-**
Software Media: QA-AAMA*-**
Software Documentation: QA-AAMAA-GZ
Software Product Services: QT-AAMA*-**

* Denotes variant fields. For additional information on available licenses, services and media, refer to the appropriate price book.

The above information is valid at time of release. Please contact your local Digital office for the most up-to-date information.

® PostScript is a registered trademark of Adobe Systems, Inc.

® HP is a registered trademark of Hewlett-Packard Company.

™ The DIGITAL Logo, WPS-PLUS, CDA, CI, DECmate, DDIF, DX, FMS, LQP02, LA50, LA324, PrintServer, MicroVAX, VAX, VAXserver, VAXstation, VMS and VT are trademarks of Digital Equipment Corporation.