

# TCPware Master Index

## Guide to Abbreviations

**IG**—*TCPware Installation and Configuration*

**MG**—*TCPware Management Guide*

**NET**—*NETCU Command Reference*

**PG**—*TCPware Programmer's Guide*

**UG**—*TCPware User's Guide*

---

## Symbols

"Next Code" prompt UG 14-8

/etc/exports file MG 13-3

/etc/group file MG 13-3

/etc/passwd file MG 14-2

---

## A

abandoned leases MG 4-57

ACCEPT

argument for PG 3-9

description for PG 3-9

format for PG 3-9

status for PG 3-9

accept subroutine, Socket Library PG A-12

ACCEPT-WAIT

description for PG 3-8

format for PG 3-8

status for PG 3-9

Access Control List (ACL) MG 12-27, MG 14-13

applying to executables (FTP) MG 12-27

NFS file protection MG 14-10, MG 14-13, MG 14-16

Access restrictions

incoming MG 20-1

access restrictions

incoming MG 19-3, MG 20-1

ADD ACCESS command MG 20-1

ADD SERVICE command MG 20-1

MODIFY SERVICE command MG 20-2

REMOVE ACCESS command MG 20-2

SHOW ACCESS command MG 20-2

outgoing MG 19-3, MG 20-3

SET NOOUTGOING command MG 20-5

SET OUTGOING command MG 20-5

SHOW OUTGOING command MG 20-5

ACCOUNTING.H MG 12-9

ACE/client

configuring the TCPware IG 4-4

ACE/Client, definition UG 14-1

ACEMAIN\_CL utility MG 22-6

ACL types

ADD NET 2-100

MODIFY NET 2-100

SHOW NET 2-100

ADD ACCESS\_LIST MG 20-2

ADD ACE\_USER command, NETCU MG 22-7

ADD command

ACCESS\_LIST NET 2-20

ACE\_USER NET 2-22

ARP NET 2-24

EXPORT NET 2-26

GATEWAY NET 3-2

GROUP NET 2-29

KACL NET 2-31

KDB NET 2-33

KERBEROS USER NET 2-35

LOCAL-DOMAIN NET 3-3

MULTICAST\_GROUP NET 1-3, NET 2-36

PROXY NET 2-37

QUEUE-GROUP NET 3-4

ROUTE NET 2-39

SECONDARY NET 2-41

SERVICE NET 2-42

internal action routines NET 2-44

create\_rservice NET 2-44

create\_rservice\_kerberos NET 2-44

- create\_rservice\_secure NET 2-44
- create\_server\_process NET 2-44
- create\_telnet\_session NET 2-44
- ident\_protocol NET 2-44
- port\_mapper\_server NET 2-45
- report\_tcb\_metric NET 2-45
- time\_protocol NET 2-45
- options
  - HANDOFF NET 2-44
  - KEEPALIVE NET 2-44
  - MULTITHREADED NET 2-44
  - NONE NET 2-44
  - SHARE NET 2-44
- protocol values NET 2-42
  - BG\_TCP NET 2-42
  - BG\_UDP NET 2-42
  - STREAM, DGRAM NET 2-42
  - TCP NET 2-42
  - UDP NET 2-42
- additional documentation UG A-6
- address
  - DTE MG 8-3
  - IP of host, X.25 MG 8-4, MG 8-6
  - national, DNIC MG 8-3, MG 8-11
  - X.25 MG 8-3, MG 8-4, MG 8-6
- Address (A) record, DNS MG 3-20
- ADDRESS command
  - X.25 mapping database MG 8-7, MG 8-11
- Address Resolution Protocol (ARP) NET 1-2
  - displaying packets using TCPDUMP MG 30-28
  - mode
    - gateway capability MG 9-4
    - nonlocal internet address MG 9-4
- NETCU commands NET 1-2
- AFS database (AFSDB) record, DNS MG 3-21
- AgentX peers MG 7-14
- AIDA
  - configuring Compaq's IG 6-11
- Ancillary Control Process (ACP) MG 13-17, MG 13-21, MG 13-33
- anonymous
  - user access UG 3-16
  - users UG 3-15
- ANSI printer MG 15-16
- AO UG 12-21, UG 12-39
- API functions
  - closing socket PG 11-11
  - initializing client/server communication PG 11-5
  - performing all user input/output PG 11-6
  - performing the New PIN operation PG 11-10
  - performing the Next Code operation PG 11-9
  - performing user authentication PG 11-7
  - reading ACE/Server configuration PG 11-4
- APPEND command qualifier MG 12-26
- Application Programming Interface (API) routines PG 10-1

- application programs, writing PG 1-18
- Aspath Clause MG 9-66
- asynchronous
  - server, writing PG 13-5
  - system traps PG 13-6
  - transports, using PG 13-5
- Attributes Data File (ADF) MG 13-20
- auth\_destroy, RPC RTL PG 16-3
- authentication agent connection MG 25-2
- authentication passphrases
  - over network UG 16-20
- authentication private keys UG 16-20
- authnone\_create, RPC RTL PG 16-4
- AUTHORIZE utility (OpenVMS), Client NFS MG 13-4
- AUTHORIZED\_KEYS MG 25-14
- authunix\_create, RPC RTL PG 16-5
- authunix\_create\_default, RPC RTL PG 16-6
- Autonomous System (AS) MG 9-19
- AYT UG 12-21, UG 12-41

---

## B

- BACKWARD UG 12-21, UG 12-42
- banner page UG 5-16
- batch queues MG 15-10
- bcmp function, Socket Library PG A-14
- bcopy function, Socket Library PG A-15
- BELL UG 3-65
- Berkeley R Commands
  - R Services
    - exec service, customizing MG 16-4
    - host equivalence files MG 16-2
    - log file MG 16-4
    - login
      - NORMAL option MG 16-4
      - SECURE option MG 16-4
    - managing MG 16-1
    - Service Access List MG 16-1, MG 19-9
    - setting up MG 16-1
    - shell service, customizing MG 16-4
    - troubleshooting MG 16-5
  - security MG 19-9
- Berkeley R commands
  - configuring the IG 4-44
- BG\_RAW parameters and values NET 2-113
  - RECEIVE NET 2-113
  - SEND NET 2-113
- BG\_TCP parameters and values NET 2-113
  - DROP\_TIMER NET 2-113
  - PROBE\_TIMER NET 2-113
  - RECEIVE NET 2-113
  - SEND NET 2-113
- BG\_UDP parameters and values NET 2-113
  - RECEIVE NET 2-113

SEND NET 2-113  
 BGDRIVER\_TCP\_CLIENT.C file PG 2-3  
 BGDRIVER\_TCP\_SERVER.C file PG 2-3  
 BGDRIVER\_UDP\_CLIENT.C file PG 2-4  
 BGDRIVER\_UDP\_SERVER.C file PG 2-4  
 Bigendian PG 1-5  
 BINARY UG 12-21, UG 12-43  
 BIND MG 25-8  
 bind subroutine, Socket Library PG A-16  
 BOOTP server MG 4-1  
     BOOTP relay agent MG 4-2  
 Border Gateway Protocol (BGP) MG 9-45  
 BRK UG 12-21, UG 12-44  
 BSD socket data PG 1-14  
 bzero function, Socket Library PG A-18

## C

C socket library PG 8-1  
 callrpc, RPC RTL PG 16-7  
 Canonical name (CNAME) record, DNS MG 3-22  
 CAPTIVE accounts, using FTP MG 12-15  
 carrier, X.25 MG 8-6, MG 8-11  
 CCB\_UFLAGS bits PG 9-4  
 CERT, reporting security violations MG 19-2  
 Challenge Handshake Authentication Protocol (CHAP) MG 5-6  
 CHAP  
     Challenge Handshake Authentication Protocol MG 5-6  
 CHARGEND service MG 30-2  
 CHECK GATED CONFIGURATION command  
     NET 2-48  
 churn MG 9-45  
 CIPHER  
     3des UG 16-6  
     arcfour UG 16-6  
     blowfish UG 16-6  
     des UG 16-6  
     idea UG 16-6  
     none UG 16-6  
 cipher  
     3DES MG 25-2  
     3des UG 16-11  
     ARCFOUR MG 25-2  
     arcfour UG 16-11  
     BLOWFISH MG 25-2  
     blowfish UG 16-11  
     DES MG 25-2  
     des UG 16-11  
     IDEA MG 25-2  
     idea UG 16-11  
     none UG 16-11  
 class keyword  
     ALL UG 3-66  
     COMMANDS UG 3-66  
     NONE UG 3-66  
     PERFORMANCE UG 3-66  
     REPLIES UG 3-66  
 client classes MG 4-12  
 client mount commands MG 13-14  
 client-FTP file transfer formats UG 3-11  
     BLOCK UG 3-12  
     formatted ASCII UG 3-11  
     formatted binary UG 3-11  
     FORTRAN UG 3-12  
     IMAGE UG 3-12  
     VMS UG 3-12  
 clnt\_broadcast, RPC RTL PG 16-8  
 clnt\_call, RPC RTL PG 16-10  
 clnt\_control, RPC RTL PG 16-11  
 clnt\_create, RPC RTL PG 16-13  
 clnt\_destroy, RPC RTL PG 16-15  
 clnt\_freeres, RPC RTL PG 16-16  
 clnt\_geterr, RPC RTL PG 16-17  
 clnt\_pcreateerror, RPC RTL PG 16-18  
 clnt\_perrno, RPC RTL PG 16-19  
 clnt\_perror, RPC RTL PG 16-20  
 clnt\_spcreateerror, RPC RTL PG 16-18  
 clnt\_sperrno, RPC RTL PG 16-19  
 clnt\_sperror, RPC RTL PG 16-20  
 clntraw\_create, RPC RTL PG 16-21  
 clnttcp\_create, RPC RTL PG 16-23  
 clntudp\_bufcreate, RPC RTL PG 16-25  
 clntudp\_create, RPC RTL PG 16-25  
 Cluster alias failover MG 6-1  
 cluster alias failover MG 6-1  
     limitations MG 6-3  
     operation MG 6-1  
     setting up MG 6-2  
 cluster name in the NAMED.HOSTS File MG 3-43  
 CNAME records MG 3-22  
 CNFNET  
     command-driven configuration IG 5-3  
     invoking IG 5-2  
     menu-driven configuration IG 5-2  
     starting IG 3-4  
 CNFNET procedure IG 3-1  
 command line method UG 3-4, UG 3-8  
 command method  
     menu-driven IG 3-3  
 command reference UG 3-20  
     ACCOUNT UG 3-21  
     CLOSE UG 3-21  
     COPY UG 3-21  
     CREATE/DIR UG 3-21  
     DEFINE/KEY UG 3-21  
     DELETE UG 3-21  
     DIRECTORY UG 3-21  
     DISPLAY UG 3-21  
     ENABLE VMS\_PL UG 3-21

- ERROR\_EXIT UG 3-21
- EXIT UG 3-21
- GET UG 3-21
- HELP UG 3-21
- LDIR UG 3-21
- OPEN UG 3-21
- PUT UG 3-21
- PWD UG 3-21
- QUOTE UG 3-21
- REMOTEHELP UG 3-21
- RENAME UG 3-21
- SET BELL UG 3-21
- SET DEBUG UG 3-21
- SET DEFAULT UG 3-21
- SET HASH UG 3-21
- SET LOWERCASE UG 3-21
- SET PASSIVE UG 3-21
- SET STATUS UG 3-21
- SET VMS UG 3-21
- SITE UG 3-21
- SPAWN UG 3-21
- STRUCTURE UG 3-21
- TYPE UG 3-21
- USER UG 3-21
- command-driven option
  - @TCPWARE
    - CNFNET TCP IG 3-3
  - BASIC IG 3-3
  - FULL IG 3-3
  - TCP IG 3-3
  - TCPWARE IG 3-3
- command-driven option choices IG 3-3
- communication endpoint
  - internet addresses PG 1-4
  - naming PG 1-4
  - port numbers PG 1-4
- Compaq Computer Corporation documentation UG A-7
- Compaq WAN Line Configuration Options NET 2-203
- component shutdown menu IG 6-5
- component startup menu IG 6-5
- components for
  - access to network filesystem
    - NFS-OpenVMS Client UG 2-2
    - NFS-OpenVMS Server UG 2-2
  - accessing network tape drives
    - RCD client UG 2-9
    - RMT client UG 2-9
    - RMT service UG 2-9
- additional management
  - Network Control Utility (NETCU) UG 2-11
  - Simple Network Management Protocol (SNMP) services UG 2-11
- configuring hosts
  - DHCP/BOOTP UG 2-10
  - Domain Name Services UG 2-10
  - Point-to-Point Protocol (PPP) UG 2-10
  - Serial Line IP (SLIP) protocol UG 2-10
- logging in to remote hosts
  - RLOGIN UG 2-5
  - RSH UG 2-5
  - TELNET-OpenVMS UG 2-6
- network printing
  - line printer services UG 2-4
  - terminal server print services UG 2-4
- securing network resources
  - incoming access restrictions UG 2-13
  - IP Security Option (IPSO) UG 2-15
  - Kerberos authentication for
    - RCP UG 2-14
    - RLOGIN UG 2-14
    - RSH UG 2-14
    - TELNET UG 2-14
  - Kerberos server UG 2-14
  - outgoing access restrictions UG 2-13
  - packet filtering UG 2-14
  - secure shell (SSH) UG 2-15
  - token authentication UG 2-15
- sending network mail
  - IMAP server UG 2-7
  - POP3 server UG 2-7
  - SMTP-OpenVMS UG 2-7
  - TALK utility UG 2-8
- time synchronization
  - Network Time Protocol UG 2-11
  - TIMED UG 2-11
- transferring network files
  - FTP-OpenVMS UG 2-3
  - RCP UG 2-3
  - TFTP UG 2-3
- tunneling applications over IP
  - tunneling DECnet over IP UG 2-16
- conditional behavior MG 4-15
- configuration
  - DECnet over IP tunnels MG 27-2
  - IP-over-X.25 MG 8-1
  - Terminal Server Print Services MG 15-18
  - VAX P.S.I., X.25 MG 8-6
- Configuration Menu IG 6-4
- configuration method
  - command-driven IG 3-3
- configuration process
  - starting the IG 3-3
- connect subroutine, Socket Library PG A-19
- Connection Control Block (CCB) PG 7-2, PG 7-3
  - fields
    - CCB\_ASTRTN PG 9-3
    - CCB\_CHAN PG 9-3
    - CCB\_CMDRTN PG 9-3
    - CCB\_EF PG 9-3
    - CCB\_ISOPEN PG 9-3
    - CCB\_LIA PG 9-3
    - CCB\_LPORT PG 9-3
    - CCB\_RCVBCNT PG 9-3

- 
- CCB\_RCVBCT PG 9-3
  - CCB\_RCUIOC PG 9-3
  - CCB\_RIA PG 9-4
  - CCB\_RPORT PG 9-4
  - CCB\_SNDBCNT PG 9-4
  - CCB\_SNDBCT PG 9-4
  - CCB\_SNDIOC PG 9-4
  - CCB\_TIMO PG 9-4
  - CCB\_UFLAGS PG 9-4
  - FTP\_CCB\_DC\_CHAN PG 7-3
  - FTP\_CCB\_DC\_PN PG 7-3
  - FTP\_CCB\_FILENAME PG 7-3
  - FTP\_CCB\_FOR\_IA PG 7-3
  - FTP\_CCB\_FOR\_PN PG 7-3
  - FTP\_CCB\_FX\_TYPE PG 7-3
  - FTP\_CCB\_LOC\_IA PG 7-3
  - FTP\_CCB\_LOC\_PN PG 7-3
  - FTP\_CCB\_LOGGED\_IN PG 7-3
  - FTP\_CCB\_NETCHAN PG 7-4
  - FTP\_CCB\_NODENAME PG 7-4
  - FTP\_CCB\_OPENED PG 7-4
  - FTP\_CCB\_PASSWORD PG 7-4
  - FTP\_CCB\_PASV PG 7-4
  - FTP\_CCB\_RPLCOD PG 7-4
  - FTP\_CCB\_RPLEN PG 7-4
  - FTP\_CCB\_RPLTXT PG 7-4
  - FTP\_CCB\_STAT\_BYTES PG 7-4
  - FTP\_CCB\_STAT\_SECONDS PG 7-4
  - FTP\_CCB\_STATUS PG 7-4
  - FTP\_CCB\_STRU PG 7-4
  - FTP\_CCB\_USERNAME PG 7-4
  - TELNET library PG 9-2
  - connectionless service PG 1-3
  - connection-oriented services PG 1-2
  - control functions MG 18-7
  - COPY UG 3-13
  - COUNTRY specification
    - format of IG 3-15
  - creadcfg function, ACE/Client API PG 11-4
  - CREATE ACE\_USER\_DATABASE command,
    - NETCU MG 22-7
  - CREATE command
    - ACE\_USER\_DATABASE NET 2-49
    - EXPORT NET 2-50
    - GROUP NET 2-51
    - KDB NET 2-52
    - PROXY NET 2-53
    - SRVTAB NET 2-54
  - representation PG 1-5
  - Data Network Identification Code (DNIC) MG 8-3,
    - MG 8-6, MG B-1
  - Data network identification code (DNIC)
    - list MG B-1
  - Data Terminal Equipment (DTE), characteristics
    - MG 8-17
  - database, mapping MG 8-4
  - datagram
    - client, writing PG 1-20
    - forwarding MG 9-4
    - over X.25 MG 8-1
    - server, writing PG 1-21
  - daylight savings time support IG 3-13
  - DAYTIMED service MG 30-2
  - DEBUG NET 2-132
  - DEBUG command NET 1-14
  - DEBUG/IP command NET 2-56
  - DEBUG/TCP command NET 2-58
  - DEBUG/UDP command NET 2-61
  - declarations MG 4-7, MG 4-8
  - DECnet over IP MG 27-1
    - DNIPDRIVER MG 27-2
    - lines, using MG 27-2
    - troubleshooting MG 27-3
    - tunneling MG 27-1
    - tunnels
      - configuring MG 27-2
      - showing status MG 27-3
      - shutting down MG 27-3
      - starting MG 27-3
  - DECnet over IP tunnels
    - configuring the IG 4-13
  - DECnet/OSI, outgoing access restrictions MG 20-5
  - DECnet-to-SMTP mail MG 17-37
  - DECwindows
    - applications
      - displaying
        - local on remote host MG 29-2
        - remote on local host MG 29-3
    - security MG 19-11
    - transport interface MG 29-1
      - configuring MG 29-1
    - troubleshooting MG 29-4
  - default cipher
    - 3DES UG 16-23
  - default gateway
    - defining the IG 3-12
  - default remote printer for LPS
    - configuring the IG 4-25
  - default RIP announcements IG 4-18
  - DEFINE TIMEZONE command NET 2-66
  - DEFINE/KEY command NET 2-63
  - definition statements MG 9-19
  - delta time MG 13-27, MG 13-28, MG 14-20
    - examples MG 13-28
  - device type
- 
- ## D
- data
    - encoding schemes PG 1-5
    - exchange PG 1-5

- configuring the IG 5-6
- DHCP
  - address
    - allocation MG 4-10
    - pools MG 4-10
    - pools MG 4-10
  - address lease states
    - Abandoned MG 4-58
    - Bound MG 4-58
    - Free MG 4-58
    - Offered MG 4-58
    - Pinging MG 4-58
    - Reserved for Secondary MG 4-58
    - Static Assignment MG 4-58
  - address request and allocation process MG 4-3
  - administration MG 4-4
  - agent option space options MG 4-52
  - configuration MG 4-5
  - configuration file declarations MG 4-19
  - configuration file parameters MG 4-19
  - conversion tool MG 4-6
  - declaration
    - group MG 4-8
    - host MG 4-8
    - pool MG 4-10, MG 4-11
    - range MG 4-8
  - DNS dynamic updates MG 4-16
  - dump files, address lease states MG 4-58
  - failover protocol MG 4-65, MG 4-66
  - host name generation MG 4-17
  - lease
    - file statement
      - billing class MG 4-56
      - billing subclass MG 4-56
  - lease file statements
    - abandoned MG 4-55
    - client-hostname MG 4-56
    - domain-name MG 4-56
    - dynamic-bootp MG 4-56
    - ends MG 4-56
    - FQDN MG 4-56
    - hardware MG 4-56
    - hostname MG 4-56
    - starts MG 4-56
    - uid MG 4-56
  - lease format MG 4-55
  - leases MG 4-57
  - option type
    - ARRAYS MG 4-53
    - BOOLEAN MG 4-52
    - DATA STRING MG 4-53
    - INTEGER MG 4-53
    - IP-ADDRESS MG 4-53
    - RECORDS MG 4-54
    - TEXT MG 4-53
  - options MG 4-43
  - option all-subnets-local MG 4-44
  - option arp-cache-timeout MG 4-44
  - option bootfile-name MG 4-44
  - option boot-size MG 4-44
  - option broadcast-address ip-address MG 4-44
  - option cookie-servers MG 4-44
  - option default-ip-ttl MG 4-44
  - option default-tcp-ttl MG 4-44
  - option dhcp-client-identifier MG 4-44
  - option dhcp-max-message-size MG 4-45
  - option dhcp-parameter-request-list MG 4-45
  - option dhcp-server-identifier MG 4-45
  - option domain-name MG 4-45
  - option domain-name-servers MG 4-45
  - option extensions-path MG 4-46
  - option finger-server MG 4-46
  - option font-servers MG 4-46
  - option host-name MG 4-46
  - option ieee802-3-encapsulation MG 4-46
  - option ien116-name-servers MG 4-46
  - option impress-servers MG 4-46
  - option interface-mtu MG 4-46
  - option ip-forwarding MG 4-46
  - option irc-server MG 4-46
  - option log-servers MG 4-46
  - option lpr-servers MG 4-47
  - option mask-supplier MG 4-47
  - option max-dgram-reassembly MG 4-47
  - option merit-dump MG 4-47
  - option mobile-ip-home-agent MG 4-47
  - option nds-context MG 4-47
  - option nds-servers MG 4-47
  - option nds-tree-name MG 4-47
  - option netbios-dd-server MG 4-47
  - option netbios-name-servers MG 4-47
  - option netbios-node-type MG 4-47
  - option netbios-scope MG 4-48
  - option nis-domain MG 4-48
  - option nisplus-domain MG 4-48
  - option nisplus-servers MG 4-48
  - option nis-servers MG 4-48
  - option nntp-server MG 4-48
  - option non-local-source-routing MG 4-48
  - option ntp-servers MG 4-48
  - option option MG 4-48
  - option path-mtu-aging-timeout MG 4-48
  - option path-mtu-plateau-table MG 4-48
  - option perform-mask-discovery MG 4-49
  - option policy-filter MG 4-49
  - option pop-server MG 4-49
  - option resource-location-servers MG 4-49
  - option root-path MG 4-49
  - option router-discovery MG 4-49
  - option routers MG 4-49
  - option router-solicitation-address MG 4-49

- option smtp-server MG 4-49
- option static-routes MG 4-50
- option streettalk-directory-assistance-server MG 4-50
- option streettalk-server MG 4-50
- option subnet-mask MG 4-50
- option swap-server MG 4-50
- option tcp-keepalive-garbage MG 4-50
- option tcp-keepalive-interval MG 4-50
- option tftp-server-name MG 4-51
- option time-offset MG 4-51
- option time-servers MG 4-51
- option trailer-encapsulation MG 4-51
- option vendor-encapsulated-options MG 4-51
- option www-server MG 4-51
- option x-display-manager MG 4-51
- relay agent information option MG 4-51
- Safe-failover MG 4-61
  - boot file MG 4-63
  - configuration file statements MG 4-64, MG 4-65
    - backup-ack-interval MG 4-65
    - backup-pool-size MG 4-65
    - com-int-timeout MG 4-65
    - failover-port MG 4-65
    - mclt MG 4-65
    - safe-period-timeout MG 4-65
    - startup-delay MG 4-65
  - configuring MG 4-62
  - lease file statement
    - last-partner-transaction MG 4-66
    - revoked MG 4-66
  - lease file statements
    - acked-sec-interval seconds MG 4-66
    - acked-sec-interval-start seconds MG 4-66
    - active MG 4-66
    - backup MG 4-66
    - desired-interval seconds MG 4-66
    - expired MG 4-66
    - free MG 4-66
    - released MG 4-66
    - reset MG 4-66
    - safe-lease MG 4-66
    - transaction-id number MG 4-66
    - update-count n MG 4-66
  - partner-down state
    - transitioning MG 4-67
  - server modes
    - Primary MG 4-63
    - Secondary MG 4-63
    - Standalone MG 4-63
  - server state
    - backup-comint MG 4-64
    - backup-conflict MG 4-64
    - backup-normal MG 4-64
    - backup-partnerdown MG 4-64
    - backup-recover MG 4-64
    - failover-disabled MG 4-64
    - primary-comint MG 4-64
    - primary-conflict MG 4-64
    - primary-normal MG 4-64
    - primary-partnerdown MG 4-64
    - primary-recover MG 4-64
    - startup MG 4-64
    - state file MG 4-64
  - server process MG 4-2
  - spawning class MG 4-14
  - statement
    - add MG 4-19
    - allow and deny in pool declarations MG 4-22
    - allow and deny in scope MG 4-20, MG 4-21
    - always-broadcast MG 4-22
    - authoritative MG 4-24
    - class MG 4-25
    - if MG 4-30
    - invalid-ddns-chars MG 4-30
    - lease limit MG 4-30
    - lease-scan-interval MG 4-30
    - match MG 4-31
    - match if MG 4-31
    - min-lease-time MG 4-31
    - min-secs MG 4-32
    - one-lease-per-client MG 4-32
    - option definition MG 4-33
    - option space MG 4-33
    - pool MG 4-34
    - site-option-space MG 4-36
    - spawn with MG 4-36
    - vendor-option-space MG 4-39
  - statements
    - allow and deny MG 4-19
    - always-reply-rfc1048 MG 4-23
    - default-lease-time MG 4-25
    - dynamic-bootp-lease-cutoff MG 4-26
    - dynamic-bootp-lease-length MG 4-26
    - filename MG 4-26
    - fixed-address MG 4-27
    - get-lease-hostnames MG 4-27
    - group MG 4-27
    - hardware MG 4-28
    - host MG 4-29
    - max-delayed-acks MG 4-31
    - max-lease-time MG 4-31
    - next-server MG 4-32
    - option MG 4-33
    - ping MG 4-33
    - ping-retries MG 4-33
    - ping-timeout MG 4-33
    - range MG 4-34
    - requested-options-only MG 4-35
    - server-identifier MG 4-35

- server-name MG 4-35
- shared-network MG 4-36
- subnet MG 4-37
- use-host-decl-names MG 4-38
- use-lease-addr-for-default-route MG 4-38
- user-class MG 4-38
- vendor-class MG 4-38
  - subclass MG 4-13
- DHCP client MG 2-1
- DHCP server MG 4-1
- direct access facility (DAF), X.25 MG 8-6
- directories
  - how they are set up IG C-2
- directory checking UG 3-9
- FTP commands
  - ENABLE UG 3-45
- DISABLE command
  - FORWARDING NET 2-67
  - GATEWAY NET 2-67
  - REDIRECTS NET 2-68
- DISCARD utility MG 30-2
- DISCARD service MG 30-2
- Distributed Application Components PG 13-1
- Domain Name
  - logging options
    - category MG 3-13
    - channel MG 3-12
    - file MG 3-13
    - print-category MG 3-13
    - print-severity MG 3-13
    - print-time MG 3-13
    - severity MG 3-13
    - syslog daemon MG 3-13
- pointer (PTR) record, DNS MG 3-32
- service
  - client MG 3-1
    - logicals MG 3-1
    - setting up MG 3-1
    - starting up MG 3-2
  - database files
    - caching data in memory MG 3-13
    - editing MG 3-13
    - special characters MG 3-14
    - special commands MG 3-14
  - DNS concept MG 3-1
  - name servers
    - log file MG 3-3, MG 3-41
    - monitoring requests using TCPDUMP MG 30-29
    - monitoring responses using TCPDUMP MG 30-30
    - setting up MG 3-2
    - starting MG 3-3
    - stopping MG 3-3
  - NAMED.BOOT file MG 3-3
  - resource record
    - class MG 3-18
    - data MG 3-19
    - ttl MG 3-17
    - type MG 3-18
  - resource records MG 3-17
    - A MG 3-20
    - AFSDB MG 3-21
    - HINFO MG 3-23
    - ISDN MG 3-24
    - MB MG 3-25
    - MG MG 3-26
    - MINFO MG 3-27
    - MR MG 3-28
    - MX MG 3-29
    - NS MG 3-31
    - PTR MG 3-32
    - RP MG 3-33
    - RT MG 3-34
    - Start of Authority (SOA) MG 3-35
    - TXT MG 3-38
    - WKS MG 3-39
    - X25 MG 3-40
  - resource records, CNAME MG 3-22
  - special commands MG 3-14
    - \$include MG 3-16
    - \$origin MG 3-15
  - troubleshooting MG 3-41
  - zone types MG 3-6
- Domain Name Services MG 3-1
  - configuring the IG 4-15
- DTE MG 8-5
- DUMP command
  - GATED STATE NET 2-69
  - KDB NET 2-70
  - NAMED CACHE NET 2-71
  - NAMED STATISTICS NET 2-71
  - NAMED STATS NET 2-71
- Duress PIN UG 14-2
  - using a UG 14-8
- Dynamic Host Configuration Protocol client
  - configuring the IG 4-9
- Dynamic Host Configuration Protocol server
  - configuring the IG 4-12
- dynamic routing MG 9-5

---

## E

- EC UG 12-21, UG 12-48
- ECHOD service MG 30-2
- EGP importation MG 9-65
- EL UG 12-21, UG 12-49
- empty passwords MG 25-8
- ENABLE command
  - FORWARDING NET 2-73



GATEWAY NET 2-73  
 REDIRECTS NET 2-74  
 encrypted data UG 16-8  
 enterprise-wide networking UG 1-1  
 Error Status Codes PG 7-5  
 ESCAPE UG 12-21, UG 12-50  
 exclamation point MG 12-11  
 EXIT command NET 2-75, NET 3-11  
 EXIT command, NSLOOKUP MG 30-6  
 EXPORT  
     database  
         reloading on cluster MG 14-5  
         Server-NFS MG 14-4  
     options MG 14-5  
 exporting routes MG 9-71  
 expressions MG 4-39  
     Boolean MG 4-39  
     data MG 4-40  
     numeric MG 4-42  
 Exterior Gateway Protocol (EGP) MG 9-39  
 external applications over IP, tunneling UG 2-16  
 External Data Representation (XDR), protocol PG 1-10

## F

### file

attribute mapping, Server-NFS MG 14-11  
 formats and conversion, Server-NFS MG 14-14  
 locking MG 14-8  
 ownership mapping MG 13-7  
 printing UG 2-4  
 protection mapping MG 13-7  
 transfer format checking UG 3-10  
 type qualifiers (positional) UG 3-31  
 file location logicals  
     defining IG 3-1  
 File Transfer Protocol (FTP) MG 12-23  
 file version mapping  
     NFS-OpenVMS MG 13-11  
 file version mapping, NFS-OpenVMS MG 13-10  
 Filename mapping  
     NFSOpenVMS MG A-1  
 files  
     /etc/exports MG 13-3  
     /etc/group MG 13-3  
     /etc/passwd MG 14-2  
     /etc/printcap MG 15-7  
 ACECLIENT\_USER.DAT NET 1-7  
 BGDRIVER.EXE PG 2-2  
 BGDRIVER\_TCP\_CLIENT.C PG 2-3  
 BGDRIVER\_TCP\_SERVER.C PG 2-3  
 BGDRIVER\_UDP\_CLIENT.C PG 2-4  
 BGDRIVER\_UDP\_SERVER.C PG 2-4  
 CCBFLD PG 9-2  
 CCBFLD.H PG 9-21

DAYTIMED.C PG A-78  
 DEC\$PRIVATE\_SERVER\_SETUP.TEMPLATE  
     MG 29-2  
 DECW\$PRIVATE\_SERVER\_SETUP.COM MG 29-1  
 DECW\$PRIVATE\_SERVER\_SETUP.TEMPLATE  
     MG 29-2  
 DHCPD.CONF MG 4-67  
 DOMAIN-NAME-SERVICE.CACHE MG 3-6  
 FINGER.C PG 3-39  
 FTP\_APPEND\_FILE PG 7-4  
 FTP\_CONTROL.COM MG 12-10  
 FTP\_GET\_FILE PG 7-4  
 FTP\_PUT\_FILE PG 7-4  
 FTP\_STARTUP.COM MG 12-1  
 FTPDEF.H PG 7-2, PG 7-21, PG 7-46  
 FTPSAMPLE.C PG 7-2  
 FTPSERVER\_DTP.LOG MG 12-5, MG 19-11  
 GATED.CONF MG 9-2, MG 9-5, MG 9-7  
 HOST.EQUIV MG 16-2  
 HOSTS. PG A-22, PG A-23  
 Hosts.  
     updating IG 3-22  
 HOSTS.EQUIV MG 16-2  
 IF.ARP PG A-2  
 IF.H PG A-2  
 IN.H PG 6-21, PG A-2  
 INET.H PG A-2  
 INETDRIVER\_CLIENT.C PG 6-52  
 INETDRIVER\_SERVER.C PG 6-52  
 INETIODEF.H PG 6-5  
 IOCTL.H PG 6-24, PG A-2  
 IP Security Option (IPSO)  
     IPSO\_AUTHORITIES. MG 24-13  
     ROUTING.COM MG 24-12  
 IPSO\_AUTHORITIES. MG 24-13  
 KLOGIN MG 23-13  
 KSTASH.KEY MG 23-7  
 LOGIN.COM NET 1-1  
 LPD\_USERS.DAT MG 15-9  
 MISC\_CONTROL.COM MG 30-2  
 MYFILE.TXT NET 1-14  
 NAMED.BOOT MG 3-3  
 NAMESERV.H PG A-2  
 NAMESERVER.LOG MG 3-3, MG 3-41  
 NETCP.LOG NET 1-17  
 NETDB.H PG A-2  
 NETWORKS.DAT PG A-26, PG A-27  
 NFSSERVER.LOG MG 14-17, MG 14-24, MG 14-31  
 NTP.KEYS MG 10-7  
 ONCRPC\_FUNC.H PG 15-2  
 PPPLOGIN.TEMPLATE MG 5-8  
 PPPOPTIONS.DAT MG 5-5  
 PPPPAP.DAT MG 5-6  
 PPPSECRET.TEMPLATE MG 5-6  
 PRINCIPAL.OK MG 23-6  
 PRINTCAP. MG 15-4

sample entries in MG 15-4  
PROGRAM.H PG 14-4  
PROGRAM\_CLNT.C PG 14-4  
PROGRAM\_SVC.C PG 14-4  
PROGRAM\_XDR.C PG 14-4  
PROTOCOLS. PG A-29, PG A-30  
PSW\_\*.DAT MG 5-24  
RCMD.LOG MG 16-4  
RESOLV.H PG A-2, PG A-54  
RHOSTS MG 16-2  
    disabling use of MG 16-2  
ROUTE.H PG A-2  
ROUTING.COM NET 1-5, MG 6-2, MG 8-3, MG 9-2,  
    MG 24-12  
SDCONF.REC MG 22-6  
SERVICES. PG A-31, PG A-32  
SHUTNET.COM NET 1-7, MG 3-3  
SLIP\_SETUP.COM MG 5-21  
SLIPLOGIN.COM MG 5-24  
SNMP\_COMMON.H PG 10-1  
SNMP\_SUBAGENT.C PG 10-3  
SNMP\_SUBAGENT.H PG 10-3  
SNMPD.CONF MG 7-2, MG 7-10  
SNMPSERVER.LOG MG 7-15  
SOCKERR.H PG A-2, PG A-49  
SOCKET.H PG 6-21, PG A-2  
SOCKETVAR.H PG A-3, PG A-63  
SOCKLIB.OLB PG A-6  
STARTNET.COM NET 1-7, MG 3-3  
STARTUP\_RESOLVER.COM MG 3-2  
SYLOGIN.COM MG 19-11  
TCP SOCK\_CLIENT.C PG 8-3  
TCP SOCK\_SERVER.C PG 8-3  
TCPDRIVER\_CLIENT.C PG 3-39  
TCPDRIVER\_SERVER.C PG 3-39  
TCPSAMPLE.FOR PG 3-40  
TCPWARE\_CONFIGURE.COM MG 15-5  
TCPWARE\_RPCLIB\_SHR.EXE PG 15-1, PG 19-13  
TCPWARE\_RPCLIBD\_SHR.EXE PG 15-2,  
    PG 19-14  
TCPWARE\_RPCLIBG\_SHR.EXE PG 15-1,  
    PG 19-13  
TCPWARE\_RPCLIBT\_SHR.EXE PG 15-2,  
    PG 19-14  
TCPWARE SOCKLIB\_SHR.EXE PG A-6  
TCPWARE SOCKLIBD\_SHR.EXE PG A-6  
TCPWARE SOCKLIBT\_SHR.EXE PG A-6  
TELLIB.OLB PG 9-2  
TELNET\_CONTROL.COM MG 18-1  
TELNET\_SAMPLE.C PG 9-2  
TEMPLATE\_SNMPD.CONF MG 7-15  
TIMED.LOG MG 11-10, MG 11-11  
transferring PG 7-4  
TYPES.H PG A-3  
UCX\$INETDEF.H PG 2-2  
UCX\$IPC.OLB PG 2-2  
UCX\$IPC\_SHR.EXE PG 2-2  
UDP SOCK\_CLIENT.C PG 8-3  
UDP SOCK\_SERVER.C PG 8-3  
UDPDRIVER\_CLIENT.C PG 4-34  
UDPDRIVER\_SERVER.C PG 4-34  
UDPSAMPLE.FOR PG 4-34  
X25.CONF MG 8-4  
XDM\_ACCESS.DAT MG 28-3  
XDM\_CONFIG.DAT MG 28-2  
XDM\_CONFIG.TEMPLATE MG 28-2  
XDM\_KEYS.DAT MG 28-3  
XDM\_KEYS.TEMPLATE MG 28-3  
XDMSERVER.LOG MG 28-1, MG 28-2  
files, transferring UG 2-3  
FILTER NET 1-10  
filter routes MG 9-21  
FIND command  
    ARP NET 2-76  
    HOST NET 2-160  
    PROXY NET 2-77  
    ROUTE NET 2-78  
FINGER  
    command, NSLOOKUP MG 30-7  
    utility MG 30-2  
FINGERD service MG 30-2  
flag page UG 5-16  
FLAGS Options for DECnet over IP NET 2-206  
    (RETRY=seconds) NET 2-206  
    LISTENER NET 2-206  
FLAGS Options for Ethernet, FDDI, Token Ring, and  
    CLIP NET 2-204  
    NOBACKTOBACK NET 2-204  
    NOBROADCAST NET 2-204  
    RARP NET 2-205  
    TRAILERS NET 2-205  
    VCI NET 2-205  
FLAGS Options for SLIP and CSLIP NET 2-205  
    (RCV=n) NET 2-205  
    AUTOENABLE NET 2-205  
    COMPRESSED NET 2-205  
    DOUBLEEND NET 2-205  
    FLOWCONTROL NET 2-205  
FLUSH UG 12-21, UG 12-52  
FLUSH command NET 2-79  
FORWARD UG 12-21, UG 12-53  
forwarded ports  
    tunnels UG 16-8  
frame type  
    configuring the IG 5-7  
FSS console program  
    configuring the IG 5-10  
FSS system volume  
    configuring the IG 5-9  
FSS-OpenVMS  
    collecting information IG 5-9

## FTP

- client, building an PG 7-2

- command synonyms

- ASCII UG 3-21

- BELL UG 3-21

- BINARY UG 3-21

- BYE UG 3-21

- CD UG 3-21

- CONNECT UG 3-21

- DEBUG UG 3-21

- DISCONNECT UG 3-21

- H UG 3-21

- HASH UG 3-21

- IMAGE UG 3-21

- LCD UG 3-21

- LIST UG 3-21

- LOGIN UG 3-21

- LS UG 3-21

- MDELETE UG 3-21

- MGET UG 3-21

- MKDIR UG 3-22

- MPUT UG 3-22

- PASSIVE UG 3-22

- QUIT UG 3-21

- RECV UG 3-22

- RM UG 3-22

- RMDIR UG 3-22

- SEND UG 3-22

- STATUS UG 3-22

- VERBOSE UG 3-22

- Z UG 3-22

- features UG 3-2

- case conversion UG 3-2

- command line interface UG 3-2

- graphical user interface UG 3-2

- status messages UG 3-2

- wildcards UG 3-3

- log files MG 12-3

- login sequence UG 14-3

- preparation UG 3-1

- session UG 3-1

- session accounting MG 12-7

- accounting file record format MG 12-9

- configuration file MG 12-8

- configuring MG 12-8

- configuring the Accounting listener MG 12-9

- enabling MG 12-9

- file format MG 12-8

- subroutine library

- allocating connection control block PG 7-9

- appending remote file PG 7-11

- authorizing remote host user PG 7-30

- closing remote FTP server connection PG 7-13

- connection control block (CCB) fields PG 7-3

- copying remote host file PG 7-23, PG 7-40

- creating remote host directory PG 7-14

- deallocating a connection control block PG 7-16

- deleting remote host directory PG 7-18

- deleting remote host file PG 7-20

- error status, accessing PG 7-5

- FTP\_ACCOUNT PG 7-7

- FTP\_ALLOCATE\_CCB PG 7-9

- FTP\_APPEND\_FILE PG 7-11

- FTP\_CLOSE\_CONNECTION PG 7-13

- FTP\_CREATE\_DIRECTORY PG 7-14

- FTP\_DEALLOCATE\_CCB PG 7-16

- FTP\_DELETE\_DIRECTORY PG 7-18

- FTP\_DELETE\_FILE PG 7-20

- FTP\_GET\_CCB PG 7-21

- FTP\_GET\_FILE PG 7-23

- FTP\_GET\_LIST PG 7-26

- FTP\_GET\_NAME\_LIST PG 7-28

- FTP\_LOGIN\_USER PG 7-30

- FTP\_OPEN\_CONNECTION PG 7-33

- FTP\_PASSWORD PG 7-36

- FTP\_PRINT\_DIRECTORY PG 7-38

- FTP\_PUT\_FILE PG 7-40

- FTP\_QUOTE PG 7-42

- FTP\_RENAME\_FILE PG 7-44

- FTP\_SET\_DEBUG PG 7-46

- FTP\_SET\_DIRECTORY PG 7-48

- FTP\_SET\_PASV PG 7-50

- FTP\_SET\_STRU PG 7-51

- FTP\_SET\_TYPE PG 7-53

- FTP\_USER PG 7-55

- getting connection control block

- information PG 7-21

- getting remote host file listing PG 7-26

- getting remote host filename listing PG 7-28

- linking applications PG 7-2

- opening remote host FTP connection PG 7-33

- programming PG 1-10

- reference PG 7-6

- renaming remote host file PG 7-44

- returning remote host current directory PG 7-38

- sending remote host FTP command PG 7-42

- setting FTP library debugging mode PG 7-46

- setting passive mode PG 7-50

- setting remote directory PG 7-48

- specifying data representation type PG 7-53

- specifying file structure PG 7-51

- specifying remote host user PG 7-55

- specifying remote host user account PG 7-7

- specifying remote host user password PG 7-36

- FTP commands

- ACCOUNT UG 3-27

- CLOSE UG 3-28

- COPY UG 3-29
- CREATE/DIRECTORY UG 3-34
- DEFINE/KEY UG 3-36
- DELETE UG 3-39
- DIRECTORY UG 3-42
- DISPLAY UG 3-44
- ERROR\_EXIT UG 3-46
- EXIT UG 3-47
- GET UG 3-48
- HELP UG 3-52
- LDIR UG 3-53
- OPEN UG 3-54
- PUT UG 3-56
- PWD UG 3-60
- QUOTE UG 3-61
- REMOTEHELP UG 3-62
- RENAME UG 3-63
- SET
  - DEBUG
    - /CLASS UG 3-66
  - DEFAULT UG 3-68
- SHOW STATUS UG 3-75
- SITE UG 3-76
- SPAWN UG 3-77
- STRUCTURE UG 3-78
- TYPE UG 3-79
- USER UG 3-81
- FTP Subroutine Library
  - programming PG 7-1
- FTP-OpenVMS
  - ANONYMOUS support MG 12-11
  - CAPTIVE accounts MG 12-15
  - exiting, status on MG 12-2
  - logicals MG 12-12
  - passive state MG 12-24
  - RETR, STOR, APPE command qualifiers MG 12-26
  - security MG 12-2, MG 19-11
  - server implementation MG 12-23
  - service commands MG 12-23
    - ACCT MG 12-23
    - ALLO MG 12-23
    - APPE MG 12-23
    - CDUP MG 12-23
    - CWD MG 12-23
    - DELE MG 12-23
    - HELP MG 12-23
    - LIST MG 12-23
    - MDTM MG 12-23
    - MKD MG 12-23
    - MODE MG 12-24
    - NLST MG 12-24
    - NOOP MG 12-24
    - PASS MG 12-24
    - PASV MG 12-24
    - PORT MG 12-24
    - PWD MG 12-24

- QUIT MG 12-24
- REIN MG 12-24
- RETR MG 12-24
- RMD MG 12-24
- RNFR MG 12-24
- RNTO MG 12-24
- SITE MG 12-25
- SIZE MG 12-25
- STOR MG 12-25
- STOU MG 12-25
- STRU MG 12-26
- SYST MG 12-26
- TYPE MG 12-26
- USER MG 12-26
- startup command file MG 12-1
- troubleshooting MG 12-27
- FTP-OpenVMS server
  - configuring the IG 4-17
- FTPSERVER\_DTP.COM MG 12-3

---

## G

- GA UG 12-21, UG 12-54
- GateD NET 1-5, MG 9-5
  - BGP MG 9-5
  - configuration
    - file MG 9-5
    - language MG 9-8
  - EGP MG 9-5
  - Global Trace options MG 9-9
  - HELLO MG 9-5
  - NETCU commands MG 9-7
  - OSPF MG 9-5
  - RIP MG 9-5
  - route selection MG 9-5
  - Router Discovery Protocol MG 9-5
  - starting and stopping MG 9-7
- GATED.CONF file
  - conflict with ROUTING.COM file MG 9-2
  - creating the IG 4-18
- Gateway
  - Routing Daemon (GateD) MG 9-1
- gateway
  - address
    - default MG 9-1
    - examples MG 9-2
    - rotation MG 9-1
    - sequence of use MG 9-1
  - multiple gateway support MG 9-1
- gateway routing daemon
  - configuring the IG 4-17
- GET UG 3-13
- GET command
  - TGT NET 2-80
- get\_myaddress routine, RPC RTL PG 15-6

---

getdomainname/gethostname subroutines, Socket Library PG A-21

gethostbyaddr subroutine, Socket Library PG A-22

gethostbyname subroutine, Socket Library PG A-23

gethostid subroutine, Socket Library PG A-25

getnetbyaddr subroutine, Socket Library PG A-26

getnetbyname subroutine, Socket Library PG A-27

getpeername subroutine, Socket Library PG A-28

getprotobyname subroutine, Socket Library PG A-29

getprotobynumber subroutine, Socket Library PG A-30

getrpcbynumber, RPC RTL PG 15-7

getrpcport, RPC RTL PG 15-8

getservbyname subroutine, Socket Library PG A-31

getservbyport subroutine, Socket Library PG A-32

getsockname subroutine, Socket Library PG A-33

getsockopt subroutine, Socket Library PG A-34

GETSYI client PG 20-2

GETSYI sample programs PG 20-4

global pages IG 6-3

graphical user interface UG 3-6

- method UG 3-4, UG 3-9, UG 3-14
- from local to remote UG 3-14
- from remote to local UG 3-14

GROUP database, Client-NFS MG 13-3, MG 13-5

GROUP groups

- adding IG 4-8

Group Identification Mapping MG 13-5

GROUP users

- adding IG 4-7

guest account

- configuring the IG 5-9

---

## H

hardware clock overview IG 3-13

HASH UG 3-71

HELLO protocol MG 9-29

HELP

- command NET 2-81, NET 3-13
- command, NSLOOKUP MG 30-8

HNS\_LOOKUPOST subroutine, Socket Library PG A-35

HNS\_LOOKUPIA subroutine, Socket Library PG A-36

home directory MG 25-10

host

- declaration MG 4-9
- DNIC, X.25 MG 8-6
- information (HINFO) record, DNS MG 3-23
- IP address, X.25 MG 8-6
- local, X.25 MG 8-6
- network name, X.25 MG 8-6
- public key MG 25-20
- remote, X.25 MG 8-6

host equivalence file IG 4-46

host key

- creating MG 25-20
- private part MG 25-20
- public part MG 25-20

host name patterns MG 25-7

hostent structure, Socket Library PG 1-15, PG A-8

hosts, configuring UG 2-10

htonl subroutine, Socket Library PG A-37

htons subroutine, Socket Library PG A-38

HYPERchannel lines IG 3-7

HYPERchannel physical addresses NET 2-24

---

IBM VM NFS MG 13-24

IBM, supported models UG 12-4

IBM-to-OpenVMS keyboard map UG 12-13

ICMP

- redirect messages MG 9-33
- tracing options MG 9-32

IDENT service MG 30-3

idle timeout MG 25-7

IMAP

- configuration directives in .IMAPRC MG 17-28
- mail folders MG 17-27
- server MG 17-26
- state information files MG 17-29

implicit labeling MG 24-5

include command, DNS MG 3-16

incoming access restriction

- commands MG 12-3

inet\_ subroutines, Socket Library PG A-39

INET\_TCP

- DROP\_TIMER NET 2-120
- parameters and values NET 2-120
- PROBE\_TIMER NET 2-120

INETDRIVER Services

- programming PG 6-1

INETDRIVER services

- accepting and assigning channel PG 6-9
- assigning address to socket PG 6-13
- assigning channel to device PG 6-49
- asynchronous system trap (AST) PG 6-39
- call arguments PG 6-5
- call format PG 6-5
- cancelling I/O PG 6-51
- closing socket PG 6-52
- connecting to peer socket PG 6-15
- controlling socket characteristics PG 6-24
- creating desired socket type PG 6-47
- creating socket type

  - SOCK\_DGRAM PG 6-48
  - SOCK\_RAW PG 6-48
  - SOCK\_STREAM PG 6-48

- enabling AST delivery PG 6-39

- function codes
  - IO\$\_ACCEPT PG 6-9
  - IO\$\_ACCEPT\_WAIT PG 6-12
  - IO\$\_BIND PG 6-13
  - IO\$\_CONNECT PG 6-15
  - IO\$\_GETPEERNAME PG 6-17
  - IO\$\_GETSOCKNAME PG 6-19
  - IO\$\_GETSOCKOPT PG 6-21
  - IO\$\_IOCTL PG 6-24
  - IO\$\_LISTEN PG 6-27
  - IO\$\_RECEIVE PG 6-29
  - IO\$\_SEND PG 6-33
  - IO\$\_SETCHAR PG 6-37
  - IO\$\_SETMODE | IO\$\_M\_ATTNAST PG 6-39
  - IO\$\_SETSOCKOPT PG 6-41
  - IO\$\_SHUTDOWN PG 6-45
  - IO\$\_SOCKET PG 6-47
  - SYSS\$ASSIGN PG 6-49
  - SYSS\$CANCEL PG 6-51
  - SYSS\$DASSGN PG 6-52
- getting local address of socket PG 6-19
- getting peer name PG 6-17
- getting socket option values PG 6-21
- multicasting PG 6-3
- placing stream in listen state PG 6-27
- programming PG 1-9
- retrieving data from socket PG 6-29
- sample program PG 6-52
- sending data/messages PG 6-33
- sequence of operations PG 6-2
  - client PG 6-2
  - server PG 6-2
- setting socket options PG 6-41
- setting special device characteristics PG 6-37
- shutting down connection PG 6-45
- waiting for connection without accepting PG 6-12
- INETDRIVER, socket library PG 6-4
- INETDRIVER\_CLIENT.C file PG 6-52
- INETDRIVER\_SERVER.C file PG 6-52
- INGRES/Net IG 2-8
  - installing and configuring IG 6-9
- INITIALIZE/QUEUE command MG 15-15
  - Terminal Service Print Services MG 15-15
- insecure network UG 16-1
- Integrated Service Digital Network (ISDN) record,
  - DNS MG 3-24
- Internet
  - Bootstrap Protocol MG 4-1
  - Control Message Protocol (ICMP), redirect messages MG 9-1
  - Time Servers (ITs) MG 10-4
- internet
  - device driver (INETDRIVER) services PG 6-1
  - TCP/IP protocol suite UG A-5
- internet address classes IG 3-11
- Internet Message Protocol (IMAP) server
  - configuring the IG 4-18
- Internet Protocol Implementation Notes PG 5-3
- IO\$\_ACCEPT function code, INETDRIVER PG 6-9
- IO\$\_ACCEPT\_WAIT function code, INETDRIVER PG 6-12
- IO\$\_BIND function code, INETDRIVER PG 6-13
- IO\$\_CONNECT function code, INETDRIVER PG 6-15
- IO\$\_CREATE function code, TCPDRIVER PG 3-7
- IO\$\_GETPEERNAME function code, INETDRIVER PG 6-17
- IO\$\_GETSOCKNAME function code, INETDRIVER PG 6-19
- IO\$\_GETSOCKOPT function code, INETDRIVER PG 6-21
- IO\$\_IOCTL function code, INETDRIVER PG 6-24
- IO\$\_LISTEN function code, INETDRIVER PG 6-27
- IO\$\_READVBLK function code
  - TCPDRIVER
    - IO\$\_M\_DATACHECK modifier PG 3-11
    - IO\$\_M\_NOW modifier PG 3-11
    - IO\$\_M\_PACKED modifier PG 3-11
  - UDPDRIVER PG 4-7
    - IO\$\_M\_DATACHECK modifier PG 4-7
    - IO\$\_M\_NOW modifier PG 4-7
- IO\$\_READVBLK function code, TCPDRIVER PG 3-11
- IO\$\_RECEIVE function code, INETDRIVER PG 6-29
- IO\$\_SEND function code, INETDRIVER PG 6-33
- IO\$\_SENSEMODE | IO\$\_M\_CTRL function code
  - TCPDRIVER PG 3-15
  - UDPDRIVER PG 4-13
- IO\$\_SENSEMODE | IO\$\_M\_RD\_COUNT function code
  - TCPDRIVER
    - IO\$\_M\_CLR\_COUNT modifier PG 3-19
  - UDPDRIVER PG 4-16
    - IO\$\_M\_CLR\_COUNT modifier PG 4-16
- IO\$\_SENSEMODE | IO\$\_M\_RD\_COUNT function code,
  - TCPDRIVER PG 3-19
- IO\$\_SENSEMODE function code, TCPDRIVER PG 3-13
- IO\$\_SENSEMODE function code, UDPDRIVER PG 4-10
- IO\$\_SETCHAR function code, INETDRIVER PG 6-37
- IO\$\_SETMODE | IO\$\_M\_ATTNAST function code,
  - INETDRIVER PG 6-39
- IO\$\_SETMODE | IO\$\_M\_ATTNAST function code,
  - TCPDRIVER PG 3-21
- IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_SHUTDOWN function code
  - TCPDRIVER
    - IO\$\_M\_ABORT modifier PG 3-27
- IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_SHUTDOWN function code, UDPDRIVER PG 4-22
- IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_STARTUP function code, TCPDRIVER PG 3-28
- IO\$\_SETMODE | IO\$\_M\_CTRL function code,
  - TCPDRIVER PG 3-23
- IO\$\_SETSOCKOPT function code, INETDRIVER PG 6-41

- IO\$\_SHUTDOWN function code, INETDRIVER PG 6-45
- IO\$\_SOCKET function code, INETDRIVER PG 6-47
- IO\$\_WRITEVBLK | IO\$\_M\_EXTEND function code UDPDRIVER
  - IO\$\_M\_NOFORMAT modifier PG 4-28
- IO\$\_WRITEVBLK | IO\$\_M\_EXTEND function code, TCPDRIVER PG 3-32
- IO\$\_WRITEVBLK | IO\$\_M\_EXTEND function code, UDPDRIVER PG 4-28
- IO\$\_WRITEVBLK function code TCPDRIVER
  - IO\$\_M\_OUTBAND modifier PG 3-30
- UDPDRIVER
  - IO\$\_M\_NOFORMAT qualifier PG 4-25
- IO\$\_WRITEVBLK function code, TCPDRIVER PG 3-30
- IO\$\_WRITEVBLK function code, UDPDRIVER PG 4-25
- IOCTL.H file PG 6-24
- IP UG 12-21, UG 12-55
  - address, X.25 MG 8-4, MG 8-6
  - fragments, monitoring using TCPDUMP MG 30-32
  - Security Option (IPSO) MG 19-9, MG 24-1
    - automatic startup MG 24-12
    - basic options
      - setting first in datagram MG 24-11
      - stripping datagrams of MG 24-10
    - basic security option MG 24-2
    - commands, using MG 24-7
    - extended options, setting MG 24-10
    - extended security option MG 24-2
    - ICMP error messages, enabling MG 24-11
    - implementation, sample MG 24-5
    - implicit labels
      - received datagrams MG 24-9
      - transmitted datagrams MG 24-8
    - line options MG 24-3, MG 24-7
    - protection authorities MG 24-2
    - security levels MG 24-2
    - setting options MG 24-3
    - SHOW IPSO /FULL output MG 24-14
    - site-specific authorities, creating MG 24-13
    - system options MG 24-3
    - troubleshooting MG 24-15
- IP addresses
  - obtaining for network devices IG 1-4
- IP device driver (IPDRIVER) services PG 5-1
- IP multicast datagrams
  - receiving PG 1-17
  - sending PG 1-17
- IP Security Option (IPSO)
  - management MG 24-1
- IPDRIVER
  - ARP table entry flag PG 5-16
  - line ID values PG 5-15
- IPDRIVER external interface PG 5-34
- I/O functions PG 5-35
  - IO\$\_INITIALIZE PG 5-35
  - IO\$\_READVBLK PG 5-35
  - IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_SHUTDOWN PG 5-35
  - IO\$\_WRITEVBLK PG 5-35
- system service call codes PG 5-35
  - IO\$\_INITIALIZE (External) PG 5-37
  - IO\$\_INITIALIZE PG 5-36
  - IO\$\_READVBLK PG 5-36
  - IO\$\_READVBLK (External) PG 5-40
  - IO\$\_SETMODE PG 5-36
  - IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_SHUTDOWN (External) PG 5-42
  - IO\$\_WRITEVBLK PG 5-36
  - IO\$\_WRITEVBLK (External) PG 5-43
  - shutting down the external interface for the channel PG 5-42
- IPDRIVER services, programming PG 1-9
- IPDRIVER system service call
  - arguments PG 5-4
  - format PG 5-3
- IPDRIVER user interface system service call function code
  - assigning a channel to a device PG 5-31
  - canceling any pending I/O PG 5-33
  - closing the port PG 5-24
  - IO\$\_READVBLK PG 5-8
  - IO\$\_SENSEMODE | IO\$\_M\_CTRL PG 5-10
  - IO\$\_SENSEMODE | IO\$\_M\_RD\_COUNT PG 5-19
  - IO\$\_SETMODE | IO\$\_M\_CTRL PG 5-21
  - IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_SHUTDOWN PG 5-24
  - IO\$\_SETMODE | IO\$\_M\_CTRL | IO\$\_M\_STARTUP PG 5-25
  - IO\$\_WRITEVBLK PG 5-26
  - opening a port PG 5-25
  - P3 function codes PG 5-11
  - performing reads PG 5-10
  - reading
    - extended characteristics PG 5-12
    - network device information PG 5-12
    - the ARP table function PG 5-16
    - the routing table PG 5-13
  - reading the IP counters PG 5-19
  - receiving a datagram PG 5-8
  - releasing a channel PG 5-34
  - sending data PG 5-26
  - setting the port characteristics PG 5-21
  - SYSS\$ASSIGN PG 5-31
  - SYSS\$CANCEL PG 5-33
  - SYSS\$DASSGN PG 5-34
- IPDRIVER user interface system service call function codes PG 5-7
- IP-over-DECnet lines IG 3-7
- IP-over-X.25

- configuring MG 8-1
    - KEEPALIVE MG 8-3
    - maximum transmission unit MG 8-2
    - min/max transmission time MG 8-3
  - IP-over-X.25 devices IG 3-9
  - IPPROTO\_IP option
    - IP\_ADD\_MEMBERSHIP PG 6-44
    - IP\_DROP\_MEMBERSHIP PG 6-44
    - IP\_MULTICAST\_IF PG 6-43
    - IP\_MULTICAST\_LOOP PG 6-43
    - IP\_MULTICAST\_TTL PG 6-43
    - IP\_OPTIONS PG 6-43
  - IPPROTO\_TCP option
    - TCP\_KEEPAIVE PG 6-43
  - IPSO NET 1-10
    - protection authorities NET 2-125, PG A-41
      - DOE NET 2-125
      - GENSER NET 2-125
      - NSA NET 2-125
      - SCI NET 2-125
      - SIOP-ESI NET 2-125
    - security levels NET 2-124, PG A-44
  - IPSO\_AUTHORIZITIES.file MG 24-13
  - ipso\_getauthbyname, Socket Library PG A-41
  - ipso\_getauthbynumber, Socket Library PG A-43
  - ipso\_getlevelbyname, Socket Library PG A-44
  - ipso\_getlevelbynumber, Socket Library PG A-45
  - IPX network number
    - locating the IG 5-4
  - IPX node name
    - configuring the IG 5-7
  - IPX/SPX protocol
    - frame type IG 5-5
      - 802.2 IG 5-5
      - 802.2 SNAP IG 5-5
      - 802.3 IG 5-5
    - Ethernet II IG 5-5
- 
- K**
- keepalive UG 16-13
  - keepalive messages MG 25-8
  - KEEPALIVE, IP-over-X.25 configuration MG 8-3
  - Kerberos
    - administration server MG 19-8, MG 23-4, MG 23-9
    - application server MG 19-6
    - authentication MG 23-1
    - authenticator MG 19-5
    - command reference UG 4-2
    - command users MG 19-6
    - database MG 19-7, MG 19-8
      - adding to MG 23-7
      - creating MG 23-6
      - dumping to text file MG 23-8
      - loading from text file MG 23-8
    - modifying MG 23-7
    - removing entry from MG 23-8
    - showing entry MG 23-8
  - description MG 23-4
  - instance MG 19-4
  - management MG 19-4
  - management commands MG 19-8
  - master password
    - setting MG 23-8
    - stashing MG 23-7
    - troubleshooting if not stashed MG 23-7
  - name MG 19-4
  - principal MG 19-4
  - process MG 19-5
  - R Services
    - customizing authentication MG 23-14
    - KLOGIN file MG 23-13
    - management MG 23-13
    - requests parameter MG 23-13
  - RCP authentication MG 19-8
  - realm MG 19-4
  - RLOGIN authentication MG 19-8
  - RSH authentication MG 19-8
  - sequence MG 19-7
  - server MG 19-7, MG 23-4
    - Key Distribution Center (KDC) MG 19-7
    - keys file, creating MG 23-9
    - logicals MG 23-4
      - TCPWARE\_KERBV4\_MAXAGE MG 23-5
      - TCPWARE\_KERBV4\_PRIMARY MG 23-5
      - TCPWARE\_KERBV4\_REALM MG 23-5
      - TCPWARE\_KERBV4\_SRVTYM MG 23-4
    - management MG 23-1
    - management commands MG 23-6
    - managing from server MG 23-9
    - process MG 19-5
  - service ticket MG 19-5
  - session, typical MG 19-6
  - TELNET
    - authentication MG 19-8
    - commands MG 23-14
    - management MG 23-14
    - proper operation MG 23-14
    - request parameter MG 23-14
  - terms MG 19-4
  - ticketgranting ticket MG 19-5, MG 19-6
  - user command
    - GET TGT UG 4-1
    - REMOVE TICKETS UG 4-1
    - SET KERBEROS\_PASSWORD UG 4-1
    - SHOW TICKETS UG 4-1
  - user commands MG 19-7
  - Kerberos applications IG 4-22



Kerberos server  
   configuring the IG 4-20  
 Kerberos user commands  
   GET TGT UG 4-3  
   REMOVE TICKETS UG 4-5  
   SET KERBEROS\_PASSWORD UG 4-6  
   SHOW TICKETS UG 4-7  
 key designations for three terminal types UG 3-36,  
   UG 12-24  
 Key-Names NET 2-63  
 keyword value pairs MG 25-4  
 KILL CONNECTIONS command NET 2-82  
 KLOGIN file MG 23-13  
 klogin service MG 23-13  
 kshell service MG 23-13

---

## L

line identification codes  
   entering IG 3-5  
 line IDs IG 3-8  
 line printer services  
   configuring the IG 4-24  
 Line Printer Services (LPS) MG 15-1  
   batch queues MG 15-10  
   client MG 15-1  
     troubleshooting MG 15-7  
   LPR command MG 15-10  
   LPRSMB symbiont, tuning logicals MG 15-7  
   PRINT command MG 15-10  
   VMSLPRSMB symbiont, tuning logicals MG 15-6  
 LISTEN  
   argument for PG 3-8  
   description for PG 3-7  
   format for PG 3-7  
   status for PG 3-8  
 listen subroutine, Socket Library PG A-46  
 Littleendian PG 1-5  
 LOAD command  
   GATED CONFIGURATION NET 2-83  
   KDB NET 2-84  
 loadable time zone rules IG 3-17  
 local hostname  
   defining the IG 3-21  
 local mount point MG 13-29  
 local system commands UG 3-22  
   DEFINE/KEY UG 3-22  
   HELP UG 3-22  
   LCD UG 3-22  
   LDIR UG 3-22  
   SET BELL UG 3-22  
   SET DEBUG UG 3-22  
   SET HASH UG 3-22  
   SET LOWERCASE UG 3-22  
   SET PASSIVE UG 3-22  
   SET VMS UG 3-22  
   SHOW STATUS UG 3-22  
   SPAWN UG 3-22  
   STRUCTURE UG 3-23  
   TYPE UG 3-23  
 local time zone  
   defining the IG 3-19  
 LOCAL\_FLOW UG 12-21  
 LOCAL\_FLOW\_CONTROL UG 12-57  
 LocalPref MG 9-45  
 LOG NET 1-8, NET 1-11  
 log file MG 12-5  
 logical  
   DECW\$DISPLAY UG 16-4  
   FTP\_STARTUP UG B-1, MG 12-2  
   NETCU\_STARTUP NET 1-1, UG B-1  
   TCPWARE\_ACECLIENT\_DATA\_DIRECTORY  
     MG 22-4  
   TCPWARE\_ACECLIENT\_NETWORK MG 22-4  
   TCPWARE\_ACECLIENT\_PASSCODE\_TIME  
     UG B-3, MG 22-5  
   TCPWARE\_ACECLIENT\_CL UG B-2, MG 22-4  
   TCPWARE\_ACECLIENT\_DATA\_DIRECTORY  
     UG B-2, MG 22-6  
   TCPWARE\_ACECLIENT\_ENABLE UG B-2,  
     MG 22-4  
   TCPWARE\_ACECLIENT\_NETWORK UG B-3  
   TCPWARE\_ACECLIENT\_REMO UG B-3, MG 22-5  
   TCPWARE\_ACECLIENT\_SHR UG B-3, MG 22-5  
   TCPWARE\_DOMAINLIST UG B-3, MG 3-2  
   TCPWARE\_DOMAINNAME UG B-3, PG A-21, PG  
     A-52, PG A-59, MG 3-2  
   TCPWARE\_FTP\_220\_REPLY UG B-4, MG 12-13  
   TCPWARE\_FTP\_221\_REPLY UG B-4, MG 12-14  
   TCPWARE\_FTP\_230\_REPLY UG B-4, MG 12-14  
   TCPWARE\_FTP\_421\_REPLY UG B-5, MG 12-14,  
     MG 19-12  
   TCPWARE\_FTP\_ALL\_VERSIONS UG B-5,  
     MG 12-15  
   TCPWARE\_FTP\_ALLOWCAPTIVE UG B-5,  
     MG 12-15  
   TCPWARE\_FTP\_ANONYMOUS\_230\_REPLY  
     UG B-6, MG 12-15  
   TCPWARE\_FTP\_ANONYMOUS\_RIGHTS UG B-6,  
     MG 12-16, MG 19-12  
   TCPWARE\_FTP\_ANONYMOUS\_ROOT UG B-6,  
     MG 12-5, MG 12-16, MG 19-12  
   TCPWARE\_FTP\_DISALLOW\_UNIX\_STYLE  
     UG B-6, MG 12-16  
   TCPWARE\_FTP\_DONT\_REPORT\_FILESIZE  
     UG B-6  
   TCPWARE\_FTP\_EXTENSION\_QUANTITY UG B-7  
   TCPWARE\_FTP\_GETHOST\_MAX\_TIME UG B-7,  
     MG 12-17  
   TCPWARE\_FTP\_IDLE\_TIMEOUT UG B-7,  
     MG 12-17

TCPWARE\_FTP\_KEEP\_DIR\_EXT UG B-7  
TCPWARE\_FTP\_LOG\_ALL\_USERS UG B-8,  
MG 12-18  
TCPWARE\_FTP\_LOGFILE UG B-8, MG 12-5,  
MG 12-18, MG 19-12  
TCPWARE\_FTP\_MAX\_SERVERS UG B-8,  
MG 12-18  
TCPWARE\_FTP\_MAXREC UG B-8, MG 12-18  
TCPWARE\_FTP\_MESSAGE\_FILE UG B-8,  
MG 12-18  
TCPWARE\_FTP\_ONLY\_BREAK\_ON\_CRLF  
UG B-9, MG 12-19  
TCPWARE\_FTP\_PASSWORD\_WARNING\_  
MESSAGE UG B-9, MG 12-19  
TCPWARE\_FTP\_PASSWORD\_WARNING\_TIME  
UG B-9, MG 12-19  
TCPWARE\_FTP\_PROMPT\_NODENAME MG 12-11  
TCPWARE\_FTP\_RECEIVE\_THRESHOLD UG B-9,  
MG 12-19  
TCPWARE\_FTP\_RECODE\_NONVMS\_FILE\_  
NAMES UG B-9, MG 12-20  
TCPWARE\_FTP\_ROOT UG B-10, MG 12-4,  
MG 12-5, MG 12-20  
TCPWARE\_FTP\_SEMANTICS\_FIXED\_IGNORE\_  
CC UG B-10, MG 12-21  
TCPWARE\_FTP\_SEMANTICS\_VARIABLE\_  
IGNORE\_CC UG B-11, MG 12-21  
TCPWARE\_FTP\_SERVER\_DATA\_PORT\_RANGE  
UG B-11, MG 12-21  
TCPWARE\_FTP\_SERVER\_LOG\_LIMIT UG B-11,  
MG 12-4, MG 12-5, MG 12-21  
TCPWARE\_FTP\_SERVER\_RELAXED\_PORT\_  
COMMAND UG B-11, MG 12-21  
TCPWARE\_FTP\_SET\_DEFAULT\_TO\_ROOT  
MG 12-4  
TCPWARE\_FTP\_STRIP\_VERSION UG B-11,  
MG 12-22  
TCPWARE\_FTP\_SYST\_BANNER UG B-12,  
MG 12-22  
TCPWARE\_FTP\_UNIX\_STYLE\_BY\_DEFAULT  
UG B-12, MG 12-22  
TCPWARE\_FTP\_UNIX\_STYLE\_CASE\_  
INSENSITIVE UG B-12, MG 12-22  
TCPWARE\_FTP\_username\_ROOT UG B-10,  
MG 12-5, MG 12-20  
TCPWARE\_FTP\_WINDOW UG B-12, MG 12-10,  
MG 12-23  
TCPWARE\_IMAP\_UDPATE\_LOGIN\_TIME  
MG 17-27  
TCPWARE\_KERBV4\_MAXAGE UG B-12, MG 23-4,  
MG 23-5  
TCPWARE\_KERBV4\_PRIMARY UG B-12,  
MG 23-4, MG 23-5  
TCPWARE\_KERBV4\_REALM UG B-13, MG 23-4,  
MG 23-5  
TCPWARE\_KERBV4\_RLOGIN UG B-13, MG 23-4  
TCPWARE\_KERBV4\_RSHELL UG B-13, MG 23-4  
TCPWARE\_KERBV4\_SRVTYPE UG B-13, MG 23-4  
TCPWARE\_KERBV4\_TELNET UG B-13, MG 23-4  
TCPWARE\_KERBV4\_TKFILE UG B-13, MG 23-4  
TCPWARE\_LINE MG 5-25  
TCPWARE\_LPD\_DEFAULT\_USER MG 15-11  
TCPWARE\_LPD\_DEFAULT\_USER UG B-13,  
MG 15-9  
TCPWARE\_LPD\_OPTIONS UG B-13, MG 15-11  
TCPWARE\_LPD\_qname\_FORM\* MG 15-11  
TCPWARE\_LPD\_qname\_OPTION MG 15-11  
TCPWARE\_LPD\_qname\_PARAMETER\* MG 15-12  
TCPWARE\_LPD\_qname\_QUEUE\* MG 15-12  
TCPWARE\_LPD\_qname\_\*\_FORM UG B-13  
TCPWARE\_LPD\_qname\_\*\_PARAMETER UG B-14  
TCPWARE\_LPD\_qname\_\*\_QUEUE UG B-14  
TCPWARE\_LPD\_qname\_OPTION UG B-13  
TCPWARE\_LPD\_SPOOL UG B-14, MG 15-9,  
MG 15-12  
TCPWARE\_LPR\_PRINTER UG B-14, MG 15-6  
TCPWARE\_LPR\_qname\_PRINTER MG 15-5  
TCPWARE\_LPR\_qname\_PRINTER\_DEFAULT  
MG 15-5  
TCPWARE\_LPR\_qname\_PRINTER UG B-14  
TCPWARE\_LPR\_qname\_PRINTER\_DEFAULT  
UG B-14  
TCPWARE\_LPR\_QUEUES UG B-14, MG 15-5  
TCPWARE\_LPR\_SPOOL UG B-14, MG 15-5  
TCPWARE\_LPRSM UG B-15  
TCPWARE\_LPRSM\_qname\_PRECONN MG 15-7  
TCPWARE\_LPRSMB\_\*\_RETRY\_INTERVAL  
MG 15-7  
TCPWARE\_LPRSMB\_\*\_TIMEOUT MG 15-7  
TCPWARE\_LPRSMB\_qname\_RETRY\_INTERVAL  
MG 15-7  
TCPWARE\_LPRSMB\_qname\_TIMEOUT MG 15-7  
TCPWARE\_NAMED\_MAX\_CACHE\_TTL UG B-15,  
MG 3-13  
TCPWARE\_NAMESERVERS UG B-15, MG 3-2  
TCPWARE\_NFS\_ACCESS\_IDENTIFIER UG B-15,  
MG 14-16  
TCPWARE\_NFS\_DFLT\_GID UG B-15, MG 14-20  
TCPWARE\_NFS\_DFLT\_UID UG B-15, MG 14-20  
TCPWARE\_NFS\_DIRLIFE\_TIMER UG B-16,  
MG 14-20  
TCPWARE\_NFS\_DIRREAD\_LIMIT UG B-16,  
MG 14-20  
TCPWARE\_NFS\_DIRTIME\_TIMER UG B-16,  
MG 14-20  
TCPWARE\_NFS\_DYNAMIC\_EXPORT UG B-16,  
MG 14-5  
TCPWARE\_NFS\_DYNAMIC\_PROXY UG B-16,  
MG 14-4  
TCPWARE\_NFS\_FILE\_CACHE\_SIZE UG B-16,  
MG 14-21  
TCPWARE\_NFS\_LOG\_CLASS UG B-17, MG 14-17  
TCPWARE\_NFS\_NOCHECKSUM UG B-17,  
MG 14-21

- 
- TCPWARE\_NFS\_OPENFILE\_TIMER UG B-17, MG 14-21
  - TCPWARE\_NFS\_PCNFSD\_DFLTPRTOPT UG B-17, MG 14-21
  - TCPWARE\_NFS\_PCNFSD\_ENABLE UG B-17, MG 14-19
  - TCPWARE\_NFS\_PCNFSD\_JOB\_LIMIT UG B-17, MG 14-22
  - TCPWARE\_NFS\_PCNFSD\_PRINTER UG B-17, MG 14-22
  - TCPWARE\_NFS\_PCNFSD\_PRINTER\_LIMIT UG B-18, MG 14-22
  - TCPWARE\_NFS\_PCNFSD\_SPOOL UG B-18, MG 14-19
  - TCPWARE\_NFS\_PORT UG B-18, MG 14-22
  - TCPWARE\_NFS\_SECURITY UG B-18, MG 14-17
  - TCPWARE\_NFS\_TCP\_THREADS UG B-19, MG 14-22
  - TCPWARE\_NFS\_UDP\_THREADS UG B-19, MG 14-22
  - TCPWARE\_NFS\_XID\_CACHE\_SIZE UG B-19, MG 14-23
  - TCPWARE\_PCNFSD\_DFLTPRTOPT UG B-19, MG 14-21
  - TCPWARE\_POP3\_UDPATE\_LOGIN\_TIME MG 17-30
  - TCPWARE\_PPPD\_DEBUG\_LEVEL UG B-19, MG 5-19
  - TCPWARE\_PPPD\_OPCOM\_LEVEL UG B-19, MG 5-19
  - TCPWARE\_QUOTE UG B-20, MG 30-24
  - TCPWARE\_RCMD\_FLAGS UG B-20, MG 16-2
  - TCPWARE\_RCMD\_OUTPUT UG B-20, MG 16-4, MG 16-5
  - TCPWARE\_RES\_OPTIONS UG B-20, MG 3-2
  - TCPWARE\_SLIP\_ UG B-20
  - TCPWARE\_SLIP\_n MG 5-20
  - TCPWARE\_SNMP\_DEBUG UG B-26, PG 10-3
  - TCPWARE\_SVCORDER UG B-26, PG A-23
  - TCPWARE\_TCLB\_BIAS UG B-26, MG 3-45
  - TCPWARE\_TELNET\_WINDOW UG B-26
  - TCPWARE\_TELNETD\_DEFCHAR UG B-26, MG 18-4
  - TCPWARE\_TELNETD\_FLAGS UG B-26
  - TCPWARE\_TELNETD\_INTRO\_MSG UG B-27, MG 19-14
  - TCPWARE\_TELNETD\_NO\_FORCED\_HANGUP UG B-26, MG 18-2, MG 18-4
  - TCPWARE\_TIMED\_EXCLUDE UG B-27, MG 11-4
  - TCPWARE\_TIMED\_INCLUDE UG B-27
  - TCPWARE\_TIMED\_MODE UG B-27, MG 11-4
  - TCPWARE\_TIMEZONE UG B-27, PG A-76
  - TCPWARE\_TSSYM\_ UG B-28
  - TCPWARE\_TSSYM\_\*\_RETRY\_INTERVAL UG B-28, MG 15-20
  - TCPWARE\_TSSYM\_\*\_TIMEOUT MG 15-20
  - TCPWARE\_TSSYM\_\*\_TIMEOUT UG B-28
  - TCPWARE\_TSSYM\_qname MG 15-16, MG 15-17
  - TCPWARE\_TSSYM\_qname\_RETRY\_INTERVAL MG 15-20
  - TCPWARE\_TSSYM\_qname\_TIMEOUT MG 15-20
  - TCPWARE\_TSSYM\_qname\_RETRY\_INTERVAL UG B-28
  - TCPWARE\_TSSYM\_qname\_TIMEOUT UG B-28
  - TCPWARE\_VMSLPRSMB\_qname\_PRECONN UG B-28
  - TCPWARE\_VMSLPRSMB\_\*\_RETRY\_INTERVAL UG B-28, MG 15-6
  - TCPWARE\_VMSLPRSMB\_\*\_TIMEOUT UG B-29, MG 15-6
  - TCPWARE\_VMSLPRSMB\_qname\_PRECONN MG 15-6
  - TCPWARE\_VMSLPRSMB\_qname\_RETRY\_INTERVAL UG B-28, MG 15-6
  - TCPWARE\_VMSLPRSMB\_qname\_TIMEOUT UG B-28, MG 15-6
  - TELNET\_WINDOW MG 18-2
  - TELNETD\_DEFCHAR MG 18-2
  - TELNETD\_FLAGS MG 18-2
  - TELNETD\_INTRO\_MSG MG 18-2
  - TT2\$M\_HANGUP MG 18-4
  - UCX\$DEVICE UG B-29, PG 2-3
  - UCX\$INET\_HOST UG B-29, PG 2-3
  - UCX\$IPC\_SHR UG B-29, PG 2-3
  - WIN/TCP PG A-11
  - login interfaces UG 14-3
  - LOWERCASE UG 3-72
  - LPD Server
    - access file
      - creating MG 15-9
      - description MG 15-9
      - format MG 15-9
      - name MG 15-9
      - sample MG 15-10
      - username logical MG 15-10
    - command qualifiers MG 15-11
    - control files MG 15-9
    - data files MG 15-9
    - description MG 15-7
    - function MG 15-7
    - option MG 15-8
    - troubleshooting MG 15-13
    - use of /etc/printcap file MG 15-7
  - LPD server
    - configuring the IG 4-29
  - LPD server access file
    - building the IG 4-30
  - LPQ UG 5-6
  - LPR UG 5-8
  - LPR command, Line Printer Services MG 15-10
  - LPRM UG 5-12
  - LPS
    - client commands
      - LPQ MG 15-2

- LPR MG 15-2
- LPRM MG 15-2
- PRINT MG 15-2
- print forms, DEFINE/FORM qualifiers MG 15-3
- print symbionts
  - TCPWARE\_LPR SMB MG 15-2
  - TCPWARE\_VMSLPR SMB MG 15-2
- system logicals, VMSLPR SMB tuning logicals MG 15-6
- LPS client OpenVMS print queues
  - configuring the IG 4-26
- LPS for batch startup
  - configuring the IG 4-28
- LS command, NSLOOKUP MG 30-10
- LSERVER command, NSLOOKUP MG 30-14

---

## M

### Mail

- Exchanger (MX) record, DNS MG 3-29
- Information (MINFO) record, DNS MG 3-27
- mail
  - delivery mechanisms, using MG 17-7
  - parameters MG 17-16
- mail monitoring MIB
  - MtaFailedConvertedMessages MG 17-12
  - MtaLoopsDetected MG 17-13
  - MtaReceivedMessages MG 17-12
  - MtaReceivedRecipients MG 17-12
  - MtaReceivedVolume MG 17-12
  - MtaStoredMessages MG 17-12
  - MtaStoredRecipients MG 17-12
  - MtaStoredVolume MG 17-12
  - MtaSuccessfulConvertedMessages MG 17-12
  - MtaTransmittedMessages MG 17-12
  - MtaTransmittedRecipients MG 17-12
  - MtaTransmittedVolume MG 17-12
- mail, transferring UG 2-7
- Mailbox
  - (MB) record, DNS MG 3-25
  - Group (MG) record, DNS MG 3-26
  - Rename (MR) record, DNS MG 3-28
- mailbox UG B-2, MG 25-23, MG C-2
- MAIL-CONFIG commands NET 1-12, NET 3-1
  - ADD GATEWAY NET 1-12, NET 3-2
  - ADD LOCAL-DOMAIN NET 1-12, NET 3-3
  - ADD QUEUE-GROUP NET 1-12, NET 3-4
  - ALIAS-FILE NET 3-19
  - ATTACH NET 1-12, NET 3-5
  - CLEAR NET 1-12, NET 3-6
  - DECNET-DOMAIN NET 3-20
  - DELETE GATEWAY NET 1-12, NET 3-7
  - DELETE LOCAL-DOMAIN NET 1-12, NET 3-8
  - DELETE QUEUE-GROUP NET 1-12, NET 3-9
  - DELIVERY-RECEIPTS NET 3-21

- DISABLE-PSIMAIL NET 3-22
- ERASE NET 1-12, NET 3-10
- EXIT NET 1-12, NET 3-11
- GATEWAY NET 3-16
- GET NET 1-12, NET 3-12
- HELP NET 1-12, NET 3-13
- PUSH NET 1-12, NET 3-14
- QUEUE-GROUP NET 3-17
- QUIT NET 1-12, NET 3-15
- REMOVE GATEWAY NET 1-12
- REMOVE QUEUE-GROUP NET 1-13
- SAVE NET 1-13, NET 3-18
- SET ALIAS-FILE NET 1-13
- SET DECNET-DOMAIN NET 1-13
- SET DELIVERY-RECEIPTS NET 1-13
- SET DISABLE-PSIMAIL NET 1-13
- SET DISALLOW-USER-REPLY-TO NET 1-13, NET 3-23
- SET FORWARDER NET 1-13, NET 3-24
- SET FORWARD-LOCAL-MAIL NET 1-13, NET 3-25
- SET FORWARD-REMOTE-MAIL NET 1-13, NET 3-26
- SET HEADER-CONTROL NET 1-13, NET 3-27
- SET HOST-ALIAS-FILE NET 1-13, NET 3-28
- SET LOCAL-MAIL-FORWARDER NET 1-13, NET 3-29
- SET LOCASE-USERNAME NET 3-30
- SET POSTMASTER NET 1-13, NET 3-31
- SET QUEUE-COUNT NET 1-13, NET 3-32
- SET REPLY-CONTROL NET 1-14, NET 3-33
- SET RESENT-HEADERS NET 1-14, NET 3-34
- SET RETRY-INTERVAL NET 1-14, NET 3-35
- SET RETURN-INTERVAL NET 1-14, NET 3-36
- SET RFC822-TO-HEADER NET 3-37
- SET SEND-BROADCAST-CLASS NET 1-14, NET 3-38
- SET SMTP-HOST-NAMES NET 1-14, NET 3-39
- SET START-QUEUE-MANAGE NET 1-14
- SET START-QUEUE-MANAGER NET 3-40
- SHOW NET 1-14, NET 3-41
- SPAWN NET 1-14, NET 3-42
- STATUS NET 1-14, NET 3-43
- USE NET 1-14, NET 3-44
- VERSION NET 1-14, NET 3-45
- WRITE NET 1-14, NET 3-46
- maintenance agreement number
  - entering your IG 3-5
- Management Information Base (MIB) MG 7-2
- MAP command, X.25 mapping database MG 8-7, MG 8-8
- Maximum Transmission Unit (MTU)
  - IP-over-X.25 configuration MG 8-2
- messages, exchanging UG 2-7
- MINFO record MG 3-27
- Miscellaneous NETCU Commands NET 1-11
- miscellaneous services

---

CHARGEND IG 4-31  
 configuring the IG 4-31  
 DAYTIMED IG 4-31  
 DISCARD IG 4-31  
 ECHOD IG 4-31  
 IDENT IG 4-31  
 QUOTED IG 4-31  
 TFTP D IG 4-31  
 TIME IG 4-31  
 miscellaneous utilities & services  
 CHARGEND service MG 30-2  
 DAYTIMED service MG 30-2  
 DISCARD utility MG 30-2  
 DISCARD service MG 30-2  
 ECHOD service MG 30-2  
 FINGERD service MG 30-2  
 NETCU DEBUG MG 30-3  
 modems  
 compression MG 5-25  
 data transfer mode MG 5-25  
 MODIFY command  
 KDB NET 2-85  
 KERBEROS USER NET 2-87  
 SERVICE NET 2-88  
 protocol values NET 2-88  
 BG\_TCP NET 2-88  
 BG\_UDP NET 2-88  
 STREAM, DGRAM NET 2-88  
 TCP NET 2-88  
 UDP NET 2-88  
 mount  
 commands MG 13-14  
 point, Client-NFS MG 13-11  
 mount and dismount commands MG 13-27  
 MOUNT protocol MG 14-7  
 mount/dismount sequence MG 13-18  
 mounting filesystems  
 Client-NFS MG 13-11, MG 13-13  
 automounting MG 13-18  
 background mounting MG 13-18  
 cluster MG 13-12  
 MOUNT command MG 13-16  
 occluded mounts MG 13-19  
 overmounting MG 13-19  
 Server-NFS MG 14-7  
 multicast address, Socket Library PG A-16  
 multicasting PG 1-17  
 multicasting command  
 SHOW MULTICAST\_GROUPS NET 1-3  
 Multi-Exit Discriminator (MED) MG 9-45  
 MX records MG 3-29

NAMED.  
 BOOT file MG 3-3  
 CONF options MG 3-7  
 allow-query MG 3-7  
 allow-transfer MG 3-7  
 check-names MG 3-8  
 directory MG 3-8  
 fake-iquery MG 3-8  
 fetch-glue MG 3-8  
 forward MG 3-9  
 forwarders MG 3-9  
 listen-on MG 3-9  
 notify MG 3-10  
 recursion MG 3-10  
 topology MG 3-10  
 CONF zone fields MG 3-5  
 HOSTS file, overlapping clusters MG 3-43  
 NAMESERVER.LOG file MG 3-3, MG 3-41  
 national address MG 8-3  
 X.25 DNIC MG 8-3, MG 8-11  
 NETCP  
 OPCOM messages NET 1-16  
 startup messages NET 1-15  
 NETCP.LOG file NET 1-17  
 NETCU  
 ARP command  
 ADD NET 1-2  
 FIND NET 1-2  
 FLUSH NET 1-2  
 REMOVE NET 1-2  
 SET INTERFACE NET 1-2  
 SHOW NET 1-2  
 SHOW INTERFACE NET 1-2  
 command reference NET 1-15  
 DHCP commands  
 RELEASE NET 1-2  
 SET NET 1-2  
 SHOW NET 1-2  
 STOP/ NET 1-2  
 UPDATE NET 1-3  
 Dynamic Host Configuration commands NET 1-2  
 exiting NET 1-15  
 GateD command  
 CHECK GATED CONFIG MG 9-7  
 DUMP GATED STATE MG 9-7  
 LOAD GATED CONFIG MG 9-7  
 SET GATED TRACE MG 9-7  
 SHOW GATED TRACE MG 9-7  
 SHOW OSPF ADVERTISE MG 9-7  
 SHOW OSPF AS MG 9-7  
 SHOW OSPF DESTINATIONS MG 9-7  
 SHOW OSPF ERRORS MG 9-7  
 SHOW OSPF HOPS MG 9-7  
 SHOW OSPF INTERFACES MG 9-7  
 SHOW OSPF LOG MG 9-7  
 SHOW OSPF NEIGHBORS MG 9-7

---

## N

Name Server (NS) record, DNS MG 3-31

- SHOW OSPF ROUTING MG 9-7
- SHOW OSPF STATE MG 9-8
- SHOW RIP MG 9-8
- STOP/GATED MG 9-8
- TOGGLE GATED TRACING MG 9-8
- UPDATE GATED INTERFACES MG 9-8
- miscellaneous commands
  - ADD SECONDARY NET 1-11
  - DEFINE/KEY NET 1-11
  - EXIT NET 1-11
  - HELP NET 1-11
  - REMOVE SECONDARY NET 1-11
  - SET DOMAINNAME NET 1-11
  - SET PASSWORD NET 1-11
  - SET/SHOW INTERFACE NET 1-11
  - SHOW SNMP NET 1-11
  - SHOW TIMEZONE NET 1-11
  - SHOW VERSION NET 1-11
  - SPAWN NET 1-11
- multicasting commands NET 1-3
  - ADD MULTICAST\_GROUP NET 1-3
  - REMOVE MULTICAST\_GROUP NET 1-3
  - SHOW MULTICAST\_GROUPS NET 1-3
- NFS commands NET 1-3
  - ADD EXPORT NET 1-3
  - ADD GROUP NET 1-3
  - ADD PROXY NET 1-3
  - ADD SM NET 1-3
  - CREATE EXPORT NET 1-3
  - CREATE GROUP NET 1-3
  - CREATE PROXY NET 1-3
  - FIND PROXY NET 1-4
  - RELOAD GROUP NET 1-4
  - RELOAD PROXY NET 1-4
  - REMOVE EXPORT NET 1-4
  - REMOVE GROUP NET 1-4
  - REMOVE PROXY NET 1-4
  - REMOVE SM NET 1-4
  - SHOW EXPORT NET 1-4
  - SHOW GROUP NET 1-4
  - SHOW MOUNT NET 1-4
  - SHOW PROXY NET 1-4
  - SHOW SM NET 1-4
  - SHOW STATISTICS NET 1-4
  - STOP/SERVER NET 1-4
  - UNMOUNT ALL NET 1-4
- OPCOM messages
  - interfaces NET 1-17
  - IP-over-DECnet lines NET 1-17
- routing commands NET 1-5
  - ADD ROUTE NET 1-5
  - CHECK GATED CONFIG NET 1-5
  - DISABLE FORWARDING NET 1-5
  - DISABLE REDIRECTS NET 1-5
  - DUMP GATED STATE NET 1-5
  - ENABLE FORWARDING NET 1-5
  - ENABLE REDIRECTS NET 1-5
  - FIND ROUTE NET 1-5
  - FLUSH/ROUTE NET 1-5
  - LOAD GATED CONFIGURATION NET 1-6
  - REMOVE ROUTE NET 1-6
  - SET GATED TRACE NET 1-6
  - SET GATEWAY NET 1-6
  - SHOW GATED TRACE NET 1-6
  - SHOW OSPF NET 1-6
  - SHOW RIP NET 1-6
  - SHOW ROUTES NET 1-6
  - STOP/GATED NET 1-6
  - TOGGLE GATED TRACING NET 1-6
  - UPDATE GATED INTERF NET 1-6
- running NET 1-1
- security commands NET 1-9
  - ADD KACL NET 1-9
  - ADD KDB NET 1-9
  - ADD KERBEROS USER NET 1-9
  - CREATE KDB NET 1-10
  - CREATE SRVTAB NET 1-10
  - DUMP KDB NET 1-10
  - GET TGT NET 1-10
  - LOAD KDB NET 1-10
  - MODIFY KDB NET 1-10
  - MODIFY KERBEROS USER NET 1-10
  - REMOVE KACL NET 1-10
  - REMOVE KDB NET 1-10
  - REMOVE TICKETS NET 1-10
  - SET KERBEROS\_PASS NET 1-10
  - SET MASTER\_PASS NET 1-10
  - SHOW FILTER NET 1-10
  - SHOW IPSO NET 1-10
  - SHOW KACL NET 1-10
  - SHOW KDB NET 1-10
  - SHOW KERBEROS USER NET 1-10
  - SHOW OUTGOING NET 1-10
  - SHOW TICKETS NET 1-11
  - STASH MASTER\_PASS NET 1-11
- service commands NET 1-6
  - ADD ACCESS\_LIST NET 1-6
  - ADD SERVICE NET 1-6
  - MODIFY SERVICE NET 1-6
  - REMOVE ACCESS\_LIST NET 1-6
  - REMOVE SERVICE NET 1-6
  - SHOW ACCESS\_LIST NET 1-6
  - SHOW SERVICES NET 1-6
- SET commands NET 1-5
- starting and stopping commands NET 1-7
  - KILL CONNECTIONS NET 1-7
  - START/DNIP NET 1-7
  - START/INET NET 1-7
  - START/IP NET 1-7
  - START/PWIP NET 1-7
  - START/TCP NET 1-7
  - START/UCX NET 1-7

---

- START/UDP NET 1-7
- STOP/DNIP NET 1-7
- STOP/GATED NET 1-7
- STOP/INET NET 1-7
- STOP/IP NET 1-7
- STOP/NETCP NET 1-7
- STOP/PWIP NET 1-7
- STOP/SERVER NET 1-7
- STOP/TCP NET 1-7
- STOP/UCX NET 1-7
- STOP/UDP NET 1-7
- startup messages NET 1-15
- status commands NET 1-8
  - DEBUG/IP NET 1-8
  - DEBUG/TCP NET 1-8
  - DEBUG/UPD NET 1-8
  - SHOW NET 1-8
  - SHOW ACCESS\_LIST NET 1-8
  - SHOW ARP NET 1-8
  - SHOW CONNECTIONS NET 1-8
  - SHOW COUNTERS NET 1-8
  - SHOW DHCP NET 1-8
  - SHOW DNIP NET 1-9
  - SHOW GATED TRACE NET 1-9
  - SHOW HOST NET 1-9
  - SHOW INTERFACE NET 1-9
  - SHOW MULTICAST\_GROUPS NET 1-9
  - SHOW NETWORKS NET 1-9
  - SHOW OSPF NET 1-9
  - SHOW RIP NET 1-9
  - SHOW ROUTES NET 1-9
  - SHOW SERVICES NET 1-9
  - SHOW SNMP NET 1-9
  - SHOW STATISTICS NET 1-9
- token authentication commands NET 1-8
  - ADD ACE\_USER NET 1-8
  - CREATE ACE\_USER\_DATABASE NET 1-8
  - REMOVE ACE\_USER NET 1-8
  - SHOW ACE\_USER NET 1-8
- troubleshooting NET 1-15
- NETCU Commands
  - SET KERBEROS\_PASSWORD NET 2-128
  - SHOW DNIP NET 2-152
- NETCU commands
  - ADD ACCESS\_LIST NET 2-20
  - ADD ACE\_USER NET 2-22
  - ADD ARP NET 2-24
  - ADD EXPORT NET 2-26
  - ADD GROUP NET 2-29
  - ADD KACL NET 2-31
  - ADD KDB NET 2-33
  - ADD KERBEROS\_USER NET 2-35
  - ADD MULTICAST\_GROUP NET 2-36
  - ADD PROXY NET 2-37
  - ADD ROUTE NET 2-39
  - ADD SECONDARY NET 2-41
  - ADD SERVICE NET 2-42
  - CHECK GATED CONFIGURATION NET 2-48
  - CREATE ACE\_USER\_DATABASE NET 2-49
  - CREATE EXPORT NET 2-50
  - CREATE GROUP NET 2-51
  - CREATE KDB NET 2-52
  - CREATE PROXY NET 2-53
  - CREATE SRVTAB NET 2-54
  - DEBUG/IP NET 2-56
  - DEBUG/TCP NET 2-58
  - DEBUG/UDP NET 2-61
  - DEFINE TIMEZONE NET 2-66
  - DEFINE/KEY NET 2-63
  - DISABLE FORWARDING NET 2-67
  - DISABLE REDIRECTS NET 2-68
  - DUMP GATED STATE NET 2-69
  - DUMP KDB NET 2-70
  - DUMP NAMED NET 2-71
  - ENABLE FORWARDING NET 2-73
  - ENABLE REDIRECTS NET 2-74
  - EXIT NET 2-75
  - FIND ARP NET 2-76
  - FIND PROXY NET 2-77
  - FIND ROUTE NET 2-78
  - FLUSH NET 2-79
  - GET TGT NET 2-80
  - HELP NET 2-81
  - KILL CONNECTIONS NET 2-82
  - LOAD GATED CONFIGURATION NET 2-83
  - LOAD KDB NET 2-84
  - MODIFY KDB NET 2-85
  - MODIFY KERBEROS\_USER NET 2-87
  - MODIFY SERVICE NET 2-88
  - RELOAD GROUP NET 2-90
  - RELOAD NAMED NET 2-91
  - RELOAD PROXY NET 2-93
  - REMOVE ACCESS\_LIST NET 2-95
  - REMOVE ACE\_USER NET 2-94
  - REMOVE ARP NET 2-96
  - REMOVE DHCP NET 2-97
  - REMOVE EXPORT NET 2-98
  - REMOVE GROUP NET 2-99
  - REMOVE KACL NET 2-100
  - REMOVE KDB NET 2-102
  - REMOVE MULTICAST\_GROUP NET 2-104
  - REMOVE PROXY NET 2-105
  - REMOVE ROUTE NET 2-107
  - REMOVE SECONDARY NET 2-108
  - REMOVE SERVICE NET 2-109
  - REMOVE TICKETS NET 2-110
  - SET NET 2-111
  - SET BG\_ NET 2-113
  - SET DHCP NET 2-114
  - SET DOMAINNAME NET 2-115
  - SET FILTER NET 2-116

SET GATED TRACE NET 2-117  
SET GATEWAY NET 2-119  
SET INET NET 2-120  
SET INTERFACE NET 2-121  
SET IPSO NET 2-124  
SET LOG NET 2-129  
SET LOG /NFS NET 2-129  
SET MASTER\_PASSWORD NET 2-130  
SET NAMED MAXIMUM\_TTL NET 2-133  
SET NAMED MINIMUM\_TTL NET 2-134  
SET OUTGOING\_ACCESS\_RESTRICTIONS  
NET 2-135  
SET SSH /DEBUG NET 2-136  
SET TIMEZONE NET 2-137  
SHOW NET 2-138  
SHOW ACCESS\_LISTS NET 2-142  
SHOW ACE\_USER NET 2-141  
SHOW ARP NET 2-143  
SHOW CONNECTIONS NET 2-145  
SHOW COUNTERS NET 2-147  
SHOW DHCP NET 2-149  
SHOW EXPORT NET 2-154  
SHOW FILTER NET 2-156  
SHOW GATED TRACE NET 2-158  
SHOW GROUP NET 2-159  
SHOW HOST NET 2-160  
SHOW INTERFACE NET 2-161  
SHOW IPSO NET 2-163  
SHOW KACL NET 2-165  
SHOW KDB NET 2-166  
SHOW KERBEROS USER NET 2-168  
SHOW MOUNT NET 2-169  
SHOW MULTICAST\_GROUPS NET 2-170  
SHOW NAMED VERSION NET 2-197  
SHOW NETWORKS NET 2-171  
SHOW OSPF NET 2-172  
SHOW OUTGOING\_ACCESS\_RESTRICTIONS  
NET 2-180  
SHOW PROXY NET 2-181  
SHOW RIP NET 2-182  
SHOW ROUTES NET 2-184  
SHOW SERVICES NET 2-186  
SHOW SNMP NET 2-189  
SHOW SSH NET 2-191  
SHOW STATISTICS NET 2-192  
SHOW TICKETS NET 2-195  
SHOW TIMEZONE NET 2-196  
SHOW VERSION NET 2-198  
SPAWN NET 2-199  
START/DNIP NET 2-200  
START/INET NET 2-201  
START/IP NET 2-202  
START/PWIP NET 2-210  
START/TCP NET 2-211  
START/UCX NET 2-213  
START/UDP NET 2-214  
STASH MASTER\_PASSWORD NET 2-215  
STOP /SSH NET 2-226  
STOP/DHCP NET 2-216  
STOP/DNIP NET 2-217  
STOP/DNS NET 2-218  
STOP/GATED NET 2-219  
STOP/INET NET 2-220  
STOP/IP NET 2-221  
STOP/NAMED NET 2-222  
STOP/NETCP NET 2-223  
STOP/PWIP NET 2-224  
STOP/SERVER NET 2-225  
STOP/TCP NET 2-227  
STOP/UCX NET 2-228  
STOP/UDP NET 2-229  
TCPDUMP NET 2-230  
TOGGLE GATED TRACING NET 2-231  
UNMOUNT ALL NET 2-232  
UPDATE GATED INTERFACES NET 2-234  
USE NET 2-235  
VERSION NET 2-236  
WRITE NET 2-237  
NETCU output files  
creating NET 1-14  
netent structure, Socket Library PG A-9  
netgroups MG 25-22  
NetWare IG 5-1  
services configuration menu IG 5-3  
services directories and files IG C-3  
NetWare configuration option  
component IG 5-1  
core environment IG 5-1  
full IG 5-1  
Network  
Control Utility (NETCU) MG 15-13  
File System (NFS)  
requests and replies, monitoring using  
TCPDUMP MG 30-31  
Lock Manager (NLM) MG 14-8  
Status Monitor (NSM) MG 14-8  
Time Protocol (NTP) MG 10-1  
Kerberos use of MG 19-5  
network  
device drivers, programming PG 1-7  
drives, accessing UG 2-9  
functions, controlling UG 2-11  
interfaces, programming UG 2-16  
interfaces, unnumbered MG 5-10, MG 5-23  
name, X.25 MG 8-6  
print services command  
LPQ UG 5-2  
LPR UG 5-2  
LPRM UG 5-2  
PRINT UG 5-2  
programming interfaces  
FTP library UG 2-16



- QIO programming interfaces UG 2-17
- SNMP extendible agent UG 2-17
- socket library UG 2-16
- TELNET library UG 2-17
- token authentication ACE/Client API
  - functions UG 2-17
- UCX compatibility services UG 2-17
- programming with sockets PG 1-11
- testing tools MG 30-1
  - FINGER UG 2-12
  - IDENT UG 2-12
  - NSLOOKUP UG 2-12
  - PING UG 2-12
  - TCPDUMP utility UG 2-12
  - TRACEROUTE UG 2-12
  - WHOIS UG 2-13
- time, changing MG 11-3
- network classes and masks NET 2-206
- Network Control Utility (NETCU) NET 1-1
- network device addresses
  - entering IG 3-10
- network device information
  - tips for entering IG 3-11
- network devices IG 3-8
- network number
  - configuring the IG 5-6
- network print services UG 5-2
- network service monitoring MG 12-6
  - items
    - ApplAccumulatedInboundAssociations MG 12-6
    - ApplDescription MG 12-6
    - ApplInboundAssociations MG 12-6
    - ApplIndex MG 12-6
    - ApplLastChange MG 12-6
    - ApplLastInboundActivity MG 12-6
    - ApplName MG 12-6
    - ApplOperStatus MG 12-6
    - ApplRejectedInboundAssociations MG 12-6
    - ApplUptime MG 12-6
    - ApplVersion MG 12-6
- Network Time Protocol
  - configuring the IG 4-41
- next-server parameter MG 4-8
- NFS server
  - starting and restarting IG 4-39
  - testing IG 4-40
- NFS statistics
  - Files NET 2-192
  - Memory in use NET 2-192
  - MOUNT NET 2-194
  - NFS NET 2-193
  - RPC NET 2-193
  - RPC Errors NET 2-193
  - Started NET 2-192
  - Threads NET 2-192
  - Uptime NET 2-192
- NFS user identification MG 13-3
- NFS\_ACCESS\_IDENTIFIER parameter MG 14-16
- NFS\_DFTL\_GID parameter MG 14-20
- NFS\_DFTL\_UID parameter MG 14-20
- NFS\_DIRLIFE\_TIMER parameter MG 14-20
- NFS\_DIRREAD\_LIMIT parameter MG 14-20
- NFS\_DIRTIME\_TIMER parameter MG 14-20
- NFS\_FILE\_CACHE\_SIZE parameter MG 14-21
- NFS\_LOG\_CLASS parameter MG 14-17
- NFS\_NOCHECKSUM parameter MG 14-21
- NFS\_OPENFILE\_TIMER parameter MG 14-21
- NFS\_PCNFSD\_DFLTPTOPT parameter MG 14-21
- NFS\_PCNFSD\_ENABLE parameter MG 14-19
- NFS\_PCNFSD\_JOB\_LIMIT parameter MG 14-22
- NFS\_PCNFSD\_PRINTER parameter MG 14-22
- NFS\_PCNFSD\_PRINTER\_LIMIT parameter MG 14-22
- NFS\_PCNFSD\_SPOOL parameter MG 14-19
- NFS\_PORT parameter MG 14-22
- NFS\_SECURITY parameter MG 14-17
- NFS\_TCP\_THREADS parameter MG 14-22
- NFS\_UDP\_THREADS parameter MG 14-22
- NFS\_XID\_CACHE\_SIZE parameter MG 14-23
- NFSDISMOUNT command, Client-NFS MG 13-40
- NFSFile Ownership and Protection MG 13-5
- NFSMOUNT /CONFIG command, Client-NFS MG 13-36
- NFSMOUNT /LOCK command MG 13-19
- NFSMOUNT /SHOW command, Client-NFS MG 13-38
- NFSMOUNT command MG 13-13, MG 13-29
- NFS-OpenVMS Client
  - /etc/group file MG 13-3
  - attributes data files (ADFs) MG 13-20
  - cache space, increasing MG 13-26
  - cache timeout, setting MG 13-22
  - default GID, setting MG 13-22
  - default UID, setting MG 13-22
  - default user, setting MG 13-22
  - delta time, using MG 13-27
  - disk quotas, displaying MG 13-26
  - file locking MG 13-12
  - file protection mask MG 13-6, MG 13-7
  - file version mapping rules MG 13-10, MG 13-11
  - file versions, limiting MG 13-22
  - GID protection MG 13-3
  - GROUP database MG 13-3, MG 13-5
  - IBM VM server type setting MG 13-24
  - implementation MG 13-27
  - master file directory (MFD) MG 13-11
  - mount
    - background MG 13-18
    - occluded MG 13-19
    - options setting MG 13-20
    - overmounting MG 13-19
  - mount device specification MG 13-11
  - mount point MG 13-11

- mount type, setting MG 13-23
- mount, automounting MG 13-18
- mounting filesystems MG 13-11, MG 13-13
  - cluster MG 13-12
- POSIX limitation MG 13-27
- privileges MG 13-9
- protection mapping, client to server MG 13-9
- PROXY database MG 13-3, MG 13-4
- read/write transfer size, setting MG 13-22
- retry time, setting MG 13-25
- security auditing MG 13-16
- server concept MG 13-1
- server type, setting MG 13-23
- special users MG 13-9
- superusers MG 13-23
- symbolic links MG 13-15
- TCPWARE server type setting MG 13-24
- template device MG 13-11
- text files, autoconverting MG 13-20
- timeout time, setting MG 13-25
- troubleshooting MG 13-28
- UIC protection MG 13-4
- UID protection MG 13-3
- user identification MG 13-3
- virtual directory MG 13-12
- volume labels, setting MG 13-26
- NFS-OpenVMS client
  - configuring the IG 4-6
- NFS-OpenVMS Server MG 14-1
  - /etc/passwd file MG 14-2
  - default, GID setting MG 14-20
  - default, UID setting MG 14-20
  - delta time, using MG 14-20
  - EXPORT database MG 14-4
  - file
    - attribute mapping MG 14-11
      - UNIX to OpenVMS MG 14-12
    - conversion MG 14-14
    - converting manually MG 14-15
    - formats MG 14-14
    - locking MG 14-8
      - NFS client's view of MG 14-8
      - OpenVMS user's view of MG 14-9
    - protection MG 14-10
      - UIC in OpenVMS MG 14-10
      - UID/GID in UNIX MG 14-11
    - protection, ACL MG 14-13
    - version mapping rules MG 13-10
  - filename translation MG 14-9
  - files
    - reading MG 14-14
    - writing MG 14-14
  - GID protection MG 14-2
  - implementation MG 14-23
  - log file MG 14-17
  - parameters
    - advanced MG 14-19
    - basic MG 14-16
  - protocol procedures MG 14-24
    - create MG 14-24
    - getattr MG 14-25
    - link MG 14-25
    - lookup MG 14-26
    - mkdir MG 14-26
    - read MG 14-26
    - readdir MG 14-26
    - readlink MG 14-26
    - remove MG 14-26
    - rename MG 14-26
    - rmdir MG 14-26
    - setattr MG 14-27
    - statfs MG 14-25
    - symlink MG 14-27
    - write MG 14-27
  - PROXY database MG 14-2
  - reading files MG 14-14
  - restrictions MG 14-24
  - security MG 19-12
    - features MG 14-1
  - stream\_if-to-variable conversion MG 14-15
  - STREAM-LF files MG 14-14
  - troubleshooting MG 14-31
  - UIC protection MG 14-2
  - UID protection MG 14-2
  - variable-to-stream conversion MG 14-15
  - variable-to-stream\_if conversion MG 14-15
  - writing files MG 14-14
  - XID cache MG 14-23
- NFS-OpenVMS server
  - configuring the IG 4-33
- NFS-to-OpenVMS
  - character sequence mapping MG A-2
  - filename translation rules MG A-5
- FTP commands
  - SET UG 3-65
    - UG 3-71, UG 3-72, UG 3-73, UG 3-74
- NETCU
  - miscellaneous commands
    - SET NET 1-11
  - security commands
    - SET NET 1-10
  - status commands
    - SET NET 1-8
- NETCU commands
  - SET NAMED NET 2-132
- TELNET
  - command reference
    - SET UG 12-21
- TELNET commands
  - SET
    - UG 12-39, UG 12-41, UG 12-42, UG 12-43,
    - UG 12-44, UG 12-48, UG 12-49,
    - UG 12-50, UG 12-52, UG 12-53,

UG 12-54, UG 12-55, UG 12-57,  
 UG 12-62  
 nopwd MG 25-9  
 NPS-OpenVMS  
   configuring IG 5-12  
 NS records MG 3-31  
 NSLOOKUP utility MG 30-3  
   error messages MG 30-20  
   EXIT command MG 30-6  
   FINGER command MG 30-7  
   HELP command MG 30-8  
   interactive mode MG 30-4  
   LS command MG 30-10  
   LSERVER command MG 30-14  
   non-interactive mode MG 30-4  
   ROOT command MG 30-13  
   SERVER command MG 30-14  
   SET command MG 30-15  
   SPAWN command MG 30-19  
   VIEW command MG 30-20  
 NTA device  
   creating a permanent UG 12-9  
   handling a broken connection UG 12-10  
 ntohl subroutine, Socket Library PG A-47  
 ntohs subroutine, Socket Library PG A-48  
 NTP  
   access control commands  
     ignore MG 10-11  
     limited MG 10-12  
     nomodify MG 10-11  
     nopeer MG 10-12  
     noquery MG 10-11  
     noserve MG 10-12  
     notrust MG 10-12  
     ntpport MG 10-12  
   configuration commands  
     broadcast MG 10-5  
     peer MG 10-5  
     server MG 10-5  
   configuration file MG 10-5  
   files MG 10-3  
   functions MG 10-2  
   monitoring commands  
     loopstats MG 10-9  
     peerstats MG 10-9  
     rawstats MG 10-9  
   parameter  
     waytoobig MG 10-11  
   WAYTOOBIG IG 4-42  
 NTPDATE  
   command line options MG 10-33  
   utility MG 10-17, MG 10-33  
 NTPQ  
   command line format MG 10-24  
   control message commands MG 10-19  
   utility MG 10-17

NTPTRACE  
   command line options MG 10-35  
   utility MG 10-17, MG 10-35  
 NULL routine, calling PG 13-7

## O

ONC RPC Run-Time Library (RTL) PG 16-1  
   conventions PG 15-1  
 ONC RPC Services  
   active cache PG 12-10  
   asynchronous server PG 13-5  
   asynchronous system traps (ASTs) PG 13-6  
   asynchronous transports PG 13-5  
   batch facilities PG 12-11  
   broadcast RPC PG 12-11  
   client PG 12-3  
   client stub PG 12-4  
   components PG 12-2  
     Port Mapper PG 12-3  
     RPCGEN compiler PG 12-3  
     Run-Time Libraries (RTLs) PG 12-2  
   definition PG 12-1  
   distributed applications PG 12-2  
     build structure PG 13-3  
     building PG 13-1  
     compile all files PG 13-3  
     design PG 13-2  
     execute client and server programs PG 13-5  
     link object code PG 13-4  
     start port mapper PG 13-4  
     write and compile definition PG 13-2  
     write code PG 13-3  
   error handling PG 12-5  
   External Data Representation (XDR) PG 12-4  
   for network programming PG 12-1  
   global variables  
     svc\_fdset PG 18-11  
   implementation PG 12-1  
   local calls vs. remote calls PG 12-5  
   management routines PG 15-1  
   marshalling PG 12-4  
   null routine, calling PG 13-7  
   Port Mapper PG 12-3  
     binding PG 12-3  
     registration PG 12-3  
   port mapper routines PG 17-1  
   processing flow PG 12-4  
   program listing, requesting PG 13-7  
   program version numbers PG 12-12  
   programming PG 1-10  
   programming fundamentals PG 12-1  
   remote procedure call (RPC) PG 1-10, PG 12-2  
   remote procedure numbers PG 12-13

- remote programs/procedures, identifying PG 12-12
- RFCs PG 12-2
- routines
  - high-level PG 12-6
  - low-level PG 12-6
  - mid-level PG 12-6
- RPC language PG 14-2
- RPCGEN compiler PG 12-3, PG 14-1
  - error handling PG 14-6
  - input files PG 14-2
  - interface definitions PG 14-2
  - invoking PG 14-4
  - output files PG 14-3
  - preprocessor directives PG 14-4
  - restrictions PG 14-6
  - software requirements PG 14-1
- RPCINFO utility PG 12-3, PG 13-6
  - sample PG 13-7
- RTL Client routines PG 16-1
- RTL client routines
  - auth\_destroy PG 16-3
  - authnone\_create PG 16-4
  - authunix\_create PG 16-5
  - authunix\_create\_default PG 16-6
  - callrpc PG 16-7
  - clnt\_broadcast PG 16-8
  - clnt\_call PG 16-10
  - clnt\_control PG 16-11
  - clnt\_create PG 16-13
  - clnt\_destroy PG 16-15
  - clnt\_freeres PG 16-16
  - clnt\_geterr PG 16-17
  - clnt\_pcreateerror PG 16-18
  - clnt\_perrno PG 16-19
  - clnt\_perror PG 16-20
  - clnt\_spcreateerror PG 16-18
  - clnt\_sperrno PG 16-19
  - clnt\_sperror PG 16-20
  - clntraw\_create PG 16-21
  - clnttcp\_create PG 16-23
  - clntudp\_bufcreate PG 16-25
  - clntudp\_create PG 16-25
  - common arguments PG 16-1
  - reference PG 16-2
- RTL Management routines PG 15-1
- RTL management routines
  - boolean values PG 15-3
  - D\_float library PG 15-1
  - G\_float library PG 15-1
  - get\_myaddress PG 15-6
  - getrpcbnumber PG 15-7
  - getrpcport PG 15-8
  - header files PG 15-2
  - implementation differences
    - TCPware/Sun PG 15-4
  - ONCRPC\_GET\_CHAR PG 15-9
  - ONCRPC\_GET\_STATS PG 15-12
  - ONCRPC\_SET\_CHAR PG 15-15
  - reference PG 15-5
  - routine name conventions PG 15-2
  - T\_float library PG 15-2
- RTL Port Mapper routines PG 17-1
  - arguments PG 17-1
  - pmap\_freemaps PG 17-3
  - pmap\_getmaps PG 17-4
  - pmap\_getport PG 17-5
  - pmap\_rmtcall PG 17-6
  - pmap\_set PG 17-7
  - pmap\_unset PG 17-8
- RTL port mapper routines, reference PG 17-2
- RTL Server routines PG 18-1
  - svcerr\_systemerr PG 18-17
- RTL server routines
  - reference PG 18-3
  - registerrpc PG 18-4
  - svc\_destroy PG 18-5
  - svc\_freeargs PG 18-6
  - svc\_getargs PG 18-7
  - svc\_getcaller PG 18-8
  - svc\_getchan PG 18-9
  - svc\_getport PG 18-10
  - svc\_getreqset PG 18-11
  - svc\_register PG 18-13
  - svc\_run PG 18-14
  - svc\_sendreply PG 18-15
  - svc\_sendreply\_dq PG 18-15
  - svc\_unregister PG 18-16
  - svcerr\_auth PG 18-17
  - svcerr\_decode PG 18-17
  - svcerr\_noproc PG 18-17
  - svcerr\_noprog PG 18-17
  - svcerr\_progvers PG 18-17
  - svcerr\_weakauth PG 18-17
  - svcfld\_create PG 18-19
  - svccraw\_create PG 18-20
  - svctcp\_create PG 18-21
  - svctcpa\_create PG 18-22
  - svctcpa\_enablecache PG 18-23
  - svctcpa\_freecache PG 18-25
  - svctcpa\_getxdrs PG 18-26
  - svctcpa\_shutdown PG 18-27
  - svcudp\_create PG 18-28
  - svcudp\_enablecache PG 18-29
  - svcudpa\_bufcreate PG 18-30
  - svcudpa\_create PG 18-30
  - svcudpa\_enablecache PG 18-32
  - svcudpa\_freecache PG 18-34
  - svcudpa\_getxdrs PG 18-35
  - svcudpa\_shutdown PG 18-36
  - xprt\_register PG 18-37
  - xprt\_unregister PG 18-38

- 
- RTL XDR routines PG 19-1
    - reference PG 19-2
    - xdr\_accepted\_reply PG 19-5
    - xdr\_array PG 19-6
    - xdr\_authunix\_parms PG 19-7
    - xdr\_bool PG 19-8
    - xdr\_bytes PG 19-9
    - xdr\_callhdr PG 19-10
    - xdr\_callmsg PG 19-11
    - xdr\_char PG 19-12
    - xdr\_double PG 19-13
    - xdr\_enum PG 19-15
    - xdr\_float PG 19-16
    - xdr\_free PG 19-17
    - xdr\_hyper PG 19-18
    - xdr\_int PG 19-19
    - xdr\_long PG 19-20
    - xdr\_netobj PG 19-21
    - xdr\_opaque PG 19-22
    - xdr\_opaque\_auth PG 19-23
    - xdr\_pmap PG 19-24
    - xdr\_pmaplist PG 19-25
    - xdr\_pointer PG 19-26
    - xdr\_reference PG 19-28
    - xdr\_rejected\_reply PG 19-29
    - xdr\_replymsg PG 19-30
    - xdr\_short PG 19-31
    - xdr\_string PG 19-32
    - xdr\_u\_char PG 19-33
    - xdr\_u\_hyper PG 19-34
    - xdr\_u\_int PG 19-35
    - xdr\_u\_long PG 19-36
    - xdr\_u\_short PG 19-37
    - xdr\_union PG 19-38
    - xdr\_void PG 19-40
    - xdr\_wrapstring PG 19-41
    - xdrmem\_create PG 19-42
    - xdrrec\_create PG 19-43
    - xdrrec\_endofrecord PG 19-45
    - xdrrec\_eof PG 19-46
    - xdrrec\_skiprecord PG 19-47
    - xdrstdio\_create PG 19-48
  - sample programs PG 20-1
    - GETSYI PG 20-2, PG 20-4
    - PRINT PG 20-3, PG 20-5
    - running PG 20-1
    - SYSINFO PG 20-3, PG 20-5
  - server PG 12-3
  - system crashes PG 12-5
  - transport protocols PG 12-7
  - unmarshalling PG 12-4
  - XDR language PG 14-2
  - XID cache PG 12-9
  - ONCRPC\_FUNC.H file PG 15-2
  - ONCRPC\_GET\_CHAR routine, RPC RTL PG 15-9
  - ONCRPC\_GET\_STATS routine, RPC RTL PG 15-12
  - ONCRPC\_SET\_CHAR routine, RPC RTL PG 15-15
  - Open Shortest Path First (OSPF) routing MG 9-54
  - OpenVMS
    - character sets UG 12-16
    - file ownership and protection MG 13-6
    - mail
      - addresses, specifying UG 10-1
      - host alias, specifying UG 10-3
      - individual aliases, specifying UG 10-3
      - to folders, delivering UG 10-4
      - under ALL-IN-1, using UG 10-4
      - user-defined headers UG 10-4
      - using across network UG 10-1
    - user identification MG 13-4
  - Oracle software IG 3-9
  - Oracle's SQL\*Net IG 2-8
  - origin command, DNS MG 3-15
  - OUTGOING NET 1-10
- 
- ## P
- P3 Transmit Characteristics PG 5-28
  - packet
    - filtering MG 19-3, MG 21-1
    - tracing options MG 9-57
  - Packet filtering MG 21-1
  - parameters
    - NFS\_ACCESS\_IDENTIFIER MG 14-16
    - NFS\_DFLT\_GID MG 14-20
    - NFS\_DFLT\_UID MG 14-20
    - NFS\_DIRLIFE\_TIMER MG 14-20
    - NFS\_DIRREAD\_LIMIT MG 14-20
    - NFS\_DIRTIME\_TIMER MG 14-20
    - NFS\_FILE\_CACHE\_SIZE MG 14-21
    - NFS\_LOG\_CLASS MG 14-17
    - NFS\_NOCHECKSUM MG 14-21
    - NFS\_OPENFILE\_TIMER MG 14-21
    - NFS\_PCNFSD\_SPOOL MG 14-19
    - NFS\_PCNFSD\_DFLTPTOPT MG 14-21
    - NFS\_PCNFSD\_ENABLE MG 14-7, MG 14-19
    - NFS\_PCNFSD\_JOB\_LIMIT MG 14-22
    - NFS\_PCNFSD\_PRINTER MG 14-22
    - NFS\_PCNFSD\_PRINTER\_LIMIT MG 14-22
    - NFS\_PCNFSD\_SPOOL MG 14-7
    - NFS\_PORT MG 14-22
    - NFS\_SECURITY MG 14-17
    - NFS\_TCP\_THREADS MG 14-22
    - NFS\_UDP\_THREADS MG 14-22
    - NFS\_XID\_CACHE\_SIZE MG 14-23
  - PASSCODE UG 14-2
  - PASSIVE UG 3-73
  - passphrase UG 16-20, UG 16-22
    - forgotten UG 16-22

- lost UG 16-22
- password authentication MG 25-8
- Password Authentication Protocol (PAP) MG 5-6
- password-based authentication MG 25-2
- PATHWORKS MG 26-1, MG 30-1
  - managing support MG 26-1, MG 30-1
  - outgoing access restrictions and MG 20-5
- PC
  - installation MG 26-3
  - server name format MG 26-3
  - system files MG 26-3
  - third party products MG 26-2
- server MG 26-1
- troubleshooting MG 26-3
- VAX/Alpha
  - error logs MG 26-1
  - server software location MG 26-1
  - services MG 26-2
  - startup command MG 26-1
  - system processes MG 26-1
- Version 4 MG 26-1
- patterns
  - host name MG 25-7
  - hostname MG 25-15, MG 25-17
  - hostnames MG 25-18
  - port number MG 25-15, MG 25-17
  - rights identifier MG 25-6
  - user name MG 25-7
- PCNFS Client MG 14-30
- PCNFS Server (PCNFSD) MG 14-6
  - authentication MG 14-7
  - break-in security MG 14-30
  - print options MG 14-29
  - protocol procedures MG 14-27
    - ALERT OPERATOR MG 14-28
    - AUTHENTICATE MG 14-28
    - CANCEL PRINT MG 14-28
    - HOLD PRINT MG 14-28
    - INFORMATION MG 14-28
    - INITIALIZE PRINTER MG 14-28
    - LIST PRINTERS MG 14-29
    - LIST QUEUE MG 14-29
    - NULL MG 14-28, MG 14-29
    - PRINTER STATUS MG 14-29
    - RELEASE PRINT MG 14-29
    - START PRINTER MG 14-28, MG 14-29
  - remote printing MG 14-7
- PCNFSD, authentication services MG 14-6
- PDP-11
  - operating systems UG 1-8
- TCPware for
  - IAS UG 1-8
  - RSX UG 1-8
  - RT-11 UG 1-8
  - TSX UG 1-8
- peer hosts MG 10-4
- permit list MG 4-11
- PIN UG 14-2
  - creating your own UG 14-6
- PING utility MG 30-22
  - example MG 30-22
  - PING\_V2
    - example MG 30-23
    - using MG 30-23
  - using MG 30-22
- pmap\_freemaps, RPC RTL PG 17-3
- pmap\_getmaps, RPC RTL PG 17-4
- pmap\_getport, RPC RTL PG 17-5
- PMAP\_PROT.H file PG 15-3
- pmap\_rmtcall, RPC RTL PG 17-6
- pmap\_set, RPC RTL PG 17-7
- pmap\_unset, RPC RTL PG 17-8
- pnerror subroutine, Socket Library PG A-49
- Point-to-Point Protocol (PPP) MG 5-1
  - authentication MG 5-5
  - compatibility with other products MG 5-2
  - configuration MG 5-1
  - configuring MG 5-2
  - function MG 5-1
  - line speeds MG 5-2
  - PPP link, configuring MG 5-5
  - pppd, running MG 5-3
  - troubleshooting MG 5-19
  - unnumbered interface MG 5-2
- pool permit lists MG 4-11
- port forwarding
  - definition UG 16-8
- Port Mapper PG 1-10
  - binding PG 12-3
  - broadcast RPC PG 12-3
  - registration PG 12-3
  - requesting a listing PG 13-7
- port number MG 27-3
- Post Office Protocol (POP) MG 17-29
- Post Office Protocol Version 3
  - configuring the IG 4-42
- PPP links MG 5-5
- PPPD
  - command MG 5-3, MG 5-12
  - command file parameters
    - CONNECT MG 5-4
    - DISCONNECT MG 5-4
    - IPDOWN MG 5-4
    - IPUP MG 5-4
  - link authentication options
    - +PAP MG 5-6
    - AUTH MG 5-6
    - PAP MG 5-6
  - link customization options
    - PASSIVE MG 5-5
    - PERSIST MG 5-5
    - SILENT MG 5-5

- options
    - command file parameters MG 5-4
  - PRINCIPAL.OK file MG 23-6
  - PRINT UG 5-14
    - qualifiers UG 5-4
  - PRINT client PG 20-3
  - PRINT command
    - OpenVMS MG 15-10
    - queues based on PRINTCAP. file MG 15-4
  - print symbiont
    - Terminal Server Print Services MG 15-13
  - PRINT.X PG 14-2
  - PRINTCAP (printer capability) MG 15-4
  - private addresses
    - using IG 1-4
  - private network addresses IG 1-5
  - process quotas
    - configuring IG 5-13
  - Product Authorization Key (PAK)
    - registering your IG 6-12
  - Programming
    - introduction PG 1-1
      - TCP/IP programming concepts PG 1-1
      - writing application programs PG 1-18
  - programming
    - services
      - options PG 1-6
  - Protocols
    - XDR PG 1-10
  - protocols
    - FINGER MG 30-2
    - FINGERD MG 30-2
    - IDENT MG 30-3
    - IP MG 8-2
    - load request MG 3-44
    - TIME MG 30-44
    - X.25 MG 8-2
  - protoent structure, Socket Library PG A-9
  - PROXY database MG 14-2
    - Client-NFS MG 13-3, MG 13-4
  - reloading
    - dynamic MG 14-4
    - static MG 14-3
  - Server-NFS MG 14-2
    - superuser account MG 14-3
  - PROXYARP option MG 5-10
  - pseudoterminal MG 25-14
  - public-key cryptography UG 16-2
  - PUT UG 3-13
  - pwdlifetime UG B-25, MG 25-24, MG C-24
  - PWIPDRIVER
    - configuring the IG 4-44
- 
- Q**
- QIO programming PG 1-8
  - query programs MG 10-1
  - quote character MG 12-11
  - QUOTED service MG 30-24
    - message MG 30-24
    - port MG 30-24
  - QUOTE command MG 30-24
    - syntax MG 30-24
    - testing MG 30-24
- 
- R**
- R services
    - configuring the IG 4-44
  - R Shell (RSH) server MG 16-1
  - random number generator MG 25-21
  - RCD client UG 6-1
  - RCD/RMT command
    - RMTSETUP UG 6-3
  - RCMD.LOG file MG 16-4
  - RCP
    - security MG 19-13
    - service MG 19-13
  - RCP command
    - RCP UG 7-3
  - recvfrom subroutine, Socket Library PG A-50
  - regenerate server key MG 25-8
  - registerrpc, RPC RTL PG 18-4
  - RELEASE command
    - DHCP NET 2-97
  - RELOAD command
    - GROUP NET 2-90
    - NAMED NET 2-91
    - PROXY NET 2-93
  - RELOAD EXPORT command, NETCU MG 14-5
  - remote
    - filesystem access UG 2-2
    - hosts, logging in to UG 2-5
    - system commands
      - CD UG 3-23
      - DELETE UG 3-23
      - DIR UG 3-23
      - ls UG 3-23
      - LIST UG 3-23
      - MKDIR UG 3-23
      - PWD UG 3-23
      - QUOTE UG 3-23
      - REMOTEHELP UG 3-23
      - RENAME UG 3-23
      - SITE UG 3-23
      - USER UG 3-23

- Remote Copy Program (RCP) MG 16-1, MG 16-5
  - password security MG 16-5
  - security MG 19-13
    - /PASSWORD qualifier MG 16-5
  - server
    - management MG 16-5
    - troubleshooting MG 16-5
- remote host information MG 7-15
- remote login program
  - first authentication method UG 16-1
  - fourth authentication method UG 16-4
  - second authentication method UG 16-1
  - third authentication method UG 16-2
- Remote Magnetic Tape (RMT) MG 16-6
  - client, examples MG 16-8
  - dump service MG 16-7
  - dumping and restoring files MG 16-6
  - rdump service MG 16-7
  - restore service MG 16-7
  - rrestore service MG 16-7
  - server MG 16-1
- Remote Procedure Call (RPC) PG 12-2
- REMOVE ACE\_USER command, NETCU MG 22-7
- REMOVE command
  - ACCESS\_LIST NET 2-95
  - ACE\_USER NET 2-94
  - ARP NET 2-96
  - DHCP NET 2-97
  - EXPORT NET 2-98
  - GROUP NET 2-29, NET 2-99
  - KACL NET 2-100
  - KDB NET 2-102
  - MULTICAST\_GROUP NET 2-104
  - PROXY NET 2-105
  - ROUTE NET 2-107
  - SECONDARY NET 2-108
  - SERVICE NET 2-109
  - TICKETS NET 2-110
- Requests for Comments (RFCs) UG A-1
- resolver subroutines, Socket Library PG A-52
- resource record types MG 3-18
- responsible person (NS) record, DNS MG 3-33
- RETRIEVE command qualifier MG 12-26
- Reverse Address Resolution Protocol (RARP)
  - displaying packets using TCPDUMP MG 30-28
- RFC
  - 1001 MG 4-48
  - 1001/1002 MG 4-47
  - 1002 MG 4-48
  - 1035 MG 4-45, MG 4-46, MG 4-48
  - 1042 MG 4-46
  - 1073 MG 18-7
  - 1079 MG 18-6
  - 1091 MG 18-1
  - 1122 MG 4-44, MG 4-49
  - 1179 MG 4-47
  - 1191 MG 4-48
  - 1256 MG 4-49
  - 1372 MG 18-6
  - 2131 MG 4-3
  - 2132 MG 4-3
  - 2741 MG 7-14
  - 2742 MG 7-14
  - 2788 MG 12-6
  - 2789 MG 17-12
  - 854 MG 18-1
  - 858 MG 18-1
  - 865 MG 4-44
  - 868 MG 4-51
  - 885 MG 18-1
  - 887 MG 4-49
  - 893 MG 4-51
  - 894 MG 4-46
  - 950 MG 4-50
- RFC 791 PG 5-9
- RFCs, implemented by TCPware for OpenVMS UG A-2
- rhosts authentication MG 25-2, MG 25-19
- RhostsAuthentication UG 16-14
- RhostsRSAAuthentication UG 16-14
- rights identifier patterns MG 25-6
- RLOGIN UG 8-3, MG 25-2
  - commands UG 8-3
  - configuring IG 4-45
- RMT
  - configuring IG 4-45
- RMT client UG 6-1
- ROOT command, NSLOOKUP MG 30-13
- ROUTE command, X.25 mapping database MG 8-7, MG 8-9
- Route Through (RT) record, DNS MG 3-34
- router
  - advertisements MG 9-34
  - discovery
    - protocol MG 9-34
    - server MG 9-34
  - ID MG 9-19
- Routing MG 9-1
- routing
  - configuration options
    - DEFAULTROUTE MG 5-9
    - IP MG 5-9
    - NETMASK MG 5-9
    - PROXYARP MG 5-9
  - datagram
    - fragmentation MG 9-4
    - over known route MG 9-4
  - default gateway, defining MG 9-3
  - dynamic MG 9-5
  - examples MG 9-2, MG 9-3
  - forwarding MG 9-4
  - gateway
    - capability in ARP mode MG 9-4



- default address MG 9-1
- multiple gateway support MG 9-1
- guidelines MG 9-2
- link failure MG 9-1
  - redirect messages MG 9-1
- link recovery, route selection MG 9-2
- local network MG 9-2
- multicast MG 9-4
- route selection MG 9-2
- router failure MG 9-1
- router recovery MG 9-2
- static MG 9-2
- Routing Information Protocol (RIP) MG 9-23
- ROUTING.COM file MG 8-3, MG 24-12
  - cluster alias failover MG 6-2
  - conflict with GATED.CONF file MG 9-2
- RPC
  - batch programs PG 20-5
  - protocol compiler, RPCGEN PG 14-1
- RPC-based services MG 30-31
- RPCGEN
  - file naming conventions PG 14-3
  - output files PG 14-3
- RPCINFO utility PG 13-6
- RSA authentication UG 16-20
- RSA authentication identity UG 16-22, UG 16-24
- RSA challenge-response authentication MG 25-2
- RSA host authentication MG 25-2, MG 25-9
- RSA key
  - bits MG 25-14
  - comment MG 25-14
  - exponent MG 25-14
  - modulus MG 25-14
  - options MG 25-14
- RSA key file
  - Allowforwardingport MG 25-15
  - Allowforwardingto MG 25-15
  - command MG 25-16
  - Denyforwardingport MG 25-16
  - Denyforwardingto MG 25-17
  - from MG 25-17
  - idle-timeout MG 25-18
  - no-agent-forwarding MG 25-18
  - no-port-forwarding MG 25-18
  - no-X11-forwarding MG 25-18
- RSA key file examples MG 25-18
- RSA keys MG 25-14
- RSA-based authentication UG 16-2
- RSA-based host authentication UG 16-1
- RSH
  - configuring IG 4-45
- RSH command
  - RSH UG 9-2
- RSHELL MG 25-2
- RT records MG 3-34
- RULE specification

format of IG 3-16

## S

- sd\_auth function, ACE/Client API PG 11-6
- sd\_check function, ACE/Client API PG 11-7
- sd\_close function, ACE/Client API PG 11-11
- sd\_init function, ACE/Client API function PG 11-5
- sd\_next function, ACE/Client API PG 11-9
- sd\_pin function, ACE/Client API PG 11-10
- sdamin program, ACE/Server MG 22-3
- SDCONF.REC file MG 22-6
- secure encrypted communications MG 25-1
- Secure Server
  - security MG 19-13
- secure shell
  - configuration file
    - keyword
      - BatchMode UG 16-11
      - Cipher UG 16-11
      - ClearAllForwardings UG 16-11
      - Compression UG 16-11
      - CompressionLevel UG 16-11
      - ConnectionAttempts UG 16-12
      - EscapeChar UG 16-12
      - FallBackToRsh UG 16-12
      - ForwardAgent UG 16-12
      - ForwardX11 UG 16-12
      - GatewayPorts UG 16-12
      - GlobalKnownHostsFile UG 16-12
      - Host UG 16-12
      - IdentityFile UG 16-13
      - KeepAlive UG 16-13
      - LocalForward UG 16-13
      - NumberOfPasswordPrompts UG 16-13
      - PasswordAuthentication UG 16-13
      - PasswordPromptHost UG 16-13
      - PasswordPromptLogins UG 16-14
      - Port UG 16-14
      - ProxyCommand UG 16-14
      - RemoteForward UG 16-14
      - RhostsAuthentication UG 16-14
      - RhostsRSAAuthentication UG 16-14
      - RSAAuthentication UG 16-14
      - StrictHostKeyChecking UG 16-15
      - UsePrivilegedPort UG 16-15
      - UserKnownHostsFile UG 16-15
      - UseRsh UG 16-15
    - configuration files UG 16-11
- Secure Shell (SSH)
  - daemon (SSHD) MG 25-1
  - restrictions MG 25-1
  - security MG 25-2
  - server UG 2-15, MG 25-1

- understanding MG 25-1
- SSHD MG 25-2
- SSHD\_MASTER MG 25-1
- secure shell client UG 16-1
- SecurID token
  - logging in with UG 14-4
  - type, identifying the UG 14-2
  - user responsibilities UG 14-4
- Security MG 19-1
- security
  - Client-NFS
    - file protection MG 13-2
    - privileges MG 13-9
    - protection mapping MG 13-9
    - security auditing and alarms MG 13-16
    - superuser MG 13-23
    - UID MG 13-3
    - user protection MG 13-2
  - features MG 19-1
- FTP-OpenVMS
  - ANONYMOUS support MG 12-11
  - directory access restrictions MG 12-5
  - idle control connection timeout MG 12-5
  - log file MG 12-5
  - login procedures MG 12-3
  - password MG 12-24
- RMT service MG 16-6
- Server-NFS MG 14-1
  - access control lists MG 14-16
  - GID
    - default MG 14-20
  - superuser MG 14-2, MG 14-3
  - UIC MG 14-2
  - UID MG 14-2
    - default MG 14-20
- Server-TELNET
  - ECHO option MG 18-5
  - SUPPRESS-GO-AHEAD option MG 18-6
- TCPware product MG 19-9
- tips MG 19-1
  - contacting CERT MG 19-2
- Security Dynamics ACE/Server MG 22-1
- See also individual commands
  - ARP commands NET 1-2
  - dynamic host configuration commands NET 1-2
  - miscellaneous commands NET 1-11
  - multicasting commands NET 1-3
  - NFS commands NET 1-3
  - parameter setting commands NET 1-5
  - routing commands NET 1-5
  - security commands NET 1-9
  - service commands NET 1-6
  - starting and stopping commands NET 1-7
  - status commands NET 1-8
  - Token Authentication commands NET 1-7
- select subroutine, Socket Library PG A-55
- select\_wake subroutine, Socket Library PG A-56
- sendto subroutine, Socket Library PG A-57
- Serial Line IP (SLIP)
  - compressed (CSLIP) MG 5-26
  - configuration MG 5-20
    - sample MG 5-22, MG 9-4
  - configuring MG 5-21
  - flowcontrol MG 5-25
  - function MG 5-19
  - high speed modems MG 5-25
  - interface MG 5-19
  - line
    - dedicated MG 5-21
    - dialup MG 5-21
      - incoming MG 5-8, MG 5-24
      - outgoing MG 5-24
    - disconnecting MG 5-25
  - line speeds MG 5-20
  - numbered interfaces, traditional MG 5-9
  - protocol MG 5-20
  - qualifiers MG 5-26
  - routing commands MG 5-22
  - troubleshooting MG 5-27
  - unnumbered interface MG 5-10, MG 5-20, MG 5-21, MG 5-23
- Serial Line IP (SLIP) devices IG 3-9
- servent structure PG 1-16
- servent structure, Socket Library PG A-9
- server
  - writing PG 1-22
- SERVER command, NSLOOKUP MG 30-14
- server EXPORT database
  - adding directories to the IG 4-35
- server key MG 25-3
- server listens MG 25-4
- server PROXY database
  - adding users to the IG 4-33
- Server-FTP MG 12-18
- SERVERS.COM. MG 20-2
- services options
  - programming
    - DEC C socket routines PG 1-7
    - FTP library routines PG 1-10
    - ONC RPC services PG 1-10
    - system Queue Input/Output (QIO) calls PG 1-8
    - BGDRIVER PG 1-8
    - IPDRIVER PG 1-9
    - TCPDRIVER PG 1-9
    - UDPDRIVER PG 1-9
    - TCPware socket library PG 1-8
    - TELNET library routines PG 1-10
    - UCX compatibility services PG 1-7
    - VAX C socket routines PG 1-7
- session accounting MG 12-7

- 
- SET
    - DEBUG
      - class keyword
        - ALL UG 12-46
        - NETINPUT UG 12-46
        - NETOUTPUT UG 12-46
        - NONE UG 12-46
        - OPTIONS UG 12-46
        - TTYINPUT UG 12-46
    - TRANSLATION
      - keyword
        - CR UG 12-61
        - LF UG 12-61
        - NONE UG 12-61
  - set class values MG 30-15
  - SET command NET 2-111
    - BG\_ NET 2-113
    - DHCP NET 2-114
    - DOMAINNAME NET 2-115
    - FILTER NET 2-116
    - GATED TRACE NET 2-117
    - GATEWAY NET 2-119
    - INET NET 2-120
    - INTERFACE NET 2-121
    - IPSO NET 2-124
    - KERBEROS\_PASSWORD NET 2-128
    - LOCASE-USERNAME NET 3-30
    - LOG NET 2-129
    - MASTER\_PASSWORD NET 2-130
    - NAMED DEBUG NET 2-132
    - NAMED MAXIMUM\_TTL NET 2-133
    - NAMED MINIMUM\_TTL NET 2-134
    - NOARP NET 2-96
    - NOFILTER NET 2-116
    - NOLOG NET 2-129
    - NOROUTE NET 2-107
    - OUTGOING\_ACCESS\_RESTRICTIONS NET 2-135
    - RFC822-TO-HEADER NET 3-37
    - TIMEZONE NET 2-137
  - SET command, NSLOOKUP MG 30-15
  - SET TCPRTOMAX command
    - NETCU, IP-over-X.25 MG 8-3
  - SET TCPRTOMIN command
    - NETCU, IP-over-X.25 MG 8-3
  - setdomainname/sethostname subroutines, Socket Library PG A-59
  - setsockopt subroutine, Socket Library PG A-60
  - shared-network declaration MG 4-8
  - SHOW ACE\_USER command, NETCU MG 22-7
  - SHOW command NET 1-14, NET 2-138, NET 3-41
    - ACCESS\_LISTS NET 2-142
    - ACE\_USER NET 2-141
    - ARP NET 2-143
      - flag fields
        - CONF NET 2-143
        - LASU NET 2-143
      - LOCK NET 2-143
      - PEND NET 2-143
      - PERM NET 2-143
      - PUBL NET 2-143
  - CONNECTIONS NET 1-14, NET 2-145
  - COUNTERS NET 2-147
  - DHCP NET 2-149
  - DNIP NET 2-153
  - EXPORT NET 2-154
  - FILTER NET 2-156
  - GATED TRACE NET 2-158
  - GROUP NET 2-159
  - HOST NET 2-160
  - INTERFACE NET 2-161
  - IPSO NET 2-163
  - KACL NET 2-165
  - KDB NET 2-166
  - KERBEROS USER NET 2-168
  - MOUNT NET 2-169
  - MULTICAST\_GROUPS NET 2-170
  - NAMED VERSION NET 2-197
  - NETWORKS NET 2-171
  - OSPF NET 2-172
  - OUTGOING\_ACCESS\_RESTRICTIONS NET 2-180
  - PROXY NET 2-181
  - RIP NET 2-182
  - ROUTES NET 2-184
  - SERVICES NET 2-186
  - SNMP NET 2-189
  - STATISTICS NET 2-192
  - TICKETS NET 2-195
  - TIMEZONE NET 2-196
  - VERSION NET 2-198
  - shutdown process IG 6-4, IG 6-6
  - shutdown subroutine, Socket Library PG A-62
  - SHUTNET.COM file NET 1-7, MG 3-3
  - SITE
    - SHOW TIME UG 3-18
    - SPAWN UG 3-18
  - site-specific commands UG 3-18
    - issuing UG 3-18
  - SLIP, line identification MG 5-20
  - SMTP
    - configuration file, modifying MG 17-2
    - DECnet mail gateway, configuring MG 17-37
    - host aliases MG 17-23
    - local mail, forwarding MG 17-22
    - logicals
      - A1\_NAME UG B-21, MG 17-3, MG C-20
      - ACCEPT\_UNIX\_LF UG B-21, MG 17-3, MG C-20
      - ALLOW\_USER\_FROM UG B-21, MG 17-3, MG C-20
      - ALLOW\_VIRTUAL\_DOMAIN UG B-21, MG 17-3, MG C-21
      - AM\_DOMAIN UG B-21, MG 17-3, MG C-21

AM\_NAME UG B-21, MG 17-3, MG C-21  
APPEND\_FORWARDER\_TO\_MX MG C-21  
APPEND\_FORWARDER\_TO\_MX UG B-21,  
MG 17-3  
BATCH\_QUEUE UG B-21, MG 17-3,  
MG C-21  
DECNET\_DOMAIN UG B-21, MG 17-4,  
MG C-21  
DELIVERY\_RECEIPTS UG B-21, MG 17-4,  
MG C-21  
DISABLE\_DELIVERY\_RECEIPT\_  
DISCLAIMER UG B-21, MG 17-4,  
MG C-21  
DISABLE\_FOLDER\_DELIVERY UG B-22,  
MG 17-4, MG C-21  
DISABLE\_PSMAIL UG B-22, MG 17-4,  
MG C-21  
ENVELOPE\_FROM\_HOST UG B-22,  
MG 17-4, MG C-21  
FORWARDER UG B-22, MG 17-4, MG C-22  
FROM\_HOST UG B-22, MG 17-4, MG C-22  
HEADER\_ORG UG B-22, MG 17-4,  
MG C-22  
HEADER\_RETURN\_RECEIPT\_TO  
UG B-22, MG 17-4, MG C-22  
HEADER\_SYS UG B-22, MG 17-4, MG C-22  
HOST\_ALIAS\_FILE UG B-22, MG 17-4,  
MG C-22  
HOST\_NAME UG B-22, MG 17-5, MG C-22  
LOCALDOMAIN UG B-20, MG 17-3,  
MG C-12  
MAXIMUM\_822\_TO\_LENGTH UG B-23,  
MG 17-5, MG C-22  
MRGATE\_NAME UG B-23, MG 17-5,  
MG C-22  
NAMESERVERS UG B-20, MG 17-3  
NO\_USER\_REPLY\_TO UG B-23, MG 17-5,  
MG C-22  
NON\_LOCAL\_FORWARDER UG B-23,  
MG 17-5, MG C-22  
POSTMASTER UG B-23, MG 17-5, MG C-23  
REJECT\_INVALID\_DOMAINS UG B-23,  
MG 17-5, MG C-23  
REPLY\_TO UG B-23, MG 17-5, MG C-23  
RESENT\_HEADERS UG B-23, MG 17-5,  
MG C-23  
RETRY\_INTERVAL UG B-23, MG 17-5,  
MG C-23  
RETURN\_INTERVAL UG B-23, MG 17-5,  
MG C-23  
RETURN\_MSG UG B-23, MG 17-6,  
MG C-23  
RETURN\_RECEIPT\_TO\_HEADER\_ENABLE  
UG B-23, MG 17-6  
SEND\_CLASS UG B-24, MG 17-6, MG C-23  
SERVER\_DISABLE\_VRFYEXPN UG B-24,

MG 17-6, MG C-23  
SERVER\_LOG UG B-24, MG 17-6, MG C-23  
SERVER\_RCPT\_CHECK\_HOST UG B-24,  
MG 17-6, MG C-23  
SERVER\_REJECT\_FILE UG B-24,  
MG 17-6, MG C-23  
SERVER\_REJECT\_INFO UG B-24,  
MG 17-6, MG C-24  
SMTP\_LOG UG B-22, MG 17-5, MG C-22  
SUPPRESS\_VENDOR UG B-24, MG 17-6,  
MG C-24  
SYMBIONT\_LOG UG B-24, MG 17-6,  
MG C-24  
SYMBIONT\_PURGWS\_TIMER UG B-24,  
MG 17-6, MG C-24  
VMSMAIL\_HEADER\_CONTROL UG B-25,  
MG 17-6, MG C-28  
VMSMAIL\_LOCASE\_USERNAME UG B-25,  
MG 17-7, MG C-28  
VMSMAIL\_NO\_EXQUOTA UG B-25,  
MG 17-7, MG C-28  
VMSMAIL\_REPLY\_CONTROL UG B-25,  
MG 17-7, MG C-28  
VMSMAIL\_USE\_RFC822\_TO\_HEADER  
UG B-25, MG 17-7, MG C-28  
WINDOW\_SIZE UG B-24, MG 17-6,  
MG C-24

## mail

aliases, configuring MG 17-24  
gateways, configuring MG 17-23  
messages, rejecting MG 17-8  
parameters  
    ALIAS-FILE MG 17-16  
    DECNET-DOMAIN MG 17-16  
    DELIVERY-RECEIPTS MG 17-16  
    DISABLE-PSMAIL MG 17-16  
    DISALLOW-USER-REPLY-TO  
        MG 17-16  
    FORWARDER MG 17-16  
    FORWARD-LOCAL-MAIL MG 17-16  
    FORWARD-REMOTE-MAIL MG 17-16  
    HEADER-CONTROL MG 17-16  
    HOST-ALIAS-FILE MG 17-16  
    LOCAL-MAIL-FORWARDER MG 17-17  
    POSTMASTER MG 17-17  
    QUEUE-COUNT MG 17-17  
    REPLY-CONTROL MG 17-17  
    RESENT-HEADERS MG 17-17  
    RETRY-INTERVAL MG 17-17  
    RETURN-INTERVAL MG 17-17  
    SEND-BROADCAST-CLASS MG 17-17  
    SMTP-HOST-NAMES MG 17-17  
    START-QUEUE-MANAGER MG 17-17  
queues MG 17-18  
    configuring MG 17-19  
multiple queues, configuring MG 17-20

- network service monitoring MG 17-12
- queue groups, configuring MG 17-20
- server, inbound mail MG 17-17
- service for ALL-IN-1 users MG 17-31
- session accounting MG 17-13
  - accounting file record format MG 17-14
  - configuration file MG 17-13
  - configuring MG 17-13
  - configuring the Accounting listener MG 17-14
  - enabling MG 17-14
  - file format MG 17-14
- specific folders, delivering mail to MG 17-7
- symbiont MG 17-18
- SMTP/MR
  - configuration MG 17-35
  - document conversion MG 17-34
- SMTP\_SERVER\_REJECT MG 17-8
- SMTP-OpenVMS
  - configuring IG 4-47
- SMTP-to-DECnet mail MG 17-37
- SMUX
  - peers, adding MG 7-13
- SNMP
  - agent extensibility MG 7-14
  - logical
    - DEBUG UG B-24, MG C-24
  - services
    - access profile MG 7-3
    - community MG 7-3
      - parameters MG 7-12
    - configuration file MG 7-10
    - configuring MG 7-9
    - extendible MIBs, supporting MG 7-14
    - links MG 7-1
    - log file MG 7-15
    - Management Information Base (MIB) MG 7-2
      - access rules MG 7-3
      - groups MG 7-3
    - management objects MG 7-2
      - defining values MG 7-10
      - supported MG 7-2
    - management objects, client-controllable MG 7-3
  - traps MG 7-1
    - client controllable MG 7-2
    - client-controllable MG 7-13
    - enabling/disabling MG 7-12
    - generating MG 7-13
    - unsupported MG 7-2
  - troubleshooting MG 7-15
- session accounting NET 2-189
- session accounting command
  - FILENAME NET 2-190
  - PEER NET 2-190
  - PORT NET 2-190
- SNMP agent
  - configuring an IG 4-49
- SNMP Extendible Agent API Routines
  - data structures PG 10-3
  - programming PG 10-1
- SNMP extendible agent API routines
  - debugging code PG 10-3
  - initializing SNMP subagent PG 10-4
  - installing the extension agent image PG 10-3
  - linking the extension agent image PG 10-2
  - prerequisites PG 10-2
  - querying SNMP subagent PG 10-8
  - reference PG 10-3
  - registering multiple subtrees PG 10-6
  - sample code PG 10-3
  - sending trap from subagent PG 10-10
  - SnmpExtensionInit PG 10-4
  - SnmpExtensionInitEx PG 10-6
  - SnmpExtensionQuery PG 10-8
  - SnmpExtensionTrap PG 10-10
- SNMP Multiplexing (SMUX) protocol MG 7-13
- SNMP Services MG 7-1
  - managing MG 7-1
- SNMP services
  - configuring IG 4-48
- SNMP\_COMMON.H file PG 10-1
- SNMPD.CONF file MG 7-2, MG 7-10
- SnmpExtensionInit
  - SNMP Extendible Agent API Subroutines PG 10-4
- SnmpExtensionInitEx
  - SNMP Extendible Agent API Subroutines PG 10-6
- SnmpExtensionQuery
  - SNMP Extendible Agent API Subroutines PG 10-8
- SnmpExtensionTrap
  - SNMP Extendible Agent API Subroutines PG 10-10
- SOA record MG 3-35
- sockaddr\_in structure PG 1-15
- sockaddr\_in structure, Socket Library PG A-10
- socket
  - call
    - accept PG 1-12
    - bind PG 1-13
    - close PG 1-13
    - connect PG 1-13
    - getpeername PG 1-13
    - getsockname PG 1-13
    - getsockopt PG 1-13
    - listen PG 1-13
    - read PG 1-13
    - recv PG 1-13
    - recvfrom PG 1-13
    - select PG 1-14
    - send PG 1-14
    - sendto PG 1-14
    - setsockopt PG 1-13
    - socket PG 1-14
    - write PG 1-14

- calls in network programming, using PG 1-11
- concepts PG 1-4
- data structures PG 1-14
  - hostent PG 1-15
  - servent PG 1-16
  - sockaddr\_in PG 1-15
- library PG 8-1
- library services, sample programs PG 8-2
- programming PG 1-11
- subroutine, Socket Library PG A-63
- system calls PG 1-11
- Socket Library Services
  - hostent structure PG A-8
  - include (header) files PG A-2
  - netent structure PG A-9
  - programming PG 1-8, PG 8-1, PG A-1
  - protoent structure PG A-9
  - sample programs PG A-6
  - sample server programs PG A-77
  - servent structure PG A-9
  - server operation PG A-8
  - sockaddr\_in structure PG A-10
  - socket option values
    - SOL\_SOCKET PG A-60
  - subroutine categories PG A-7
    - byte order conversion operations PG A-8
    - byte string operations PG A-8
    - ia address conversion subroutines PG A-8
    - lookup operations PG A-7
    - socket operations PG A-7
  - subroutine reference PG A-11
    - accept PG A-12
    - bcmp PG A-14
    - bcopy PG A-15
    - bind PG A-16
    - bzero PG A-18
    - connect PG A-19
    - getdomainname/gethostname PG A-21
    - gethostbyaddr PG A-22
    - gethostbyname PG A-23
    - gethostid PG A-25
    - getnetbyaddr PG A-26
    - getnetbyname PG A-27
    - getpeername PG A-28
    - getprotobyname PG A-29
    - getprotobynumber PG A-30
    - getservbyname PG A-31
    - getservbyport PG A-32
    - getsockname PG A-33
    - getsockopt PG A-34
    - HNS\_LOOKUPHOST PG A-35
    - HNS\_LOOKUPIA PG A-36
    - htonl PG A-37
    - htons PG A-38
    - inet\_ PG A-39
    - ipso\_getauthbyname PG A-41
    - ipso\_getauthbynumber PG A-43
    - ipso\_getlevelbyname PG A-44
    - ipso\_getlevelbynumber PG A-45
    - listen PG A-46
    - ntohl PG A-47
    - ntohs PG A-48
    - pnerror PG A-49
    - recvfrom PG A-50
    - resolver PG A-52
    - select PG A-55
    - select\_wake PG A-56
    - sendto PG A-57
    - setdomainname/sethostname PG A-59
    - setsockopt PG A-60
    - shutdown PG A-62
    - socket PG A-63
    - socket\_close PG A-65
    - socket\_ioctl PG A-66
    - socket\_read/socket\_recv PG A-68
    - socket\_send/socket\_write PG A-70
    - tcpware\_atolineid PG A-72
    - tcpware\_gettimezone PG A-73
    - tcpware\_lineidtoa PG A-74
    - tcpware\_server PG A-75
    - tcpware\_settimezone PG A-76
    - subroutines list PG A-3
  - SOCKET.H file PG 6-21
  - socket\_close subroutine, Socket Library PG A-65
  - socket\_ioctl subroutine, Socket Library PG A-66
  - socket\_read/socket\_recv subroutines, Socket Library PG A-68
  - socket\_send/socket\_write subroutines, Socket Library PG A-70
  - SOCKETVAR.H file PG A-63
  - SOCKLIB.OLB file PG A-6
  - SOL\_SOCKET option
    - SO\_BROADCAST PG 6-42
    - SO\_DEBUG PG 6-42
    - SO\_DONTROUTE PG 6-42
    - SO\_ERROR PG 6-43
    - SO\_KEEPAIVE PG 6-43
    - SO\_LINGER PG 6-43
    - SO\_OOBINLINE PG 6-43
    - SO\_RCVBUF PG 6-43
    - SO\_RCVLOWAT PG 6-43
    - SO\_RCVTIMEO PG 6-43
    - SO\_REUSEADDR PG 6-43
    - SO\_SNDBUF PG 6-43
    - SO\_SNDLOWAT PG 6-43
    - SO\_SNDTIMEO PG 6-43
    - SO\_TYPE PG 6-43
    - SO\_USELOOPBACK PG 6-43
  - SPAWN command NET 2-199
  - SPAWN command, NSLOOKUP MG 30-19
  - special characters NET 2-21

- spoofing
  - DNS UG 16-1
  - IP UG 16-1
  - routing UG 16-1
- spool directory
  - creating a IG 4-35
- SQL\*Net
  - installing and configuring Oracle's IG 6-10
- SRI International mapping MG A-1
- SSH
  - authentication agent UG 16-20
  - changing configuration MG 25-13
  - command options UG 16-5
  - connection and login MG 25-14
  - daemon files MG 25-25
    - SSH\_STARTUP.COM MG 25-25
    - SSHD.LOG MG 25-25
    - SSHD\_MASTER.LOG MG 25-25
  - enabling MG 25-13
  - logicals MG 25-22
    - ALLOW\_EXPIRED\_PW UG B-25, MG C-24
    - ALLOW\_PREEXPIRED\_PW UG B-25, MG C-24
    - KEYGEN\_MIN\_PW\_LEN UG B-25, MG C-24
    - PARAMETERS UG B-25, MG C-24
    - SSH\_CONTROL.COM UG B-1, MG C-1
    - SSH\_DIR UG B-2, MG 25-22, MG C-1
    - SSH\_EXE UG B-2, MG 25-23, MG C-2
    - SSH\_LOG UG B-2, MG 25-23, MG C-2
    - SSH\_MAX\_SESSIONS UG B-2, MG 25-23, MG C-2
    - SSH\_TERM\_MBX UG B-2, MG 25-23, MG C-2
    - TCPWARE\_SSH\_ALLOW\_EXPIRED\_PW MG 25-24
    - TCPWARE\_SSH\_ALLOW\_PREEXPIRED\_PW MG 25-24
    - TCPWARE\_SSH\_KEYGEN\_MIN\_PW\_LEN MG 25-24
    - TCPWARE\_SSH\_PARAMETERS MG 25-24
    - TCPWARE\_SSH\_USE\_SYSGEN\_LGI MG 25-24
    - USE\_SYSGEN\_LGI UG B-25, MG C-25
  - starting the server MG 25-10
- SSH command
  - ALLOW\_REMOTE\_CONNECT UG 16-5
  - CIPHER UG 16-6
  - COMPRESSION UG 16-6
  - DEBUG UG 16-6
  - ESCAPE\_CHARACTER UG 16-7
  - IDENTITY\_FILE UG 16-7
  - LOCAL\_FORWARD UG 16-7
  - LOG\_FILE UG 16-7
  - NO\_AGENT\_FORWARDING UG 16-7
  - OPTION UG 16-7
  - PORT UG 16-7
  - QUIET UG 16-8
  - REMOTE\_FORWARD UG 16-8
  - USE\_NONPRIV\_PORT UG 16-8
  - USERNAME UG 16-8
  - VERSION UG 16-8
- SSH command line option
  - bits MG 25-3
  - config\_file MG 25-3
  - debug MG 25-3
  - host MG 25-3
  - host\_key\_file MG 25-3
  - key\_gen\_time MG 25-3
  - login\_grace\_time MG 25-3
  - port MG 25-4
  - quiet\_mode MG 25-4
- SSH files
  - AUTHORIZED\_KEYS UG 16-16
  - CONFIG. UG 16-16
  - HOSTS.EQUIV UG 16-18
  - IDENTITY. UG 16-16
  - IDENTITY.PUB UG 16-16
  - KNOWN\_HOSTS UG 16-17
  - RANDOM\_SEED. UG 16-17
  - RHOSTS UG 16-18
  - SHOSTS UG 16-18
  - SHOSTS.EQUIV UG 16-19
  - SSH\_CONFIG UG 16-19
  - SSH\_KNOWN\_HOSTS UG 16-19
- SSH services
  - configuring IG 4-50
- SSH\_KNOWN\_HOSTS
  - file
    - AUTHORIZED\_KEYS MG 25-21
    - SHOSTS MG 25-21
    - SY\$LOGIN
      - RHOSTS MG 25-22
    - TCPWARE
      - HOSTS.EQUIV MG 25-19
      - SHOSTS.EQUIV MG 25-20
      - SSH\_HOST\_KEY MG 25-20
      - SSH\_HOST\_KEY.PUB MG 25-20
      - SSH\_KNOWN\_HOSTS MG 25-20
      - SSH\_RANDOM\_SEED MG 25-21
      - SSHD\_CONFIG MG 25-21
- SSHADD UG 16-20, UG 16-21
- SSHADD option
  - DELETE UG 16-21
  - LIST UG 16-21
  - PURGE UG 16-21
- SSHAGENT UG 16-20
  - authentication agent UG 16-21
  - authentication private keys UG 16-20
- SSHD MG 25-2, MG 25-14
- SSHD configuration file keyword
  - AllowForwardingPort MG 25-4
  - AllowForwardingTo MG 25-4

- AllowGroups MG 25-5
- AllowHosts MG 25-5
- AllowSHosts MG 25-5
- AllowTcpForwarding MG 25-5
- AllowUsers MG 25-6
- DenyForwardingPort MG 25-6
- DenyForwardingTo MG 25-6
- DenyGroups MG 25-6
- DenyHost MG 25-6
- DenySHosts MG 25-7
- DenyUsers MG 25-7
- HostKey MG 25-7
- IdleTimeout MG 25-7
- IgnoreRhosts MG 25-7
- KeepAlive MG 25-8
- KeyRegenerationInterval MG 25-8
- ListenAddressee MG 25-8
- LoginGraceTime MG 25-8
- PasswordAuthentication MG 25-8
- PermitEmptyPasswords MG 25-8
- PermitRootLogin MG 25-9
- Port MG 25-9
- QuietMode MG 25-9
- RandomSeed MG 25-9
- RhostsAuthentication MG 25-9
- RhostsRSAAuthentication MG 25-9
- RSAAuthentication MG 25-9
- ServerKeyBits MG 25-10
- SilentDeny MG 25-10
- StrictModes MG 25-10
- SyslogFacility MG 25-10
- VerboseLogging MG 25-10
- X11DisplayOffset MG 25-10
- SSHD\_MASTER MG 25-1, MG 25-14
- SSHKEYGEN UG 16-22
  - authentication key pairing UG 16-22
  - definition UG 16-22
  - file
    - IDENTITY UG 16-24
    - IDENTITY.PUB UG 16-24
    - RANDOM\_SEED UG 16-24
  - option
    - BITS UG 16-23
    - CHANGE\_CIPHER UG 16-23
    - CHANGE\_COMMENT UG 16-23
    - CHANGE\_PASSPHRASE UG 16-23
    - COMMENT UG 16-23
    - HOST UG 16-23
    - IDENTITY\_FILE UG 16-23
    - NEW\_PASSPHRASE UG 16-23
    - PASSPHRASE UG 16-23
- Start of Authority (SOA) record, DNS MG 3-35
- START/ command
  - DNIP NET 2-200
  - IP NET 2-202
  - NET NET 2-201
  - PWIP NET 2-210
  - TCP NET 2-211
  - UCX NET 2-213
  - UDP NET 2-214
- START/IP command
  - NETCU, IP-over-X.25 configuration MG 8-2
- START/QUEUE command MG 15-15
- START/TCP command
  - NETCU, IP-over-X.25 configuration MG 8-3
- STARTNET.COM file NET 1-7, MG 3-3
- startup
  - configuration menu IG 6-4
  - customizing your IG 6-7
- startup command IG 6-6
- startup command file UG 3-16
- startup file name IG 6-4
- startup process
  - automatic IG 6-3
- STARTUP\_RESOLVER.COM file MG 3-2
- STASH MASTER\_PASSWORD command NET 2-215
- static
  - route definitions MG 9-63
  - routing, setting up MG 9-2
- static leases MG 4-57
- stolen key MG 25-17
- STOP/ command
  - DHCP NET 2-216
  - DNIP NET 2-217
  - DNS NET 2-218
  - GATED NET 2-219
  - INET NET 2-220
  - IP NET 2-221
  - NAMED NET 2-222
  - NETCP NET 2-223
  - PWIP NET 2-224
  - SERVER NET 2-225
  - TCP NET 2-227
  - UCX NET 2-228
  - UDP NET 2-229
- STORE command qualifier MG 12-26
- STOU command MG 12-25
- stream service
  - client, writing PG 1-18
  - server, writing PG 1-19
- STRUCTURE
  - command keyword value
    - FILE UG 3-78
    - RECORD UG 3-78
    - VMS UG 3-78
  - subclass declaration MG 4-37
- Subnetwork Access Protocol (SNAP)
  - format in TCPDUMP MG 30-28, MG 30-42
- Subroutine Categories PG A-7
- superuser MG 14-3
  - adding to PROXY database MG 14-3
  - default UID/GID MG 14-20



Server-NFS MG 14-2, MG 14-3  
 svc\_destroy, RPC RTL PG 18-5  
 svc\_freeargs, RPC RTL PG 18-6  
 svc\_getargs, RPC RTL PG 18-7  
 svc\_getcaller, RPC RTL PG 18-8  
 svc\_getchan, RPC RTL PG 18-9  
 svc\_getport, RPC RTL PG 18-10  
 svc\_getreqset, RPC RTL PG 18-11  
 svc\_register, RPC RTL PG 18-13  
 svc\_run, RPC RTL PG 18-14  
 svc\_sendreply, RPC RTL PG 18-15  
 svc\_sendreply\_dq, RPC RTL PG 18-15  
 svc\_unregister, RPC RTL PG 18-16  
 svcerr\_auth, RPC RTL PG 18-17  
 svcerr\_decode, RPC RTL PG 18-17  
 svcerr\_noproc, RPC RTL PG 18-17  
 svcerr\_noprog, RPC RTL PG 18-17  
 svcerr\_progvers, RPC RTL PG 18-17  
 svcerr\_systemerr, RPC RTL PG 18-17  
 svcerr\_weakauth, RPC RTL PG 18-17  
 svcfd\_create, RPC RTL PG 18-19  
 svcraw\_create, RPC RTL PG 18-20  
 svctcp\_create, RPC RTL PG 18-21  
 svctcpa\_create, RPC RTL PG 18-22  
 svctcpa\_enablecache, RPC RTL PG 18-23  
 svctcpa\_freecache, RPC RTL PG 18-25  
 svctcpa\_getxdrs, RPC RTL PG 18-26  
 svctcpa\_shutdown, RPC RTL PG 18-27  
 svcudp\_bufcreate, RPC RTL PG 18-28  
 svcudp\_create, RPC RTL PG 18-28  
 svcudp\_enablecache, RPC RTL PG 18-29  
 svcudpa\_bufcreate, RPC RTL PG 18-30  
 svcudpa\_create, RPC RTL PG 18-30  
 svcudpa\_enablecache, RPC RTL PG 18-32  
 svcudpa\_freecache, RPC RTL PG 18-34  
 svcudpa\_getxdrs, RPC RTL PG 18-35  
 svcudpa\_shutdown, RPC RTL PG 18-36  
 SYLOGIN.COM file MG 19-11  
 symbolic links in UNIX systems UG 3-14  
 symbolic time zones IG 3-21  
 synchronized timekeeping MG 10-2  
 SYS parameter  
   CHANNELCNT IG 5-13  
   GBLPAGES IG 5-14  
   GBLPAGFIL IG 5-14  
   MAXBUF IG 5-14  
   NPAGEDYN IG 5-14  
   NPAGEVIR IG 5-14  
   VIRTUALPAGECNT IG 5-13  
   WSMAX IG 5-13  
 SYSS\$ASSIGN function code, INETDRIVER PG 6-49  
 SYSS\$ASSIGN function code, TCPDRIVER PG 3-35  
 SYSS\$ASSIGN function code, UDPDRIVER PG 4-30  
 SYSS\$CANCEL function code, INETDRIVER PG 6-51  
 SYSS\$CANCEL function code, TCPDRIVER PG 3-37  
 SYSS\$CANCEL function code, UDPDRIVER PG 4-32

SYSS\$DASSGN function code, INETDRIVER PG 6-52  
 SYSS\$DASSGN function code, TCPDRIVER PG 3-38  
 SYSS\$DASSGN function code, UDPDRIVER PG 4-33  
 SYSINFO client PG 20-3  
 SYSNAM privilege MG 13-17  
 SYSPRV privilege MG 13-9  
 system-generated PIN, receiving a UG 14-6

---

## T

TALK  
   using UG 11-1  
 TALK command  
   TALK UG 11-4  
 TALK utility  
   configuring the IG 4-52  
 TCLB  
   logical  
     BIAS MG C-25  
 TCP PG 1-2  
   counters  
     TCPDRIVER PG 3-19  
     UDPDRIVER PG 4-16  
 TCP packets, monitoring using TCPDUMP MG 30-25  
 TCP/IP  
   header compression MG 5-10  
   load balancing MG 3-41  
     address list MG 3-42  
     analogous to LAT MG 3-41  
     cluster name MG 3-42  
     cluster names, defining MG 3-42  
     configuration requirements MG 3-41  
     description MG 3-41  
     DNS server MG 3-42  
       cluster names MG 3-42  
       load metrics MG 3-42  
   load request protocol  
     function MG 3-44  
     load calculation MG 3-45  
     load updates MG 3-44  
     logicals MG 3-45  
     UDP datagram requests MG 3-44  
   logicals MG 3-45  
   observed load MG 3-42  
   process MG 3-42  
   TCP connection MG 3-41  
   use  
     TCP protocols MG 3-41  
     UDP protocols MG 3-41  
   use, TELNET MG 3-41  
   what it does not do MG 3-41  
   network programming PG 1-1  
   programming concepts PG 1-1  
 TCP/IP connections MG 25-2  
 TCP/IP services

- basic configuration choice IG 4-2
  - cluster load balancing UG 1-5
  - component configuration choice IG 4-3
  - configuring the IG 4-1
  - database support UG 1-5
  - DECnet over IP UG 1-5
  - DECwindows UG 1-5
  - full configuration choice IG 4-2
  - interface support UG 1-6
  - multicasting UG 1-6
  - network management UG 1-7
  - network security UG 1-7
  - other clients and servers UG 1-7
  - PATHWORKS support UG 1-7
  - routing UG 1-8
  - TCP\_SOCKET\_CLIENT.C file PG 8-3
  - TCP\_SOCKET\_SERVER.C file PG 8-3
  - TCPDRIVER Services
    - function codes
      - IO\$\_READVBLK
        - IO\$\_M\_DATACHECK modifier PG 3-11
        - IO\$\_M\_NOW modifier PG 3-11
        - IO\$\_M\_PACKED modifier PG 3-11
      - IO\$\_SENSEMODE | IO\$\_M\_CTRL PG 3-15
      - IO\$\_SENSEMODE | IO\$\_M\_RD\_COUNT
        - IO\$\_M\_CLR\_COUNT modifier PG 3-19
    - programming PG 3-1
    - reading
      - active connection status PG 3-13
      - TCP counters PG 3-19
    - receiving data PG 3-11
    - requesting AST delivery PG 3-21
    - scattergather write array structure PG 3-34
    - set characteristics buffer PG 3-23
    - setting connection characteristics PG 3-23
    - zeroing TCP counters PG 3-19
  - TCPDRIVER services
    - assigning channel to device PG 3-1, PG 3-35
    - asynchronous system trap (AST) PG 3-5
      - attention PG 3-21
    - call
      - arguments PG 3-3
      - format PG 3-3
    - cancelling I/O PG 3-37
    - closing local end of connection PG 3-2, PG 3-27
    - connection status PG 3-13
    - deassigning channel PG 3-2
    - function codes PG 3-6
      - IO\$\_CREATE PG 3-7
      - IO\$\_READVBLK PG 3-11
      - IO\$\_SENSEMODE PG 3-13
      - IO\$\_SENSEMODE | IO\$\_M\_CTRL PG 3-16
      - IO\$\_SENSEMODE | IO\$\_M\_RD\_COUNT PG 3-19
      - IO\$\_SETMODE | IO\$\_M\_ATTNAST PG 3-21
      - IO\$\_SETMODE | IO\$\_M\_CTRL PG 3-23
      - IO\$\_SETMODE | IO\$\_M\_CTRL |
        - IO\$\_M\_SHUTDOWN PG 3-27
      - IO\$\_M\_ABORT modifier PG 3-27
    - IO\$\_SETMODE | IO\$\_M\_CTRL |
      - IO\$\_M\_STARTUP PG 3-28
    - IO\$\_WRITEVBLK PG 3-30
      - IO\$\_M\_OUTBAND modifier PG 3-30
    - IO\$\_WRITEVBLK | IO\$\_M\_EXTEND PG 3-32
    - SYSS\$ASSIGN PG 3-35
    - SYSS\$CANCEL PG 3-37
    - SYSS\$DASSGN PG 3-38
  - I/O status block PG 3-15
  - miscellaneous operations PG 3-2
  - opening a connection PG 3-1
    - active PG 3-28
    - passive PG 3-28
  - performing read requests PG 3-2
  - programming PG 1-9
  - releasing channel PG 3-38
  - sample program PG 3-39
  - sending data PG 3-30
    - stored in list PG 3-32
    - urgent PG 3-30
  - socket style listens and accepts PG 3-7
- TCPDRIVER\_CLIENT.C file PG 3-39
- TCPDRIVER\_SERVER.C file PG 3-39
- TCPDUMP
  - command NET 2-230
  - command reference MG 30-33
  - utility MG 30-25
    - ARP and RARP packets, monitoring MG 30-28
    - command reference MG 30-34
    - data within packet, accessing MG 30-43
    - DNS name server
      - requests, monitoring MG 30-29
      - responses, monitoring MG 30-30
    - expressions MG 30-38
      - other MG 30-40
      - primitives MG 30-40
      - qualifiers MG 30-38
    - IP fragmentation, monitoring MG 30-32
    - link level headers, displaying MG 30-28
    - NFS requests and replies, monitoring MG 30-31
    - output
      - RLOGIN sample MG 30-27
      - sample MG 30-25
    - output, interpreting MG 30-25
    - primitives, combining MG 30-43
    - TCP packets, monitoring MG 30-25
    - UDP packets, monitoring MG 30-28
- TCPSAMPLE.FOR file PG 3-40
- TCPWARE
  - FTPSERVER\_DTP.COM MG 12-3
  - HOSTS.EQUIV UG 16-1

- 
- SHOST.EQUIV UG 16-1
  - SSH\_KNOWN\_HOSTS MG 25-18
  - SSHD\_CONFIG MG 25-4
  - TCPware
    - Access Control Encryption (ACE) Client MG 22-1
    - account privileges IG 6-2
    - components IG C-2
    - components to install IG 1-4
    - DECwindows Transport Interface MG 29-2
    - family members UG 1-3
      - FTP-OpenVMS UG 1-3
      - NFS-OpenVMS client UG 1-3
      - NFS-OpenVMS server UG 1-3
      - SMTP-OpenVMS UG 1-3
      - TCP-OpenVMS UG 1-4
      - TELNET-OpenVMS UG 1-3
    - for OpenVMS UG 1-2
      - documentation UG A-1
    - general requirements IG 1-3
    - global pages IG 1-2
    - hardware requirements IG 1-2
    - installation preparation IG 1-1
    - installing components IG 2-4
    - installing on mixed platform clusters IG 2-6
    - installing on multiple system disks IG 2-6
    - installing other products IG 2-7
    - load the software IG 2-1
    - online documentation IG 1-5
    - post-installation tasks IG 2-8
    - preconfiguration steps IG 3-1
    - print services MG 15-1
    - release notes IG 1-5
    - required disk space IG 1-2
    - running IG 1-1
    - sample configuration IG B-1
    - sample installation IG A-1
    - Secure Shell (SSH) client UG 16-1
    - software requirements IG 1-2
    - starting VMSINSTAL IG 2-2
    - system parameters IG 6-2
    - testing IG 6-14
    - where to install IG 1-4
  - TCPware commands
    - configuring the IG 6-3
  - TCPware component
    - ACECLIENT IG C-2
    - CNFS IG C-2
    - DHCP IG C-2
    - DNIP IG C-2
    - DNS IG C-2
    - FSS IG C-3
    - FTP IG C-2
    - GATED IG C-2
    - IMAP IG C-2
    - IPX IG C-3
    - KERBEROS IG C-2
    - LPS IG C-2
    - MISC IG C-3
    - NFS IG C-3
    - NPS IG C-3
    - NTP IG C-3
    - POP3 IG C-3
    - PWIP IG C-3
    - RCMD IG C-3
    - SMTP IG C-3
    - SNMP IG C-3
    - TALK IG C-3
    - TELNET IG C-3
    - TES IG C-3
    - TIMED IG C-3
    - XDM IG C-3
  - TCPware components
    - removing IG 6-12
  - TCPware for OpenVMS
    - socket library PG A-1
  - TCPware logical
    - TCPWARE IG 3-2
    - TCPWARE\_COMMON IG 3-2
    - TCPWARE\_INCLUDE IG 3-2
    - TCPWARE\_ROOT IG 3-2
    - TCPWARE\_SPECIFIC IG 3-2
  - TCPware logical name
    - TCPWARE IG C-1
    - TCPWARE\_COMMON IG C-2
    - TCPWARE\_INCLUDE IG C-1
    - TCPWARE\_ROOT IG C-1
    - TCPWARE\_SPECIFIC IG C-1
  - TCPware logicals
    - defining the IG C-1
  - TCPware SSH server MG 25-1
  - TCPware startup
    - preparing for IG 6-1
  - tcpware\_atolineid subroutine, Socket Library PG A-72
  - TCPWARE\_CONTROL rights identifier MG 5-24
  - TCPWARE\_DOMAINLIST logical MG 3-2
  - TCPWARE\_DOMAINNAME logical MG 3-2
  - TCPWARE\_FTP\_220\_REPLY logical MG 12-13
  - TCPWARE\_FTP\_221\_REPLY logical MG 12-14
  - TCPWARE\_FTP\_230\_REPLY logical MG 12-14
  - TCPWARE\_FTP\_421\_REPLY logical MG 12-14, MG 19-12
  - TCPWARE\_FTP\_ALLOWCAPTIVE logical MG 12-15
  - TCPWARE\_FTP\_ANONYMOUS\_230\_REPLY logical MG 12-15
  - TCPWARE\_FTP\_ANONYMOUS\_RIGHTS logical MG 12-16, MG 19-12
  - TCPWARE\_FTP\_ANONYMOUS\_ROOT logical MG 12-5, MG 12-16, MG 19-12
  - TCPWARE\_FTP\_IDLE\_TIMEOUT logical MG 12-17
  - TCPWARE\_FTP\_LOGFILE logical MG 12-18, MG 19-12
  - TCPWARE\_FTP\_MAXREC logical MG 12-18

- TCPWARE\_FTP\_ROOT logical MG 12-5, MG 12-15,  
MG 12-16, MG 12-17, MG 12-20
- TCPWARE\_FTP\_username\_ROOT logical UG B-10,  
MG 12-5, MG 12-20
- TCPWARE\_FTP\_WINDOW logical MG 12-10,  
MG 12-18, MG 12-23
- tcpware\_gettimeofday subroutine, Socket Library  
PG A-73
- TCPWARE\_KERBV4\_MAXAGE logical MG 23-5
- TCPWARE\_KERBV4\_PRIMARY logical MG 23-5
- TCPWARE\_KERBV4\_REALM logical MG 23-5
- TCPWARE\_KERBV4\_SrvTYP logical MG 23-4
- tcpware\_lineidtoa subroutine, Socket Library PG A-74
- TCPWARE\_LPD\_DEFAULT\_USER logical MG 15-9
- TCPWARE\_LPRSMB\_\*\_RETRY\_INTERVAL MG 15-7
- TCPWARE\_LPRSMB\_\*\_TIMEOUT MG 15-7
- TCPWARE\_LPRSMB\_qname\_RETRY\_INTERVAL  
MG 15-7
- TCPWARE\_LPRSMB\_qname\_TIMEOUT MG 15-7
- TCPWARE\_NAMED\_MAX\_CACHE\_TTL logical  
MG 3-13
- TCPWARE\_NAMESERVERS logical MG 3-2
- TCPWARE\_NETCU-E-TKTNODES NET 2-110
- TCPWARE\_NETCU-I-TKTDESTR NET 2-110
- TCPWARE\_NETCU-W-NTKTTODES NET 2-110
- TCPWARE\_NFS\_ACCESS\_IDENTIFIER logical  
MG 14-16
- TCPWARE\_NFS\_DFLT\_GID logical MG 14-20
- TCPWARE\_NFS\_DFLT\_UID logical MG 14-20
- TCPWARE\_NFS\_DIRLIFE\_TIMER logical MG 14-20
- TCPWARE\_NFS\_DIRREAD\_LIMIT logical MG 14-20
- TCPWARE\_NFS\_DIRTIME\_TIMER logical MG 14-20
- TCPWARE\_NFS\_FILE\_CACHE\_SIZE logical  
MG 14-21
- TCPWARE\_NFS\_LOG\_CLASS logical MG 14-17
- TCPWARE\_NFS\_NOCHECKSUM logical MG 14-21
- TCPWARE\_NFS\_OPENFILE\_TIMER logical MG 14-21
- TCPWARE\_NFS\_PCNFSD\_DFLTPRTOPT logical  
MG 14-21
- TCPWARE\_NFS\_PCNFSD\_ENABLE logical MG 14-19
- TCPWARE\_NFS\_PCNFSD\_JOB\_LIMIT logical  
MG 14-22
- TCPWARE\_NFS\_PCNFSD\_PRINTER logical  
MG 14-22
- TCPWARE\_NFS\_PCNFSD\_PRINTER\_LIMIT  
logical MG 14-22
- TCPWARE\_NFS\_PCNFSD\_SPOOL logical MG 14-19
- TCPWARE\_NFS\_PORT logical MG 14-22
- TCPWARE\_NFS\_SECURITY logical MG 14-17
- TCPWARE\_NFS\_TCP\_THREADS logical MG 14-22
- TCPWARE\_NFS\_UDP\_THREADS logical MG 14-22
- TCPWARE\_NFS\_XID\_CACHE\_SIZE logical MG 14-23
- TCPWARE\_PPPD\_DEBUG\_LEVEL logical MG 5-19
- TCPWARE\_PPPD\_OPCOM\_LEVEL logical MG 5-19
- TCPWARE\_RCMD\_OUTPUT logical MG 16-4
- TCPWARE\_RES\_OPTIONS logical MG 3-2
- TCPWARE\_RPCLIB\_SHR.EXE file PG 19-13
- TCPWARE\_RPCLIBD\_SHR.EXE file PG 19-14
- TCPWARE\_RPCLIBG\_SHR.EXE file PG 19-13
- TCPWARE\_RPCLIBT\_SHR.EXE file PG 19-14
- tcpware\_server subroutine, Socket Library PG A-75
- tcpware\_settimeofday subroutine, Socket Library  
PG A-76
- TCPWARE\_SLIP\_n logical MG 5-20
- TCPWARE SOCKLIB\_SHR.EXE file PG A-6
- TCPWARE SOCKLIBG\_SHR.EXE file PG A-6
- TCPWARE\_TCLB\_BIAS logical MG 3-45
- TCPWARE\_TELNETD\_INTRO\_MSG logical MG 19-14
- TCPWARE\_TIMED\_EXCLUDE logical MG 11-4
- TCPWARE\_TIMED\_MODE logical MG 11-4
- TEAMLINKS
  - configuring Compaq's IG 6-11
- TEL\_ABORT\_CONNECTION, TELNET subroutine  
PG 9-6
- TEL\_ALLOCATE\_CCB, TELNET subroutine PG 9-7
- TEL\_CLOSE\_CONNECTION, TELNET subroutine  
PG 9-8, PG 9-10
- TEL\_DEALLOCATE\_CCB, TELNET subroutine  
PG 9-12
- TEL\_GET\_CCB, TELNET subroutine PG 9-13
- TEL\_OPEN\_CONNECTION, TELNET subroutine  
PG 9-14
- TEL\_RECEIVE\_DATA, TELNET subroutine PG 9-16
- TEL\_SEND\_COMMAND, TELNET subroutine PG 9-18
- TEL\_SEND\_DATA, TELNET subroutine PG 9-19
- TEL\_SEND\_URGENT, TELNET subroutine PG 9-20
- TEL\_SET\_CCB, TELNET subroutine PG 9-21
- TELNET
  - closing a session UG 12-5
  - command reference
    - CLOSE UG 12-21
    - DEFINE/KEY UG 12-21
    - EXIT UG 12-21
    - FLUSH UG 12-21
    - HELP UG 12-21
    - OPEN UG 12-21
    - RESUME UG 12-21
    - SEND UG 12-21
    - SET DEBUG UG 12-21
    - SET DELETE\_ALLOWED UG 12-21
    - SET LOG UG 12-21
    - SET PRINT UG 12-21
    - SET TERMINAL\_TYPE UG 12-21
    - SET TRANSLATION UG 12-21
    - SHOW OPTIONS UG 12-21
    - SHOW STATUS UG 12-21
    - SHOW TRANSLATION UG 12-21
    - SPAWN UG 12-21
  - command synonym
    - BYE UG 12-21
    - CONNECT UG 12-21
    - DISCONNECT UG 12-21

- ESCAPE UG 12-21
- QUIT UG 12-21
- SET HOST UG 12-21
- STATUS UG 12-21
- Z UG 12-21
- control function
  - AO UG 12-37
  - AYT UG 12-37
  - BACKWARD UG 12-37
  - BRK UG 12-37
  - EC UG 12-37
  - EL UG 12-37
  - ESCAPE UG 12-37
  - FORWARD UG 12-37
  - GA UG 12-37
  - IP UG 12-37
  - NOIP UG 12-37
  - SYNCH UG 12-37
- issuing local commands UG 12-6
- logical
  - WINDOW MG C-25
- login sequence UG 14-4
- opening a session UG 12-2
- preparation UG 12-1
- running applications over UG 12-7
- sample session UG 12-19
- startup command file UG 12-10
- TELNET commands
  - CLOSE UG 12-22
  - DEFINE/KEY UG 12-24
  - EXIT UG 12-27
  - FLUSH UG 12-28
  - HELP UG 12-29
  - OPEN UG 12-30
  - RESUME UG 12-36
  - SEND UG 12-37
  - SET
    - DEBUG UG 12-46
    - DELETE\_ALLOWED UG 12-47
    - LOG UG 12-58
    - PRINT UG 12-59
    - TERMINAL\_TYPE UG 12-60
    - TRANSLATION UG 12-61
- SHOW
  - OPTIONS UG 12-63
  - STATUS UG 12-64
  - TRANSLATION UG 12-65
- SPAWN UG 12-66
- TELNET library routines PG 9-1
- TELNET sessions UG 16-9
- TELNET Subroutine Library
  - programming PG 9-1
- TELNET subroutine library
  - aborting connection PG 9-6
  - allocating connection control block PG 9-7
  - closing connection PG 9-8
  - connection control block (CCB) fields PG 9-2
  - deallocating connection control block PG 9-12
  - obtaining connection control block information PG 9-13
  - opening NTA device connection PG 9-10
  - opening remote host connection PG 9-14
  - programming PG 1-10
  - receiving remote host data PG 9-16
  - reference PG 9-5
  - sending commands to remote host PG 9-18
  - sending data to remote host PG 9-19
  - setting connection control block field value PG 9-21
  - TEL\_ABORT\_CONNECTION PG 9-6
  - TEL\_ALLOCATE\_CCB PG 9-7
  - TEL\_CLOSE\_CONNECTION PG 9-8
  - TEL\_CREATE\_TERMINAL PG 9-10
  - TEL\_DEALLOCATE\_CCB PG 9-12
  - TEL\_GET\_CCB PG 9-13
  - TEL\_OPEN\_CONNECTION PG 9-14
  - TEL\_RECEIVE\_DATA PG 9-16
  - TEL\_SEND\_COMMAND PG 9-18
  - TEL\_SEND\_DATA PG 9-19
  - TEL\_SEND\_URGENT PG 9-20
  - TEL\_SET\_CCB PG 9-21
  - user command processing PG 9-22
  - using TCP urgent notification PG 9-20
- TELNET\_SAMPLE.C file PG 9-2
- TELNETD
  - logicals
    - DEFCHAR MG C-25
    - FLAGS MG C-25
    - INTRO\_MSG MG C-26
- TELNET-OpenVMS
  - configuring IG 4-53
  - control functions MG 18-7
  - exiting status MG 18-8
  - listener port MG 15-19
  - local flow control, setting MG 18-6
  - logicals MG 18-1
  - options MG 18-5
    - ECHO MG 18-5
    - END-OF-RECORD MG 18-5
    - REMOTE-FLOW-CONTROL MG 18-6
    - SUPPRESS-GO-AHEAD MG 18-6
    - TERMINAL-SPEED MG 18-6
    - TERMINAL-TYPE MG 18-6
    - TRANSMIT-BINARY MG 18-6
    - WINDOW-SIZE MG 18-7
  - security MG 19-14
  - TELNET\_CONTROL.COM file MG 18-1
  - virtual terminals, setting up MG 18-4
- Terminal Server Print Services MG 15-1
  - /AUTOSTART\_ON qualifier MG 15-17
  - autostart queue MG 15-17
  - managing MG 15-13
  - OPCOM messages MG 15-20

- print queue
  - generic queue MG 15-16
  - initializing MG 15-15
  - setting up MG 15-14
  - starting MG 15-15
- print symbiont MG 15-13
- sample configuration MG 15-18
- spool device, setting up MG 15-17
- tuning logicals MG 15-20
- TES-OpenVMS
  - configuring IG 5-12
- testing tools
  - NSLOOKUP MG 30-3
  - PING MG 30-22
  - QUOTED MG 30-24
  - TCPDUMP MG 30-25
  - TRACEROUTE MG 30-44
- Text (TXT) record, DNS MG 3-38
- TFTP
  - command
    - CONNECT UG 13-1
    - GET UG 13-1
    - HELP UG 13-1
    - MODE UG 13-1
    - PUT UG 13-1
    - QUIT UG 13-1
    - REXMT UG 13-1
    - STATUS UG 13-1
    - TIMEOUT UG 13-1
    - TRACE UG 13-1
  - invoking UG 13-1
  - UNIX-to-VMS filename conversions UG 13-3, UG 13-6
- TFTP commands
  - CONNECT UG 13-2
  - GET UG 13-3
  - HELP UG 13-4
  - MODE UG 13-5
  - PUT UG 13-6
  - QUIT UG 13-7
  - REXMT UG 13-8
  - STATUS UG 13-9
  - TIMEOUT UG 13-10
  - TRACE UG 13-12
- TFTPD file access IG 4-32
- ticket file location logical UG 4-1
- time clocks, synchronizing UG 2-11
- time daemon MG 11-1
- TIME service MG 30-44
- Time Synchronization Protocol (TSP) MG 11-1
  - logical
    - TCPWARE\_TIMED\_EXCLUDE MG 11-4
    - TCPWARE\_TIMED\_MODE MG 11-4
  - master candidate election MG 11-2
  - parameters, setting MG 11-4
  - timedc, command reference MG 11-10
- Time zone
  - local differential time MG C-26
  - military MG C-26
  - parameters
    - offset MG C-26
  - universal time MG C-26
- time zone
  - local differential time PG A-76
  - military PG A-77
  - parameters
    - offset PG A-76
  - universal time PG A-77
- time zone configuration IG 3-13
- time zone rules
  - compiled-in IG 3-14
- time zone support IG 3-14
- TIMED
  - configuring IG 4-54
  - logicals
    - EXCLUDE MG C-26
    - INCLUDE MG C-26
    - MODE MG C-26
- TIMED operation mode MG 11-3
  - dependent MG 11-3
  - fixed primary MG 11-3
  - primary candidate MG 11-3
- TIMED.LOG file MG 11-11
- TIMEDC command MG 11-11
- timezone rules
  - COUNTRY MG 11-4
  - loadable MG 11-4, MG 11-6
  - RULE MG 11-6
  - ZONE MG 11-5
- TN3270
  - graphics keypad naming conventions UG 12-17
  - internationalization UG 12-14
    - character sets UG 12-16
  - keyboard mapping UG 12-12
    - alternative key mappings UG 12-13
  - keypad graphics characters UG 12-17
  - opening a session UG 12-3
  - screen printing and dumping UG 12-17
- TOGGLE GATED TRACING command NET 2-231
- Token Authentication
  - ACE/Client MG 19-9, MG 22-1
    - ACEMAIN\_CL utility MG 22-6
    - application functionality MG 22-8
    - database transfer and startup MG 22-6
    - disabling MG 22-5
    - error messages MG 22-11
    - functions MG 22-7
    - glossary of terms MG 22-2
    - logicals MG 22-4
    - NETCU commands MG 22-7
    - New PIN mode MG 22-8
    - Next Tokencode mode MG 22-8
    - related documents and standards MG 22-3

---

SDCONF.REC configuration file MG 22-6  
 user messages MG 22-9

ACE/Server  
 functions MG 22-3  
 generating reports MG 22-4  
 sdadmin program MG 22-3  
 slave MG 22-8

API functions PG 11-1  
 creadcfg PG 11-4  
 header files PG 11-2  
 how to use PG 11-2  
 reference PG 11-3  
 sd\_auth PG 11-6  
 sd\_check PG 11-7  
 sd\_close PG 11-11  
 sd\_init PG 11-5  
 sd\_next PG 11-9  
 sd\_pin PG 11-10  
 shareable image, activating PG 11-2  
 supported languages PG 11-2  
   BASIC PG 11-2  
   BLISS PG 11-2  
   C PG 11-2  
   FORTRAN PG 11-2  
   MACRO PG 11-2  
   PASCAL PG 11-2  
   PL1 PG 11-2

  encryption MG 22-8

Token Authentication Application Programming  
 Interface (API) PG 11-1

tokencode UG 14-2

TRACEROUTE utility MG 30-44

transfer qualifiers (positional) UG 3-30

TRANSLATE command  
   X.25 mapping database MG 8-7, MG 8-13, MG 8-15

Transmission Control Protocol (TCP) device driver  
 (TCPDRIVER) services PG 3-1

transmission time  
   min/max, IP-over-X.25 MG 8-3

troubleshooting MG 10-15  
   DECwindows transport interface MG 29-4  
   LPD Server MG 15-13  
   NFS-OpenVMS Client MG 13-28  
   NFS-OpenVMS Server MG 14-31  
   PATHWORKS MG 26-3  
   R Services MG 16-5  
   Serial Line IP (SLIP) MG 5-27  
   Terminal Server Print Services MG 15-20  
   X.25 MG 8-18

TSSYM  
 logicals  
   RETRY\_INTERVAL MG C-27  
   TIMEOUT MG C-27

tunneling UG 16-8

TYPE  
 command keyword value

ASCII UG 3-79  
 BINARY UG 3-79  
 BLOCK UG 3-80  
 DEFAULT UG 3-80  
 FORTRAN UG 3-80  
 IMAGE UG 3-80  
 VARIABLE UG 3-80

type of service (TOS) routing MG 9-54

---

## U

UCX Compatibility Services  
 programming PG 2-1

UCX compatibility services PG 2-1  
 logicals PG 2-3  
 multicasting PG 2-2  
 programming PG 1-7  
 restrictions PG 2-3  
 sample programs PG 2-3

UDP PG 1-3  
 packets, monitoring using TCPDUMP MG 30-28  
 requests MG 3-44

UDP protocol concepts PG 1-3

UDP\_SOCKET\_CLIENT.C file PG 8-3

UDP\_SOCKET\_SERVER.C file PG 8-3

UDPDRIVER Services  
 programming PG 4-1

UDPDRIVER services  
 active ports status PG 4-11  
 assigning channel PG 4-2  
 assigning channel to device PG 4-30  
 asynchronous system trap (AST) PG 4-5  
 call arguments PG 4-3  
 call format PG 4-3  
 cancelling I/O PG 4-32  
 closing a previously opened port PG 4-22  
 closing port PG 4-2  
 deassigning channel PG 4-2  
 function codes PG 4-6  
   IO\$\_READVBLK PG 4-7  
     IO\$\_DATACHECK modifier PG 4-7  
     IO\$\_NOW modifier PG 4-7  
   IO\$\_SENSEMODE PG 4-10  
   IO\$\_SENSEMODE | IO\$\_CTRL PG 4-13  
   IO\$\_SENSEMODE | IO\$\_RD\_COUNT  
     PG 4-16  
     IO\$\_CLR\_COUNT modifier PG 4-16  
   IO\$\_SETMODE | IO\$\_CTRL PG 4-18  
   IO\$\_SETMODE | IO\$\_CTRL |  
     IO\$\_SHUTDOWN PG 4-22  
   IO\$\_SETMODE | IO\$\_CTRL |  
     IO\$\_STARTUP PG 4-23  
   IO\$\_WRITEVBLK PG 4-25  
     IO\$\_NOFORMAT modifier PG 4-25

- IO\$\_WRITEBLK | IO\$\_M\_EXTEND PG 4-28
- IO\$\_M\_NOFORMAT modifier PG 4-28
- SYSS\$ASSIGN PG 4-30
- SYSS\$CANCEL PG 4-32
- SYSS\$DASSGN PG 4-33
- I/O status block PG 4-12
- miscellaneous operations PG 4-2
- opening a port PG 4-2
- opening connection PG 4-23
- performing read requests PG 4-2
- programming PG 1-9
- reading active ports status PG 4-10
- reading port characteristics PG 4-13
- reading UDP counters PG 4-16
- receiving datagram PG 4-7
- releasing channel PG 4-33
- sample program PG 4-34
- sending data, stored in array PG 4-28
- sending datagram PG 4-25
  - suppressing checksum generation PG 4-25, PG 4-28
- set characteristics buffer PG 4-18
- setting the port characteristics PG 4-18
- UDP implementation PG 4-3
- zeroing TCP counters PG 4-16
- UDPDRIVER\_CLIENT.C file PG 4-34
- UDPDRIVER\_SERVER.C file PG 4-34
- UDPSAMPLE.FOR file PG 4-34
- Ungermann-Bass's PC software MG 26-3
- UNMOUNT ALL command NET 2-232
- unsecure connections UG 16-8
- untrusted hosts UG 16-1
- UPDATE GATED INTERFACES command NET 2-234
- user and file protection MG 13-2
- User Datagram Protocol (UDP) device driver (UDPDRIVER) services PG 4-1
- User Identification Mapping MG 13-4
- user name patterns MG 25-7
- user-defined time zone rules IG 3-15
- user-written servers
  - starting IG 6-8

---

## V

- VAX P.S.I.
  - carrier name, X.25 MG 8-6
  - configuration information MG 8-17
- VAX P.S.I. for IP-over-X.25 support IG 2-7
- vendor encapsulated options MG 4-54
- verbose logging MG 25-10
- VIEW command, NSLOOKUP MG 30-20
- virtual
  - links MG 9-62
  - terminals (VTAs) MG 18-4

- VMS UG 3-74
  - print symbiont UG 5-16
- VMS\_PLUS UG 3-45
- VMSLPR Symbiont UG 5-16
- VMSLPR\$MBS
  - logicals
    - PRECONN MG C-27
    - RETRY\_INTERVAL MG C-27
    - TIMEOUT MG C-27, MG C-28

---

## W

- WAN line NET 2-203
- WAYTOOBIG IG 4-42, MG 10-11
- Well Known Services (WKS) record, DNS MG 3-39
- WHOIS UG 15-1
- Wide Area Network (WAN) device drivers IG 3-10
- WIN/TCP
  - logicals PG A-11
  - socket library PG A-10

---

## X

- X display manager
  - configuring IG 4-56
- X Display Manager Server MG 28-1
  - access control MG 28-2, MG 28-3
  - authentication option MG 28-3
  - configuration file MG 28-2
  - enabling debug logging MG 28-2
  - enabling OPCOM logging MG 28-2
  - installation and setup MG 28-1
  - removing the domain name part of the host name MG 28-3
- X.25
  - address MG 8-3, MG 8-4
  - interface MG 8-1
  - mapping database MG 8-1
    - map example MG 8-9
    - route example MG 8-10
    - translate example MG 8-14
  - module characteristics MG 8-17
  - network service MG 8-3
  - protocols MG 8-2
  - record, DNS MG 3-40
  - troubleshooting MG 8-18
- X11 connections MG 25-2
- X25.CONF file
  - example MG 8-14
  - map example MG 8-9
  - multiple entries MG 8-7
  - route example MG 8-10
  - rules MG 8-7



sample MG 8-7, MG 8-15, MG 8-16  
 translate example MG 8-14  
 Xauthority data UG 16-5  
 XDISPLOC UG 12-21, UG 12-62  
 XDM Server MG 28-1  
 XDR encoding and decoding routines PG 19-2  
 XDR routines, upper layer PG 19-4  
 XDR support routines PG 19-3  
 xdr\_accepted\_reply, RPC RTL PG 19-5  
 xdr\_array, RPC RTL PG 19-6  
 xdr\_authunix\_parms, RPC RTL PG 19-7  
 xdr\_bool, RPC RTL PG 19-8  
 xdr\_bytes, RPC RTL PG 19-9  
 xdr\_callhdr, RPC RTL PG 19-10  
 xdr\_callmsg, RPC RTL PG 19-11  
 xdr\_char, RPC RTL PG 19-12  
 xdr\_double, RPC RTL PG 19-13  
 xdr\_enum, RPC RTL PG 19-15  
 xdr\_float, RPC RTL PG 19-16  
 xdr\_free, RPC RTL PG 19-17  
 xdr\_hyper, RPC RTL PG 19-18  
 xdr\_int, RPC RTL PG 19-19  
 xdr\_long, RPC RTL PG 19-20  
 xdr\_netobj, RPC RTL PG 19-21  
 xdr\_opaque, RPC RTL PG 19-22  
 xdr\_opaque\_auth, RPC RTL PG 19-23  
 xdr\_pmap, RPC RTL PG 19-24  
 xdr\_pmaplist, RPC RTL PG 19-25  
 xdr\_pointer, RPC RTL PG 19-26  
 xdr\_reference, RPC RTL PG 19-28  
 xdr\_rejected\_reply, RPC RTL PG 19-29  
 xdr\_replymsg, RPC RTL PG 19-30  
 xdr\_short, RPC RTL PG 19-31  
 xdr\_string, RPC RTL PG 19-32  
 xdr\_u\_char, RPC RTL PG 19-33  
 xdr\_u\_hyper, RPC RTL PG 19-34  
 xdr\_u\_int, RPC RTL PG 19-35  
 xdr\_u\_long, RPC RTL PG 19-36  
 xdr\_u\_short, RPC RTL PG 19-37  
 xdr\_union, RPC RTL PG 19-38  
 xdr\_vector, RPC RTL PG 19-39  
 xdr\_void, RPC RTL PG 19-40  
 xdr\_wrapstring, RPC RTL PG 19-41  
 xdrmem\_create, RPC RTL PG 19-42  
 xdrrec\_create, RPC RTL PG 19-43  
 xdrrec\_endofrecord, RPC RTL PG 19-45  
 xdrrec\_eof, RPC RTL PG 19-46  
 xdrrec\_skiprecord, RPC RTL PG 19-47  
 xdrstdio\_create, RPC RTL PG 19-48  
 XID cache, enabling PG 12-10  
 XNTPDC  
   command line  
     arguments MG 10-32  
     format MG 10-32  
   control message commands MG 10-26  
   interactive commands MG 10-25

runtime configuration requests MG 10-30  
 utility MG 10-17, MG 10-24  
 xprt\_register, RPC RTL PG 18-37  
 xprt\_unregister, RPC RTL PG 18-38

---

## Z

ZONE specification  
   format of IG 3-16

